



Commenced survey at stone with chiseled cross, which I accepted as the $\frac{1}{4}$ corner to sections 1 and 2, T24N R9E. From said $\frac{1}{4}$ corner I ran northerly on a random line and found a 2" capped iron pipe and rock mound which I accepted as the N.W. corner of said section 1, T24N R9E. I then ran easterly on a random line and found a hand hewn post in a rock mound that I accepted as the N. $\frac{1}{4}$ corner of said section 1, T24N R9E. I thence continued easterly on a random line and found a rock mound with a hand hewn post that I accepted as the N.E. corner to said section 1, T24N R9E.

I then commenced again at $\frac{1}{4}$ corner to sections 1 and 2, T24N R9E. I thence ran southerly on a random line for approximately $\frac{1}{2}$ mile and after making a careful search I was unable to find the S.W. corner of said section 1, T24N R9E. I thence ran easterly on a random line for approximately $\frac{1}{2}$ mile and after careful search I was unable to find the south $\frac{1}{4}$ corner of said section 1, T24N R9E. I thence continued easterly for approximately $\frac{1}{2}$ mile and found a fence corner. I tied in said fence corner and after talking to Mr. Watson, the county surveyor, I accepted this fence corner as being the S.E. corner of said section 1, T24N R9E. I thence ran northerly on a random line and found a $\frac{1}{2}$ " plugged iron pipe from which a 36" blazed pine tree bears N31°10'E 29.7 feet I accepted said $\frac{1}{2}$ " plugged iron pipe as the east $\frac{1}{4}$ corner of said section 1, T24N R9E. I thence continued northerly on a random line and closed my traverse at the N.E. corner of said section 1, T24N R9E.

I then commenced at a traverse point near the S.W. corner of section 1, T24N R9E and ran westerly on a random line for approximately $\frac{1}{2}$ mile and after a careful search was unable to find the south $\frac{1}{4}$ corner of section 2, T24N R9E. I then continued west on a random line and found a 1" iron pipe set in a rock mound from which a 30" blazed pine tree bears S41°50'W 60.9 feet and a 24" blazed pine tree bears S19°40'E 45.6 feet. I accepted the 1" iron pipe in the rock mound as being the S.W. corner of section 2, T24N R9E.

In accepting the corners referred to above, I was guided by a conversation with Mr. A.J. Watson, County Surveyor, Plumas County, California

NOTE: The basis of bearings of this survey is the East line of the N.E. $\frac{1}{4}$ of Section 1, T24N R9E M.D.B. & M. which equals North.

RECORD OF SURVEY
FOR
ELIZABETH E. WAUGH

BEING A PORTION OF THE W. $\frac{1}{2}$ OF THE S.W. $\frac{1}{4}$ OF THE N.W. $\frac{1}{4}$ OF SEC. 1 T24N R9E M.D.B. & M. AND A PORTION OF THE SE. $\frac{1}{4}$ OF THE N.E. $\frac{1}{4}$ OF THE N.E. $\frac{1}{4}$ OF SEC. 2 T24N R9E M.D.B. & M.

APRIL 1958
PLUMAS COUNTY

SCALE: 1" = 400'
CALIFORNIA

NOTE:
• Solid points indicates MHM. marker set. ($\frac{3}{4}$ " iron pin with 2" brass disc fixed at top)

RECORDED AT REQUEST OF
Plumas County Abstract and Title Company
DEC. 31. 1958
AT 34 MIN PAST 12 M
VOL 2 PAGE 7
RECORD OF SURVEY
PLUMAS CO. C&L RECORDS

W. E. Hogan
RECORDER
500

Sec Cor Fd. 1" Iron Pipe in Rock Mound.
S.W. Cor. Sec. 2
S89°42'13"W 5281.49'

I, Leonard E. Bowser, do hereby certify that I am a Licensed Land Surveyor of the State of California, that the map delineated hereon correctly represents a survey made by me in April 1958 and all monuments shown hereon are of the character and occupy the positions indicated and are sufficient to enable the survey to be retraced.

Leonard E. Bowser
Licensed Land Surveyor N°2684

I, A. J. Watson, County Surveyor of the County of Plumas, State of California, do hereby certify that I have examined this map and found it to be technically correct and to comply with the provisions of Chapter 15, Division 3, of the Business and Professions Code.
Dated: 7/10/58

A. J. Watson RE. N° 2554
County Surveyor, County of Plumas,
State of California.