

35/36
2/1
FD 40' FIR BT. (SNAG) S. 4° E. 31.7'
FD 40' FIR BT. N 60° W 49.5'
FD 30' FIR BT. N 28° E 45.5'

1/4 36
FD L.P. PINE BT S 83° E. 46.9'

36/31
1/6
FD 30' CEDAR BT S 8° E. 25.1'
FD 19' CEDAR BT (SNAG) N 29° E 19.1'
FD 31' CEDAR BT N 13° W. 32.7'

1/4 31
6
FD REMAINS OF WOODEN POST IN
LARGE MOUND OF STONES
SET 2" I.P./BRASS CAP - L.S. 3621
MKD. 28" W FIR S. 25° W. 19.0'

31/32
6/5
SET 2" I.P./3" BRASS CAP - L.S. 3621
BY G.L.O. CALLS: THERE IS AN
APPARENT ERROR IN THE G.L.O.
DISTANCE ALONG THE TOWNSHIP
LINE. IN CHECKING THE CALLS
TO THE TOPOGRAPHY IT WAS FOUND
THAT THE DISTANCE BETWEEN A
LARGE ROCK EAST OF THE 1/4 31
AND THE FOUND EVIDENCE AT
THIS CORNER WAS WITHIN THE
ALLOWABLE DIFFERENCE, BUT
THE DISTANCE EAST TO THE TOP
OF THE RIDGE WAS APPROX. 6 CH.
SHORT. THE TOPO CALLS FIT VERY
GOOD FROM THE RIDGE EASTERLY.
I THEREFOR DID NOT PROPORTION
TO SET THIS LOCATION, BUT SET
IT AT G.L.O. CALL FROM THE RIDGE
AND PLACED IT ON LINE BETWEEN
FOUND CORNERS.
MKD 10" W FIR WEST 10.2'
MKD 9" W FIR N 44° W. 24.0'
MKD 12" W FIR N 18° E 22.8'

1/4 32
5
SET 2" I.P./3" BRASS CAP - L.S. 3621
BY SINGLE PROPORTION
MKD. 12" W FIR N 75° E. 10.5'
MKD 15" W FIR S 85° W 19.9'
MKD 12" W FIR S 2° W. 13.7'

32/33
5/4
FD SCB'D POST IN STONE MD
FD FIR BT. (STUMP) N 54° E. 25.1'
FD FIR BT. (STUMP) S 75° E 40.9'
(SCB'D "B" FD JUST BELOW CUT)
MARKED: 15" S PINE S 26° E. 16.8'
14" W FIR S 40° W. 12.9'
8" W FIR S 86° E. 11.8'
SET 2" I.P./3" BRASS CAP L.S. 3621

1/4 33
4
FD STONE MD
FD REMAINS OF Y PINE TO THE
S.W. NEAR THE LOCATION CALLED
FOR BT., THIS POSITION FITS
TOPO CALLS
SET 2" I.P./3" BRASS CAP L.S. 3621
MARKED: 11" W FIR N 16° E. 5.4'
22" Y. PINE S 84° E 4.8'

33/34
4/3
FD 33" Y PINE BT S 10° E. 52.1'
FD 33" Y PINE BT. S 26° W. 61.4'
FD 9" Y PINE BT N 18 1/2° E 12.5'
FD 10" W FIR BT. N 62° W. 24.4'

1/4 2 1
SET 2" I.P./3" BRASS CAP L.S. 3621
BY SINGLE PROPORTION
MARKED: 9" Y. PINE N 52° E 24.0'
8" W FIR S. 74° W 3.3'

CENTER 1/4 SECTION 1
SET 2" I.P./BRASS CAP L.S. 3621
MARKED: 17 1/2" CEDAR N. 35° E. 25.9'
W. FIR S 17° W 20.0'

1/4 1 6
FD 27" W FIR BT N 88° E. 3.96'
FD STONE MD. SET 2" I.P./BRASS CAP
MARKED 21" W FIR N 46° E. 23.0'
11" R FIR S 80° W 45.5'
SINCE RECOVERY ORIG G.L.O. BT HAS FALLEN DOWN.

WEST CENTER 1/16 SECTION 6
COR FALLS IN WILLOW LAKE
SET W.C. S 0° 18' 09" E. 117.3'
MARKED: 22" W. FIR S 35° E. 3.7'

CENTER 1/4 SECTION 6
SET 3/4" I.P. L.S. 3621
MARKED: 18" W FIR N 40° E. 13.4'
16" W FIR S 8° E. 5.8'

EAST CENTER 1/16 SECTION 6
SET 3/4" I.P. L.S. 3621
MARKED: 18" CEDAR N. 75° W. 8.8'
17" CEDAR S 82° E. 23.5'

1/4 6 5
FD. 24" CEDAR BT. S. 1/2° W. 104.9'
FD. 20" W. FIR N. 58 1/2° W. 27.7'
FD 16" W. FIR S 83 1/2° E. 53.1'

1/4 5 4
SET 2" I.P./3" BRASS CAP L.S. 3621
BY SINGLE PROPORTION
MARKED: 7" W. FIR S 78° E 5.0'
13" W FIR N 87° W 9.0'

S.W. 1/16 SECTION 6
SET 3/4" I.P. L.S. 3621
MARKED: 11" W FIR EAST 9.1'
13" W FIR N 87° W. 10.5'

S.E. 1/16 SECTION 6
SET 3/4" I.P. L.S. 3621
MARKED 14" L.P. PINE N 30° W 17.2'
14" L.P. PINE S 70° W. 25.3'

S. 1/16 6 5
SET 3/4" I.P. L.S. 3621
MARKED: 8" W FIR S 75° E 5.7'
9" W FIR N 47° W 7.0'

S.W. 1/16 SEC 5
SET 3/4" I.P. L.S. 3621
MARKED: 12" W FIR S 75° W 18.3'

4/9
3/10
T 29 N R 5 E.
FD. 28" Y. PINE BT S 28° W 79.9'
FD 7" CEDAR BT. S 26° E. 56.8'
FD 8" W. FIR BT. N 2° W. 94.1'
FD 31" Y PINE BT N 39° E 29.7'

2/11
1/12
SET 2" I.P./3" BRASS CAP L.S. 3621
BY DOUBLE PROPORTION
MARKED: 13" W FIR S. 19° E. 20.7'
14" W FIR N 6° W. 8.4'
12" W FIR S 69° W. 16.7'
12" W FIR N 26° E 28.7'

1/4 1 12
SET 2" I.P./3" BRASS CAP L.S. 3621
BY SINGLE PROPORTION
MARKED: 7" CEDAR N 18° E. 41.9'
8" Y. PINE S 48° W. 36.4'

1/12
6/7
FD 46" W FIR BT. N 27° W 50.2'
FD 32" Y. PINE BT. S 40° W 95.0'
FD. 6" W FIR BT. (NEW) S 20° E. 46.1'
FD 6" W FIR BT. (NEW) N 12° E. 18.2'

1/4 6 7
SET 2" I.P./3" BRASS CAP L.S. 3621
BY SINGLE PROPORTION
MARKED: 12" W FIR S 24° E 24.6'
9 1/2" Y PINE N 33° W. 26.6'

E. 1/16 6 7
SET 3/4" I.P. L.S. 3621
MARKED: 6" Y PINE N 20° W. 78.4'
28" CEDAR N 29° W 30.2'

6/7
5/8
FD 15" W. FIR BT S 27° W. 61.4'
FD 8" Y PINE BT. N 32 1/2° W 132'
FD 26" CEDAR BT N 1° E 172.3'

W. 1/16 5 8
SET 3/4" I.P. L.S. 3621
COR FALLS ON EDGE OF ROAD
MARKED: 15 1/2" CEDAR N 68° W 20.0'
18" W FIR S 6° W 16.4'

1/4 5 8
SET 2" I.P./3" BRASS CAP L.S. 3621
BY SINGLE PROPORTION
MARKED: 21" W. FIR S 7° E. 52.6'
8" S PINE N 15° W. 37.8'

5/8
4/9
SET 2" I.P./3" BRASS CAP L.S. 3621
BY DOUBLE PROPORTION
MARKED: 7 1/2" CEDAR S 75° W. 27.2'
17" W FIR N 44° W. 35.0'
7 1/2" CEDAR N 12° E 34.0'

1/4 4 9
FD. 34" Y PINE BT. N. 73° W. 43.6'
FD 12" W. FIR BT N 78° W 38.9'
FD. 8" W. FIR BT. S. 24° W. 48.5'

NE 1/16 SEC. 7
SET 3/4" I.P. L.S. 3621
MARKED: 13" W. FIR S 15° E. 15.7'
23" W. FIR N 35° W. 1.5'

NORTH 1/16 7 8
SET 3/4" I.P. L.S. 3621
MARKED: 16" CEDAR N 60° E. 10.2'
11" W. FIR S. 45° W. 8.0'

N.W. 1/16 SEC. 8
SET 3/4" I.P. L.S. 3621
MARKED: 11" L.P. PINE S 50° W. 31.4'
9" L.P. PINE N 25° E 9.8'

1/4 12 7
SET 2" I.P./3" BRASS CAP L.S. 3621
BY SINGLE PROPORTION
MARKED 23" R FIR N 47° W 13.3'
18" W FIR S 64° E. 58.8'

1/4 7 8
SET 2" I.P./3" BRASS CAP L.S. 3621
BY SINGLE PROPORTION
MARKED: 11" CEDAR N 40° W. 15.8'
14" CEDAR S 38° E. 39.4'

1/4 8 9
SET 2" I.P./3" BRASS CAP L.S. 3621
BY SINGLE PROPORTION
MARKED: 9" CEDAR S 33° E. 13.4'
8" W FIR S 82° W. 27.0'

11/14
12/13
FD. 9" W FIR BT. N 41 1/2° E. 11.2'
FD 6" W. FIR BT N 42° W. 37.6'
FD 46" Y. PINE BT. N 72° W 52.8'
FD 6" Y. PINE BT. S. 9° W. 67.3'
FD 19" Y PINE BT S 2° E. 34.3'

12/13
7/18
FD 46" Y PINE BT. N 2° E 46.2'
FD. 36" S PINE BT. N 53° W. 52.5'
FD 6" W FIR BT. S 76° W. 35.0'
FD. 9" W FIR BT. N 59° W. 39.6'
FD. 14" W FIR BT S. 34° E. 29.0'
FD. 22" W. FIR BT N. 75 1/2° E 21.1'

1/4 7 18
FD 36" L.P. PINE BT (SNAG) S. 45° W 3.3'
FD. 5" R. FIR BT S. 5° E 32.3'
FD 12" R. FIR BT. N 63 1/2° E 24.4'

7/18
8/17
FD. 33" W FIR BT. N 51 1/2° E. 54.8'
FD 10" W FIR BT. S 55° E. 17.5'
FD 9" W FIR BT. N 69 1/2° E. 8.6'
FD 12" CEDAR BT N 31° W 15.2'
FD 12" W FIR BT. S 65 1/2° W. 39.6'

8 17
SET 2" I.P./3" BRASS CAP L.S. 3621
BY SINGLE PROPORTION
MARKED: 13" Y PINE N. 53° W 3.5'
13 1/2" Y. PINE S. 10° E 21.8'

8 17
9 16
FD 20" Y PINE BT. N 4° W. 26.4'
FD 11" Y. PINE BT. N 56 1/2° E. 35.0'
FD 11" W. FIR BT. S 31° W. 82.5'
FD. 8" W FIR BT N 45° W 29.4'

LEGEND

- ◆ INDICATES. FOUND CORNER AS NOTED
- ◇ INDICATES: FOUND U.S. DEPT. INTERIOR BRASS CAP
- INDICATES: SET 2" I.P./3" BRASS CAP - L.S. 3621
- INDICATES: SET 3/4" I.P. L.S. 3621.

CORNER NOTES

RECORD OF SURVEY
OF PORTIONS OF
SECTIONS 5,6,7,8 T.29N.R.6E.M.D.M. AND SECTION 1 T.29N.R.5E.M.D.M.
PLUMAS COUNTY, CALIFORNIA
FOR
U.S. FOREST SERVICE AND BROOKS WALKER ET AL
OCTOBER 1974
RODNEY D. DAWSON - L.S. 3621

Rodney Dawson