

1. NW 1/4 COR SEC 18
FOUND ORIG STONE 17" x 12" x 6" ON NORTH SIDE OF ROCK MOUND MARKED "1/4" ORIG BT, 5 1/2" DBH W FIR BEARS N 5° W ~ 396' (N 7° W ~ 3168') MONUMENT APPEARS UNDISTURBED ACCEPTED AS ORIG POSITION & SET STD USFS MONUMENT STAMPED APPROPRIATELY NEW BT, A 17" W FIR, BEARS S 26° W ~ 24 75'.
2. NW COR SEC 18
FOUND ORIG CLOSING CORNER TO SECS 7 & 18 A 14" DBH BL OAK W/ BLM BRASS CAP ALONGSIDE MARKED:

T 21N	R 8E
T 21N	R 7E
R 7 1/2 E	S 7C
S 7	S 18C
1928	
3. SE COR SEC 7
FOUND BLM BRASS CAP MARKED:

T 21N	R 8E
T 21N	R 7E
R 7E	S 12
S 12	S 18
S 13	S 18
4. E 1/4 COR SEC 13
FOUND ROCK MOUND FROM WHICH RECENTLY CUT STUMP OF A 39" BL OAK BEARS WEST ~ 205' (WEST ~ 2046') AND A BL OAK LOG 14" DIA BEARS APPROX N 67° E ~ 41' (N 77° E ~ 40.92') A LOCAL BT, A 20" CEDAR SCRIBED "1/4 SBT" ABOUT 1948, BEARS S 22° E ~ 11 2'. SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T., A 22" FIR, BEARS N 64° W ~ 25.5'.
5. SW COR SEC 18
FOUND ORIGINAL STONE MONUMENT MARKED AS DESCRIBED IN HALL'S GLO NOTES FOUND STUMP OF ORIG FIR BT W/SCRIBING VISIBLE S 86° E ~ 22 3' ± (N 89° E ~ 2046') FOUND STUMP HOLE OF ORIG FIR BT. S 65° E ~ 25 7' ± (S 67° E ~ 2376') NEW BT'S N 58° 30' E ~ 42 6' TO A 18" FIR, S 22° 45' E ~ 47 8' TO A 15" FIR. SET STD USFS MONUMENT STAMPED APPROPRIATELY
6. SE COR SEC 13
FOUND ROCK MOUND FROM WHICH ORIG W FIR BT BEARS N 31° 30' W ~ 36 3' (N 32° W ~ 36 3') FIR STUMP W/VISIBLE SCRIBING BEARS N 58° E ~ 58 0' (N 57° E ~ 574'). FIR STUMP W/VISIBLE SCRIBING BEARS S 28° 30' E ~ 29 7' (S 30° E ~ 297') ROTTED FIR STUMP W/INVERSE SCRIBING BEARS S 71° W ~ 58 ± (S 71° W ~ 58 08') NEW BT'S N 66° 45' W ~ 27 1' TO 16" FIR, S 28° 45' W ~ 46 7' TO 27" PINE SET STD USFS MONUMENT STAMPED APPROPRIATELY
7. SE COR SEC 18
FOUND STD USFS MONUMENT PER RECORD OF SURVEY IN BOOK 5 OF RECORDS OF SURVEYS, PAGES 37, 38 & 39
8. S 1/4 COR SEC 18
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW BT'S BEAR N 10° 15' W ~ 22 5' TO 22" FIR, AND S 59° 45' E ~ 16 7' TO 14" OAK
9. E 1/4 COR SEC. 18
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW BT'S BEAR N 63° W ~ 16 3' TO 10" PINE, AND S 29° E ~ 13 0' TO 10" FIR
10. NE COR SEC 18
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW BT'S BEAR N 30° W ~ 59 4' TO 12" CEDAR, N 38° E ~ 16 0' TO 18" FIR, S 21° E ~ 37 2' TO 20" FIR, AND S 72° W ~ 28 6' TO 15" FIR (NOTE: THE SCRIBING FOR TOWNSHIP AND RANGE [T 21N R 8E] IS MARKED READING FROM BOTTOM TO TOP ON ALL TREES)
11. NW 1/4 COR SECS 7 & 18
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW BT'S BEAR N 74° W ~ 10 3' TO 18" W FIR, AND S 79° E ~ 36 0' TO 14" CEDAR
12. CW 1/4 COR SEC 18
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW BT'S BEAR N 32° W ~ 13 8' TO 16" S PINE, AND N 81° E ~ 11 4' TO 15" W FIR

13. CTR SEC 18
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW BT'S BEAR N 4° W ~ 38 0' TO 18" FIR, AND S 24° E ~ 19 0' TO 12" CEDAR.
14. NW 1/4 COR SEC 24
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FOR CORNER S 72° E ~ 11 2' FROM STUMP OF ORIG BT W/SCRIBING, A 46" FIR (S 72° E ~ 11 2') STUMP HOLE BEARS S 64° E ~ 19 8' ± (S 64° E ~ 19 8'). NEW BT'S S 28° 15' E ~ 20 8' TO 18" S PINE, AND N 50° W ~ 18 7' TO 20" S PINE
15. W 1/4 COR SEC 24
FOUND STONE MOUND FROM WHICH THE STUMP OF A 40" FIR WITH SCRIBING VISIBLE (TREE WAS 24" AT THE TIME OF SCRIBING) BEARS N 87° W ~ 23' (RECORD = A 24" FIR S 87° E ~ 23 1'). SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW BT'S BEAR S 67° W ~ 16 3' TO 10" S PINE, N 50° 30' E ~ 49' TO 10" CEDAR
16. SW COR SEC. 24
FOUND STONE MOUND FROM WHICH CEDAR STUMP BEARS S 48° 30' E ~ 32 ± (S 50° E ~ 36 3') SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW BT'S BEAR S 59° E ~ 48 7' TO 21" PINE, S 62° W ~ 47 9' TO 25" ALDER, N 62° W ~ 56.6' TO 20" ALDER, AND N 72° E ~ 36.6' TO 18" PINE.
17. SW COR SEC 19
FOUND STD USFS MONUMENT PER RECORD OF SURVEY IN BOOK 5 OF RECORDS OF SURVEYS, PAGES 37, 38 & 39
18. SE COR SEC 24
FOUND STD USFS MONUMENT PER RECORD OF SURVEY IN BOOK 5 OF RECORDS OF SURVEYS, PAGES 37, 38 & 39
19. S 1/4 COR SEC 24
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW BT'S BEAR N 1° 30' W ~ 47 6' TO A 14" PINE, AND S 30° W ~ 13 7' TO A 15" PINE
20. E 1/4 COR SEC 24
FOUND 50" CEDAR BT W/OPEN FACE AND VISIBLE SCRIBING CORNER FALLS IN MAIN CHANNEL OF FALL RIVER POSITION DETERMINED FROM BT, NO CORNER SET
21. NE COR LOT 37B "MILL SITE" (SEC 24)
SET STD USFS MONUMENT STAMPED:

LOT 2	S 19
LOT 37B	T 21N R 8E
S 24	
T 21N R 7E	
1980	
LS 3761	
22. NW 1/4 COR SECS 19 & 24
SET STD USFS MONUMENT STAMPED:

T 21N	T 21N
NW 1/4 S 24	S 19
R 7 E	R 8 E
1980	
LS 3761	
23. NW COR LOT 37B "MILL SITE" (SEC 24)
SET STD USFS MONUMENT STAMPED:

LOT 2	LOT 37B
T 21N R 7E	T 21N R 7E
S 24	S 19
1980	
LS 3761	
24. SW COR LOT 37B "MILL SITE" (SEC 24)
SET STD USFS MONUMENT STAMPED:
BEARING OBJECTS: S 47° W ~ 27 05' TO "+ 80"

LOT 2	LOT 37B
T 21N R 7E	T 21N R 7E
S 24	S 19
1980	
LS 3761	

CHISELED ON TOP OF N'LY. EDGE OF 6' x 7' x 30" BOULDER ON EAST SIDE OF FALL RIVER; N 34° 30' W ~ 61 85' TO "+ 80"
CHISELED ON TOP CENTER OF 42" x 18" ABANDONED BRIDGE PIER ON WEST SIDE OF FALL RIVER

25. SW COR LOT 2 (SEC 24)
SET STD USFS MONUMENT STAMPED:

LOT 2	T 21N R 7E
NEW BT'S: N 79° 30' W ~ 94' TO 26" CEDAR	S 24
SCRIBED "LOT 37A - BT"	1980
N 84° 15' E ~ 26 5' TO 13" FIR	LS 3761
SCRIBED "LOT 2 - BT"	
26. NE'LY COR LOT 37A (SEC 24)
FOUND MOUND OF ROCKS (ORIGINAL CORNER)
SET STD USFS MONUMENT STAMPED:

LOT 2	T 21N R 7E
NEW BT'S: N 37° 30' E ~ 23 0' TO 11" PINE	S 24
SCRIBED "FR 3 2874 LOT 2 - BT"	1980
N 65° W ~ 15 3' TO 14" PINE	LS 3761
SCRIBED "FR 3 2874 LOT 37A - BT"	
27. NW'LY COR LOT 2 (SEC 24)
SET STD USFS MONUMENT STAMPED:

LOT 2	T 21N R 7E
NEW BT'S: S 71° 15' E ~ 31 3' TO 13" FIR	S 24
SCRIBED "LOT 2 - BT"	1980
S 8° E ~ 15 1' TO 16" CEDAR	LS 3761
SCRIBED "LOT 37A - BT"	
28. NW'LY COR LOT 37A (SEC 24)
FOUND ORIGINAL ROCK MOUND CORNER FROM WHICH ORIG BT, A 15" BL OAK, BEARS N 69° E ~ 27 0' (12" BL OAK, N 68° 54' E ~ 27 06')
29. SE'LY COR LOT 37A (SEC 24)
FOUND ORIGINAL ROCK MOUND CORNER FROM WHICH ORIG BT, A 27" BL OAK, BEARS N 28° 40' W ~ 16 5' (24" BL OAK, N 28° 40' W ~ 16 5'), AND A 15" BL OAK BEARS S 35° 30' W ~ 6 0' (12" BL OAK, S 35° 30' W ~ 5 94') SET 3/4" IRON PIPE TAGGED LS 3761.
30. N'LY COR LOT 5 (SEC 24)
SET STD USFS MONUMENT STAMPED:

LOT 5	T 21N R 7E
NEW BT'S: N 47° 15' W ~ 13 8' TO 18" FIR	S 24
SCRIBED "LOT 38 - BT"	1980
N 62° 30' E ~ 57 9' TO 20" PINE	LS 3761
SCRIBED "S 24 - BT"	
31. SW COR LOT 5 (SEC 24)
SET STD USFS MONUMENT STAMPED:

LOT 5	T 21N R 7E
NEW BT'S: N 67° 45' E ~ 70 1' TO 13" CEDAR	S 24
SCRIBED "LOT 5 - BT"	1980
S 74° 45' W ~ 34 5' TO 12" PINE	LS 3761
SCRIBED "LOT 38 - BT"	
32. SE COR LOT 5 (SEC 24)
SET STD USFS MONUMENT STAMPED:

SE	1/16
S 79° E ~ 36 5' TO 16" FIR	S 24
SCRIBED "SE 1/16 S 24 - BT"	T 21N R 7E
N 48° 30' W ~ 24 1' TO 12" PINE	1980
SCRIBED "1/16 LOT 5 - BT"	LS 3761

Record of Survey

FOR
LOUISIANA-PACIFIC CORPORATION
& THE UNITED STATES FOREST SERVICE
 LYING WITHIN SECTION 24, T. 21 N., R. 7 E., AND SECTIONS
 9, 17, AND 18, T. 21 N., R. 8 E., M.D.B. & M., PLUMAS COUNTY, CA.

PREPARED BY
 VON GELDERN ENGINEERING CO.
 430 SECOND ST., YUBA CITY, CA.
 AUGUST 1980