


- 33 SW COR LOT 38 (SEC 24)
FOUND ORIG ROCK MOUND CORNER FROM WHICH ORIG BT, A 20" BL OAK, BEARS N 50° 20' E ~ 41 0' (16" BL OAK, N 50° 20' E ~ 40 92') SET 3/4" IRON PIPE TAGGED LS 3761.
- 34 SE COR LOT 38 (SEC 24)
ORIGINAL CORNER DESTROYED BY LOGGING. SET 3/4" IRON PIPE TAGGED LS 3761.
- 35 W 1/16TH COR SECS 17 & 20
FOUND STD USFS MONUMENT PER RECORD OF SURVEY IN BOOK 5 OF RECORDS OF SURVEYS, PAGES 37, 38 & 39
- 36 S 1/4 COR SEC 17
FOUND STD USFS MONUMENT PER RECORD OF SURVEY IN BOOK 5 OF RECORDS OF SURVEYS, PAGES 37, 38 & 39
- 37 S 1/16TH COR SECS 17 & 18
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR S 73° 50' E ~ 135' TO 14" W FIR, S 50° 46' W ~ 6.0' TO 15" CEDAR.
- 38 SW 1/16TH COR SEC 17
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR S 87° 30' E ~ 15 2' TO 11" BL OAK, S 5° 09' E ~ 22 0' TO 16" W FIR.
- 39 CW 1/16TH COR SEC. 17
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 54° 30' E ~ 21 5' TO 13" CEDAR, S 20° 30' E ~ 25 9' TO 15" BL OAK
- 40 NW 1/16TH COR SEC. 17
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 20° E ~ 105' TO 17" W FIR, S 68° E ~ 9 6' TO 14" CEDAR.
- 41 W 1/16TH COR SECS 8 & 17
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 33° 30' W ~ 54.8' TO 22" CEDAR, S 52° 15' W ~ 59 8' TO 19" PINE
- 42 CN 1/16TH COR SEC 17
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 44° 06' W ~ 33 5' TO 22" POND PINE, S 39° 50' W ~ 38.7' TO 12" W FIR
- 43 N 1/4 COR SEC 17
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 30° 06' W ~ 23 0' TO 18" CEDAR, S 58° 14' W ~ 19 5' TO 15" W FIR
- 44. E 1/4 COR SEC 17
FOUND 5" x 7" x 11" STONE SCRIBED "1/4" ON WEST EDGE OF LARGE ROCK MOUND SET STD U.S.F.S MONUMENT, APPROPRIATELY STAMPED, AT S 56° 40' W ~ 574' FROM ORIG BT, A 30" POND PINE W/ VISIBLE SCRIBING (S 50° W ~ 5742'). NEW BT, AN 11" CEDAR, BEARS N 71° 45' W ~ 77 50'
- 45 NE COR SEC 17
SET STD U.S.F.S MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR S 69° 45' E ~ 30.7' TO 22" PINE, S 40° 45' W ~ 65 2' TO 23" FIR, N 80° 30' W ~ 6 2' TO 17" FIR, N 57° E ~ 38' TO 15" FIR
- 46 W 1/4 COR SEC 9
FOUND 16" x 10" x 9" STONE WITH "1/4" SCRIBED ON FACE ON WEST SIDE ROCK MOUND FROM WHICH STUMP OF ORIG BT, A 38" FIR WITH FULL SCRIBING, BEARS S 60° W ~ 8 0' (S 60° W ~ 792'). SET STD U.S.F.S MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 70° W ~ 20.5' TO 14" CEDAR, S 69° 30' E ~ 4 0' TO 22" FIR.
- 47. NW COR SEC 9
FOUND ORIGINAL ACCESSORIES TO CORNER. A 30" S. PINE CUT STUMP WITH SCRIBING VISIBLE (14" SP), AND A 20" S PINE STUMP W/TREE ALONGSIDE WITH SCRIBING VISIBLE (10" S PINE) NO PERMANENT CORNER SET; POSITION ESTABLISHED FROM B.T.'S.

- 48 NE COR SEC 9
FOUND 18" x 10" x 8" STONE IN ROCK MOUND, FROM WHICH A 68" FIR STUMP WITH SCRIBING VISIBLE BEARS N 16° E ~ 68' (N 16° E ~ 67 98' TO 26" FIR), A 41" W FIR WITH SCRIBING VISIBLE BEARS N 18° 30' W ~ 84' (N. 18 1/2° W ~ 91.74' TO 16" FIR), AND A 54" FIR BEARS S 21° 30' E ~ 105' (S 21 1/2° E ~ 101 64' TO 24" FIR)
- 49 SE COR SEC 9
FOUND A 3/4" IRON PIPE IN ROCK MOUND FROM WHICH A 42" S PINE STUMP WITH VISIBLE SCRIBING BEARS S 50° E ~ 15 2' (S 50° E ~ 15 18' TO 42" S PINE), AND A 50" FIR STUMP WITH SCRIBING VISIBLE BEARS N 80° E ~ 43 6' (N 80° E ~ 42 24' TO 45" SPRUCE). SET STD U.S.F.S MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 67° W ~ 41 7' TO 23" FIR, N 65° E ~ 44 4' TO 14" FIR, S 61° 30' E ~ 63.6' TO 11" FIR, AND S 24° W ~ 44 8' TO 24" CEDAR
- 50 S 1/4 COR SEC. 9
FOUND A 20" x 20" x 12" STONE WITH "1/4" SCRIBED ON FACE ALONGSIDE A ROCK MOUND. SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW BT, A 7" FIR, BEARS N 2° W ~ 169 0' A 36" DIA BOULDER WITH " + B O " SCRIBED ON TOP BEARS S 12° 45' E ~ 4.11'
- 51 W 1/16TH COR SECS. 9 & 16
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 2° 30' E ~ 63' TO 26" CEDAR, S 35° 45' W ~ 24 5' TO 13" CEDAR.
- 52 S 1/16TH COR SECS 8 & 9
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 44° 15' W ~ 46 4' TO 19" FIR, N 17° 30' E ~ 34 5' TO 17" CEDAR
- 53 SW 1/16TH COR SEC 9
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR S 59° 15' W ~ 64' TO 12" FIR, N 49° 45' E ~ 29 0' TO 14" FIR.
- 54 CS 1/16TH COR SEC 9
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 51° 15' E ~ 14 2' TO 10" FIR, S 45° 45' E ~ 23.7' TO 9" FIR.
- 55 SE 1/16TH COR SEC 9
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR S 5° 45' W ~ 9 8' TO 15" FIR, N 43° W ~ 14 0' TO 14" CEDAR
- 56. E 1/16TH COR SECS 9 & 16
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 17° W ~ 17 7' TO 12" FIR, S 37° 30' W ~ 24 0' TO 14" BL OAK.
- 57 N 1/4 COR SEC 9
SET STD. USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 31° 30' E ~ 4 3' TO 22" CEDAR, S 1° 30' W ~ 77' TO 17" FIR.
- 58. E 1/4 COR SEC 9
SET STD USFS MONUMENT, APPROPRIATELY STAMPED, FROM WHICH NEW B.T.'S BEAR N 77° W ~ 25 1' TO 14" FIR, S 72° 15' E ~ 8.5' TO 11" FIR.

- 59 W 1/4 COR SEC 8
FOUND ORIGINAL CORNER, A 42" POND PINE, DEAD SNAG, WITH "1/4 S" MARKED ON WEST FACE AND 2 NOTCHES ON NORTH & SOUTH SIDES, FROM WHICH A 10" BL OAK WITH CLOSED FACE BEARS N 30° W ~ 24' (N 30° W ~ 23.76' TO 7" BL OAK), AND A 31" CEDAR WITH CLOSED FACE BEARS S 8° 45' E ~ 25 0' (S 8 3/4° E ~ 23 76' TO 14" CEDAR.) SET STD USFS MONUMENT FOR WITNESS CORNER NORTH 5 00' OF TRUE CORNER STAMPED:



FROM WHICH NEW B.T.'S BEAR N 42° 45' E ~ 27 8' TO 14" CEDAR, SCRIBED "X" @ CHEST HEIGHT AND "B.T." @ BASE, S 89° 30' W ~ 17 6' TO 14" FIR SCRIBED "X" @ CHEST HEIGHT AND "B.T." @ BASE.

Record of Survey

FOR
LOUISIANA - PACIFIC CORPORATION
& THE UNITED STATES FOREST SERVICE
 LYING WITHIN SECTION 24, T. 21 N., R. 7 E., AND SECTIONS
 9, 17, AND 18, T. 21 N., R. 8 E., M.D.B. & M., PLUMAS COUNTY, CA.

PREPARED BY
 VON GELDERN ENGINEERING CO.
 430 SECOND ST., YUBA CITY, CA.
 AUGUST 1980