

CORNER NOTES

- (GLO₁, GLO₄) Post, 8" B. Oak, N83 3/4°E, 24 Lks., 17" S. Pine, S15°W, 26 Lks., 40" Spruce, N17°E, 26 Lks.; 28" Fir, N27°E, 59 Lks.
- 1/4 C 31 32
- FD a 3/4" IP, 24" long in M.O.R. 3' dia. & 1' high from which a rotted 1 1/8" D. Fir stump w/ remains of scribing bears N31°E, 59 Lks. to face, 61 1/2 Lks. to center a 1 1/2" 30" D. Fir stump rotted level with ground bears N10°E, 26 Lks.; & a stump hole 1 1/2" S15°W, 1 1/2" 26 Lks. I scribe a 14" Cedar "SC T21N R8E S31 BT", bears N19°W, 37 1/2 Lks., a 21" S. Pine "SC T21N R8E S32 BT", bears N55°E, 27 1/2 Lks.
- 7 36 31
- (GLO₁, GLO₄) Post 27" Spruce, S85 3/4°E, 31 Lks., 50" S. Pine N37°W, 34 Lks., 4" B. Oak N29 1/4°E, 112 Lks.
- (GLO₃) 20"x10"x6" stone 76" S. Pine, N23°W, 47 Lks., 12" Spruce, N76°45'W, 46 Lks.
- FD 16"x7"x4" scribed stone 6 grooves on East, West & North sides & SC on North; from which bears 47" D. Fir with healed scar, S86°E, 32 Lks., to center; 60" S. Pine stump rotted, N37°W, 39 Lks. to center, 96" S. Pine stump with scribe, N20°W, 51 Lks. to center. I scribe a 13" S. Pine, N56°E, 29 1/2 Lks. "SC T21N R8E S31 BT", & a 22" Y. Pine N86°W, 44 1/2 Lks. "SC T21N R7E S36 BT".
- 3 30 29
- (GLO₁) 10"x10"x10" stone set 5" deep from which bears 16" Fir N42°E, 28 Lks.; 10" Fir S54 1/2°E, 49 Lks.; 10" Fir N44°W, 78 Lks.
- 31 32
- FD 10"x10"x9" stone w/ 5 notches on East & 1 on South. A 21" W. Fir, S51°E, 39.9 Lks. has been recently opened & is scribed. A 28" W. Fir N38 1/2°E, 27 Lks. has been opened & is scribed.
- 1/4 C 31 32
- After diligent search for original corner, I establish position by single proportion. I scribe a 22" White Fir bears N05°E, 44 Lks. "1/4 S32 BT". I scribe a 36" D. Fir bears S50°W, 36 Lks. "1/4 S31 BT".
- 10 CIV 1/16 531
- Scribed a 26" Y. Pine bears S79°E, 62 Lks. "CW 1/16 S31 BT".
- 11 CN 1/16 531
- Scribed a 13" W. Fir bears N66°E, 28.5 Lks. "CN 1/16 S31 BT".
- 12 CIV 1/16 531
- Scribed a 12" S. Pine bears S75°E, 15.5 Lks. "CIV 1/16 S31 BT".
- 13 NE 1/16 531
- Scribed a 53" Y. Pine bears N76°E, 76 Lks. "NE 1/16 S31 BT".
- 14 E 1/16 530 531
- Scribed a 8" Y. Pine bears S42°E, 32 Lks. "E 1/16 S31 BT".
- 15 SCIV 1/16 531
- Scribed a 16" W. Fir bears S80°E, 12 Lks. "SC 1/16 S31 BT".
- 16 (GLO₁) Granite stone 26"x13"x12" no B.T.S.
- 30 29 1/4 C
- FD a 26"x15"x12" granite stone, unmarked, on steep South slope 15' South of Rock Bluff. Stone almost covered by erosion & supported by two smaller stones. I scribe a 13" S. Pine "1/4 S30 BT", bears S80°W, 66 Lks., & I set a 60d spike & LS 3625 cap 1 1/2" high on vertical face of rock outcropping 10' high bears N56°E, 20 Lks.
- 17 19 20
- (GLO₁) Granite stone 12"x8"x7"; 4" B.O. S13°E, 6 Lks.; 40" S. Pine, S13°E, 68 Lks.; 36" Fir, S27°W, 12 Lks.
- 30 29
- Found a granite stone 12"x9"x6" with 5 notches on East side only, a 47" W. Fir, S27°W, 12 Lks. to original face & 15 Lks. to center. Tree has healed scar & has also been chopped into & rehewed. A 61" S. Pine snag N34°E, 69 Lks., to center has burned-out face. I scribe an 8" W. Fir bears N29°W, 42 Lks., "T21N R8E S19 BT", an 8" Cedar N51°E, 25 Lks., "T21N R8E S20 BT"; an 8" Cedar S27°E, 40 1/2 Lks., "T21N R8E S29 BT".
- 18 24 30
- (GLO₁) Set post, 30" Cedar S25°W, 19 Lks.; 6" Fir N23 1/2°W, 58 Lks.; 10" Fir S81°E, 45 Lks.; 10" Fir N45°E, 44 Lks.
- 25
- Found 9"x6"x3" stone standing in M.O.R. 2' dia. x6" high - stone marked "T XXI N" on East side & marked on West side but I cannot read more than "11"; a 54" Cedar bears S38°W, 22 Lks. to exposed scribe, 32" D. Fir snag, N69°E, 43.8 Lks. to exposed scribe. I scribe a 6" D. Fir, N61 1/2°W, 39.5 Lks., "T21N R7E S24 BT".
- 19
- (GLO₁) Set post, a Yew tree S03°E, 6 Lks.
- 24 30
- FD small stake in M.O.R. 2' dia. & 6" high. A stump hole with 6" dead & scribed Yew bears S03°E, 6 Lks. I scribe a 11" W. Fir, N52°E, 45 Lks. "CC T21N R8E S19 BT", & a 10" Yew, S06°E, 67 Lks. "CC T21N R8E S30 BT".
- 20 17
- (GLO₁) Set lava stone 18"x14"x12", 18" Y. Pine, N35 1/2°E, 41 Lks.; 12" Y. Pine, S48W, 106 Lks.
- 1/4 C 20
- FD 18"x13"x12" unmarked lava stone in M.O.R. 3' dia. & 1' high. A scribed 30" Y. Pine snag bears N52°E, 41 Lks. to face & 43 Lks. to center. A Y. Pine stump hole with remains of scribing bears S46°W, 106 Lks. I note a 1 1/2" 30" Y. Pine snag bears N35 1/2°E from corner. I scribe an 8" Cedar, N14°W, 75 Lks. "1/4 S17 BT", & a 12" B.O. S67°W, 53 Lks. "1/4 S20 BT".
- 21 18 17
- (GLO₁) Set lava stone 18"x13"x5"; 10" B.O. S59°E, 69 Lks.; 12" B.O., N71 1/2°E, 63 Lks.; 4" B.O., N59°W, 61 Lks.
- 19 20
- FD broken lava stone 21"x13"x5" with 5 notches on one side & other side broken & a 1" plugged iron pipe 18" exposed in M.O.R. 2' dia. & 1' high. A 28" B.O. w/healed scar N71°E, 65 Lks. to center; 21" B.O. w/healed scar S57°E, 69 Lks. to center, a 25" Cedar with partially healed scribe N43°W, 51 Lks. to center; this Cedar is block scribed & reads "T21N R8E S19 BT", & is not an original BT. I scribe a 14" S. Pine "T21N R8E S19 BT", bears S57°W, 53 1/2 Lks.
- 22 19 20
- (GLO₁) Set post; 16" Fir bears S53 1/2°E, 71 Lks.
- 1/4 C
- Found 1/2 30" rotted stump with reversed scribe of "B" & a 4"x4"x40" post laying loose 1/4" from reestablished corner. I scribe a 17" S. Pine bears N67°W, 97 Lks. "1/4 S19 BT"; & a 17" W. Fir bears S40°E, 59 1/2 Lks. "1/4 S20 BT".
- 23
- This C.C. for T20N R7E & R8E was not included in this survey but the following data was noted.
- CC 16
- (GLO₃) Set a granite stone 30"x15"x10"; an Alder 24", S37°W, 27 Lks.; 22" Alder S04°E, 34 Lks.; a Fir 18", S29 1/2°E, 149 Lks.; a 16" Cedar S05°W, 149 Lks. - Found marked stone as per notes ± 10' downstream from position. I move to true position as determined from Alder B.T.S. & build a M.O.R. 4' dia. & 3' high.
- 6 1/16 30
- Scribed a 6" S. Pine "S 1/16 S30 BT", bears S70°W, 77 Lks.
- 24 27
- Scribed an 8" Cedar "W 1/16 S17 BT", bears N78°E, 15 Lks.
- 25 20 1/16
- Scribed a 14" W. Fir "N 1/16 S29 BT", bears N30°E, 28 Lks.
- 26 27
- Calculated position only.
- 27 CIV 530
- After diligent search, this corner established by single proportion, corner falls of North toe of cut-bank on old North-South logging spur. I scribe an 8" Cedar "1/4 S19 BT", bears N44°E, 47 Lks. & a 13" W. Fir "1/4 S30 BT", bears S06°E, 70 Lks.
- 28 10
- I scribe a 14" B. Oak "S1/16 S30 BT", bears N52°E, 48 Lks.
- 29 6 1/16
- I scribe a 14" B. Oak "CS1/16 S30 BT", bears N35°E, 19 Lks.
- 30 6 1/16
- I scribe a 13" Cedar "CN1/16 S30 BT", bears S72°W, 39 1/2 Lks.
- 31 6 1/16
- I scribe a 13" Cedar "CN1/16 S30 BT", bears S72°W, 39 1/2 Lks.
- 32 20
- Set post in M.O.R. No bearing trees within 5 chs. Found M.O.R. stacked on South slope with void in center. It was noted that the GLO₁ calls along the South line of the Southwest quarter Sec 20 (3.40 ch stream, 12.80 chs stream, 23.00 chs South fork Feather River) check if no reduction to horizontal is made. I scribe an 18" S. Pine "1/4 S20 BT", bears N54°W. 26 Lks. & a 9" D. Fir, "1/4 S29 BT", bears S52°W 23 Lks.
- 33 6 1/16
- Calculated position only.
- 34 20 1/16
- (GLO₁) 18"x16"x12" stone 6" B.O. bears N13 1/2°W, 64 Lks. after a diligent search for the original corner. I accept the proportioned corner by J. Larson as per Book 2, Record of Survey, Page 81 - which is a 2" alum. cap in a mound of stone from which a 23" W. Fir w/ healed scribe, bears S35°W, 21 1/2 Lks. & a 30" W. Fir w/healed scribe bears S43°W, 41 Lks.
- 35 6 1/16
- I scribe a 20" B. Oak "CW1/16 S20 BT", bears S82°W, 56 Lks.

LEGEND

- (GLO₁) GOVERNMENT LAND OFFICE FIELD NOTES BY D.C. HALL, JULY 5, 1881
 (GLO₂) GOVERNMENT LAND OFFICE FIELD NOTES BY T.F. BATELLE, JULY 19, 1869
 (GLO₃) GOVERNMENT LAND OFFICE FIELD NOTES BY C CAUDLE, FEBRUARY 6, 1909
 (GLO₄) GOVERNMENT LAND OFFICE FIELD NOTES BY J.V. KEDDIE, AUGUST 23, 1869
- - MONUMENTED CORNERS, SEE NOTE BELOW
- - CALCULATED ONLY
- (M) - MEASURED DATA
- M.O.R. - MOUND OF ROCK
- BT - BEARING TREE
- B.O., B.OAK - BLACK OAK
- D.FIR - DOUGLAS FIR
- W.FIR - WHITE FIR
- Y.PINE - YELLOW PINE
- S.PINE - SUGAR PINE
- ◆ - MONUMENTED 1/4 CORNER OR SECTION CORNER, SEE NOTE BELOW

NOTE: ALL DISTANCES TO BEARING TREES ARE TO CENTER OF TREE UNLESS OTHERWISE NOTED. ALL CORNERS, EXCEPTING THE NORTH 1/4 CORNER OF SECTION 31, ARE MONUMENTED WITH A STANDARD U.S.G.S. 30" ALUMINUM PIPE WITH FLANGE IN A MOUND OF STONES 3" IN DIAMETER AND 1" HIGH OR LARGER. CORNERS DEVIATING FROM THIS DESCRIPTION ARE SO NOTED UNDER CORNER NOTES.

BASIS OF BEARING

THE BASIS OF BEARING IS TRUE NORTH AS DETERMINED BY SOLAR OBSERVATION

RECORD OF SURVEY

BEING SECTIONS 30 AND 31 AND A PORTION OF SECTION 20, T21N, R8E, M.D.M. IN THE UNINCORPORATED AREA OF PLUMAS COUNTY, CALIFORNIA
 FOR LOUISIANA PACIFIC CORPORATION

SURVEYOR'S CERTIFICATE
 THIS MAP CORRECTLY REPRESENTS A SURVEY MADE BY ME OR
 UNDER MY DIRECTION IN CONFORMANCE WITH THE REQUIREMENTS OF
 THE LAND SURVEYOR'S ACT AT THE REQUEST OF LOUISIANA PACIFIC
 CORPORATION IN JUNE 1978

WILLIAM IV. GEDDIS
 WILLIAM IV. GEDDIS
 13-3625

COUNTY SURVEYOR'S CERTIFICATE
 THIS MAP HAS BEEN EXAMINED FOR CONFORMANCE WITH THE
 REQUIREMENTS OF THE LAND SURVEYOR'S ACT THIS DAY
 OF 1978, 1978

COUNTY SURVEYOR

RECORDER'S CERTIFICATE
 FILED THIS DAY
 IN BOOK OF MAPS AT PAGE
 REQUEST OF
 THE COUNTY ENGINEER
 FEE
 FILE NO.
 PAYNELLE SLATEN
 RECORDER
 DEPUTY

GEDDIS
 DRISCOLL
 AND
 ASSOCIATES
 SHEET 3 OF 3 SHEETS
 78-135

ENGINEERING
 SURVEYING
 PLANNING
 463 ORO DAM BLVD, SUITE
 OROVILLE, CA. 95965
 (916) 533-2068