

CORNER NOTES

(1) 1/4 23/24 Fd: 1" I.P. w/ no markings. Set: a std. USFS monument in stone mound, from which brs. a 26" Pine stump S 32° 30' E 12 ft. (G.L.O. S 32 1/2° E 12 ft.) and a down snag w/ scribing "1/4 S BT"; a 31" Pine N 61° W 10 ft. (G.L.O. N 61° W 10 ft.) w/ opened blaze and partial scribing "1/4 S"; a 20" Cedar S 28° 30' E 37.83 ft. scribed "1/4 S 24 BT". 1" I.P. brs. S 16° W 2.04 ft. from monument.

(2) 23/24 26/25 Fd: 34" I.P. w/ metal plug mkd. "L.S. 2846" in stone mound as per 3 RS 148.

(3) 1/4 23/26 Fd: 3" x 3" x 36" wood post w/ faint scribe marks in 12" x 36" stone mound, from which brs. a decayed stump N 28° 30' W 46 ft. (G.L.O. N 28 1/2° W 46 ft.); a stump hole S 71° 30' W 64 ft. (G.L.O. S 71 1/2° W 64 ft.); a 14" Pine S 63° W 13.5 ft w/ metal tag stamped "PLACERVILLE LUMBER CO. PROPERTY CORNER"; a 16" Pine S 70° 30' E 32.65 ft. scribed "1/4 S 26 BT"; a 21" Pine N 8° W 12.45 ft. scribed "1/4 S 23 BT". Replaced wood post w/ std. USFS monument.

(4) Cor. #1 Calculated position, nothing set. Position falls in ditch along west side of Calif. Hwy. 89

(5) Cor. #2 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 21" Pine Snag S 47° 08' E 15.2 ft. w/ notch in root crown; a 23" Pine N 34° 03' W 11.2 ft. w/ notch in root crown.

(6) Cor. #3 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 9" Cedar N 60° 41 1/2' E 17.9 ft. w/ notch at root crown.

(7) Cor. #4 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 12" Pine N 17° 48' E 8.0 ft. w/ notch at root crown; a 14" Pine S 35° 37' E 19.8 ft. w/ notch at root crown.

(8) Cor. #5 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 19" Pine N 7° 28' W 9.0 ft. w/ notch at root crown; a 61" Pine S 52° 03' E 4.9 ft. w/ notch at root crown.

(9) Cor. #6 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 23" Pine S 74° 35' E 15.2 ft. w/ notch at root crown.

(10) Cor. #7 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 18" Pine N 86° 42' E 24.6 ft. w/ notch at root crown.

(11) Cor. #8 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 25" Pine N 52° 31 1/2' E 26.4 ft. w/ notch at root crown.

(12) Cor. #9 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 23" Pine N 57° 34' E 8.9 ft. w/ notch at root crown; a 32" Pine S 68° 41' E 22.2 ft. w/ notch at root crown.

(13) Cor. #10 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 13" Pine N 50° 28' W 3.2 ft. w/ notch at root crown; a 9" Pine S 66° 23' E 14.3 ft. w/ notch at root crown.

(14) Cor. #11 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 44" W. Fir N 43° 05 1/2' E 6.7 ft. w/ notch at root crown.

(15) Cor. #12 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 16" Pine N 1° 03 1/2' E 10.5 ft. w/ notch at root crown; a 9" Pine N 85° 23 1/2' E 4.2 ft. w/ notch at root crown.

(16) Cor. #13 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 9" Pine N 61° 58 1/2' W 14.2 ft. w/ notch at root crown.

(17) Cor. #14 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 26" Pine S 66° 08' E 19.2 ft. w/ notch at root crown.

(18) Cor. #15 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 24" Pine S 73° 32' W 2.9 ft. w/ notch at root crown.

(19) Cor. #16 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 24" Pine N 78° 17' E 2.3 ft. w/ notch at root crown.

(20) Cor. #17 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 21" Pine N 0° 15' E 3.0 ft. w/ notch at root crown.

(21) Cor. #18 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 14" Pine S 10° 15' W 12.6 ft. w/ notch at root crown.

(22) Cor. #19 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 15" Pine S 10° 48' W 7.4 ft. w/ notch at root crown.

(23) Cor. #20 Set: 5/8" aluminum rod w/ 3 1/4" cap in stone mound, from which brs. a 24" Pine N 88° 07' W 3.2 ft. w/ notch at root crown. This point is at the intersection of the south bankline of Frazier Creek and the west bankline of the Middle Fork of the Feather River.

Note: The std. U.S.F.S. monument is a Bernstein A-1-BR Break-off monument consisting of a 2" diameter aluminum pipe, 27 1/2" long, w/ a magnet in a 2 1/2" x 5" cast aluminum base designed to break off on impact if the monument is disturbed, and a 3 1/4" aluminum cap mkd. as per the Manual of Instructions For The Survey Of The Public Lands Of The United States, 1973 for the respective corners.

Note: The caps of corners 2 through 20 are mkd. "TRACT FR-33 PARCEL B", the respective corner number, and "R.C.E. 32780 1982".