

CORNER NOTES

H.B.=HEALED BLAZE V.S.=VISIBLE SCRIBING
S.B.T.=SCRIBED AS A BEARING TREE

T22N R7E
S32 | S33
S5
T21N R7E
1926

CORNER NO. 1

FD. 2" PIPE WITH 2 1/2" BRASS CAP IN ROCK MOUND, MARKED U.S. GENERAL LAND OFFICE SURVEY - CORNER FALLS ON TOP OF WEST RIDGE IN LARGE TIMBER

FD. 24" OAK - N58°13'E 50.0' - H.B.
(16" B.O. - N60°45'E 76 LKS - REC.)

T22N R7E
S33
C | C
S5 | S4
T21N R7E
1926

CORNER NO. 2

FD. 2" PIPE WITH 2 1/2" BRASS CAP IN ROCK MOUND, MARKED U.S. GENERAL LAND OFFICE SURVEY - CORNER FALLS ON SOUTH SLOPE ± 1000' WEST OF ROAD

FD. 46" CEDAR - S59°54'E 52.8' - V.S.

A 4" Y. PINE BEARS S35°05'E 10.9' - S.B.T.

T22N
1/4 S4
T21N R7E
LS3966
1988

CORNER NO. 3

SET STD. USFS ALUM. MON. IN ROCK MOUND CORNER FALLS ON STEEP NW SLOPE, AT WEST EDGE OF 4 FT. HIGH ROCK BLUFF

A 14" CEDAR BEARS S31°15'W 10.9' - S.B.T.

A 14" Y. PINE BEARS S35°30'E 11.3' - S.B.T.

T22N R7E
S33 | S34
S4
T21N R7E
1926

CORNER NO. 4

FD. 2" PIPE WITH 2 1/2" BRASS CAP IN ROCK MOUND, MARKED U.S. GENERAL LAND OFFICE SURVEY

FD. 7" CEDAR DEAD AND DOWN WITH B.T. TAG, NO V.S., (EDGERTON 1979) - STUMP HOLE BEARS S14°E 17.2'

FD. 19" W. FIR WITH B.T. TAG, NO V.S., (EDGERTON 1979) TREE BEARS S67°30'E 29.9' - 46 LKS

A 12" W. FIR BEARS

T22N R7E
S34
S4 | S3
T21N CC R7E
LS3966
1988

CORNER NO. 5

SET STD. USFS ALUM. MON. IN ROCK MOUND - SKID ROAD IS APPROX. 12' SOUTH OF CORNER - COR FALLS ON GENTLE SOUTH SLOPE, CLOSE TO TOP OF RIDGE

FD. 27" W. FIR - S3°23'E 31.5' - H.B.

A 8" W. FIR BEARS S26°50'W 8.6' - S.B.T.

AP
T22N R7E
S34
1926

CORNER NO. 6

FD. 1" IRON PIPE WITH 2 1/2" BRASS CAP MARKED U.S. GENERAL LAND OFFICE SURVEY - CORNER FALLS ON SOUTH SLOPE OF RIDGE ABOUT 40' EAST OF RIDGE TOP CORNER IS ± 1500' EAST OF BRIDGE THAT CROSSES MIDDLE FORK

FD. REMAINS OF 60" PINE - S17°W 9.3' - V.S.

FD. 36" Y. PINE - N13°E 54.5' - H.B.

T21N R7E
1/4 S5 | S4
LS3966
1988

CORNER NO. 7

FD. MKD. STONE, 1/4 ON WEST FACE SET STD. USFS ALUM. MON. IN ROCK MOUND (25x15x10 STONE BURIED)

FD. 38" DBL. B. OAK - S82°E 28.5' - H.B.
(20" DBL. B. OAK - S78°E 26 LKS. - REC.)

A 15" Y. PINE BEARS S75°W 16.4' - S.B.T.

ALL THE OTHER ORIG. B.T.'S ARE GONE

E1/16
C+C
S4
LS3966
1988

CORNER NO. 8

SET STD. USFS ALUM. MON. IN ROCK MOUND - CORNER IS 150' NORTH OF A ROAD AND 30' NORTH OF CREEK

B.O. 9'x15' ROCK FACE, LS TAG NAILED IN CRACK AND BT TAG PAINTED BO - N64°15'W 13.7'

A 8" CEDAR BEARS S10°30'W 7.7' - S.B.T.

T21N R7E
1/4
S4 | S3
LS3966
1988

CORNER NO. 9

FD. 2" SQ. POST NEXT TO 12"x12" ROCK SET STD. USFS ALUM. MON. IN ROCK MOUND

FD. REMAINS OF 20" FIR SNAG - S19°E 28.0' - V.S.
(15" FIR - S19°E 39 LKS - REC.)

FD. 17" CEDAR - N67°W 8.4' - V.S.
(12" CEDAR - N67°W 12 LKS - REC.)

A 14" W. FIR BEARS N20°15'E 16.8' - S.B.T.

C
S1/16 | S4
C
LS3966
1988

CORNER NO. 10

SET STD. USFS ALUM. MON. IN ROCK MOUND COR. IS ON WEST SLOPE IN LARGE TIMBER

A 19" D. FIR BEARS S87°32'W 16.7' - S.B.T.

A 23" D. FIR BEARS N5°31'W 22.4' - S.B.T.

SE1/16-S4
LS3966
1988

CORNER NO. 11

SET STD. USFS ALUM. MON. IN ROCK MD. CORNER FALLS 270' ± NORTH OF ROAD AND ON SLIGHT SW SLOPE

A 19" W. FIR BEARS N26°31'E 33.9' - S.B.T.

A 12" W. FIR BEARS N55°46'W 25.3' - S.B.T.

T21N R7E
S5 | S4
S8 | S9
1926

CORNER NO. 12

FD. STD. GLO 2 1/2" BRASS CAP ON 1 1/2" IRON PIPE

FD. 47" DOUG FIR - N34°30'W 76' - V.S.
(40" FIR - N34°30'W 6.6' - GLO)

FD. 27" W. FIR - S19°W 63.6' - V.S.
(16" FIR - S19°W 62.7' - GLO)

FD. 15" W. FIR - S65°15'E 28.3' - V.S.
(14" FIR - S65°15'E 27.7' - GLO)

FD. 28" W. FIR - N45°E 22.0' - V.S.
(24" FIR - N45°E 21.1' - GLO)

T21N R7E
1/4 S4
S9
LS3966
1988

CORNER NO. 13

SET STD. USFS ALUM. MON. IN ROCK MOUND CORNER IS 300' ± SOUTH OF CREEK ON NORTH SLOPE

FD. 20" W. FIR - S33°12'W 6.4' - V.S. 1/4 S

FD. 41" W. FIR - N51°28'W 28.0' - H.B.

A 12" W. FIR BEARS N15°49'E 22.0' - S.B.T.

T21N R7E
S4 | S3
S9 | S10
LS3966
1988

CORNER NO. 14

FD. SMALL ROCK MOUND SET STD. USFS ALUM. MON. IN ROCK MOUND

FD. 60" FIR - S6°32'W 124.6' - V.S.

A 14" W. FIR BEARS S41°05'E 24.7' - S.B.T.

A 12" W. FIR BEARS N62°18'W 54.8' - S.B.T.

A 5" CEDAR BEARS N2°14'E 25.7' - S.B.T.

AP
T22N R7E
S33
1926

CORNER NO. 15

FD. 1" IRON PIPE WITH 2 1/2" BRASS CAP MARKED U.S. GENERAL LAND OFFICE SURVEY

S1/4
S33
T22N R7E
(NO MON.)

CORNER NO. 16

POSITION FOR CORNER FALLS UNDER AN EXISTING ROAD CULVERT. TIED 31" FIR WITH VISIBLE SCRIBING CORNER BEARS N8°45'W 66 LKS. (43.56') FROM BT PER 1926 GLO SURVEY NOTES.

NOTE

STD. USFS ALUM. MON. IS A 3" ALUM. CAP ON 2 1/2" ALUM. PIPE WITH MAGNET UNDER CAP.

RECORD OF SURVEY
FOR
THE USDA FOREST SERVICE

BEING IN SECTION 4, T21N, R7E, M.D.M., IN THE UNINCORPORATED TERRITORY OF PLUMAS COUNTY, STATE OF CALIFORNIA

 **DEL TERRA, INC.**
SURVEYING
REDDING, CA. DATE JUNE 1988
SHEET 2 OF 2