

Basis of Bearings


The bearing (S. 89° 27' 37\"/>

Legend

- Corners found
- Corners set this survey - ACAP - 2 1/2\"/>
- ① Key to Corner notes
- (4) Data per 7 RS 3
- Property lines marked to USFS standards
- IP iron pipe
- BCIP brass cap on iron pipe
- amos - a mound of stones

Surveyor's Statement

This map correctly represents a survey made by me or under my direction in conformance with the requirements of the Land Surveyor's Act at the request of U.S.D.A. - Plumas National Forest in July 1988.



Jay A. Burgess
 Jay A. Burgess LS 4790
 Expires 9-30-92

County Surveyor's Statement

This map has been examined in accordance with Section 8766 of the Land Surveyors Act this 2nd day of June 1989.

Lawrence J. Brock
 Lawrence J. Brock RCE 13528

County Recorder's Statement

Filed this 9th day of June 1989, in Book 8 of Records of Survey at Page 88:89 Plumas County Records at the request of the County Engineer.

Fee: \$7.00
 File #: 3425

Jo Ann Van Gelder
 Deputy
 Ila Diggs
 County Recorder

RECORD of SURVEY
 for
USDA - PLUMAS NATIONAL FOREST

of
 SECTION 25 and portions of MS 6231 & MS 5320 in
 SECTIONS 17, 18, & 20, T.25N. R.8E., MDM.
 in the unincorporated territory of Plumas Co., Calif.



February 1989
 Scale as shown
 Sheet 1 of 2

- ① T25N R8E
 S23|S24
 S26|S25
 LS4790
 1988
 Fd 3/4\"/>
- ② T25N R8E
 1/4 S24
 1/4 S25
 LS4790
 1988
 Fd. 1/2\"/>
- ③ T25N R8E R9E
 S24|S19
 S25|S30
 1967
 Fd. BLM BCIP in amos & BTs:
 35\"/>
- ④ N1/16
 S26|S25
 LS4790
 1988
 Set ACAP in amos & mkd:
 5\"/>
- ⑤ N1/16
 S25|S25
 LS4790
 1988
 Set ACAP in amos & mkd:
 23\"/>
- ⑥ N1/16
 S25|S30
 LS4790
 1988
 Set ACAP in amos & mkd:
 8\"/>
- ⑦ T25N R8E
 1/4 S26|S25
 LS4790
 1988
 Fd. post in mos & orig BT Fir snag, N.21°E. 13.2'
 Replaced w/ ACAP in amos & mkd:
 10\"/>

- ⑧ T25N R8E
 C1/4
 S25
 LS4790
 1988
 Set ACAP in amos & mkd:
 12\"/>
- ⑨ 1/4
 S25|S30
 R8E R9E
 T25N
 1967
 Fd. BLM BCIP in amos & BTs:
 Fir snag S.20°E. 27.1' orig.
 18\"/>
- ⑩ T25N R8E
 1/4 S26
 S25
 LS2780
 1984
 Fd ACAP in amos & BTs per 7 RS 3:
 20\"/>
- ⑪ WC
 T25N R8E
 S26|S25
 S35|S36
 LS2780
 1984
 Fd. 20\"/>
- ⑫ T25N R8E
 1/4 S26
 S25
 LS4790
 1988
 Fd. orig. 12\"/>
- ⑬ T25N R8E R9E
 S25|S30
 S36|S31
 LS4790
 1988
 Fd. mos & orig. BT: Fir snag N.29°E. 5.3'
 Set ACAP in amos & mkd:
 21\"/>
- ⑭ 1/4
 S26|S31
 R8E R9E
 T25N
 1967
 Fd. BLM BCIP in amos & BTs:
 27\"/>