

T21N R8E
SC
CORNER NO. 1
FD. 3" ALUM. PIPE W/ 3 1/2" ALUM. CAP
IN STONE MOUND RECORDED ON 5 RS 37-39.
COR. FALLS ON FLAT RIDGE TOP
50± WEST OF A LOGGING ROAD.
FD. 17" CEDAR N14°W 24.7' V.S.
REC. 14" CEDAR N19°W, 24.7' 5 RS 37-39 PLUMAS CO. RECORDS
FD. 24" S. PINE N57°E 18.1' H.B.
REC. 21" S. PINE N55°E, 18.1' 5 RS 37-39 PLUMAS CO. RECORDS

LS 3966
T21N R8E
CORNER NO. 5
1/4 S5
SET STD. MON IN STONE MOUND.
CORNER SET BY SINGLE PROPORTION.
COR. FALLS ON EAST SLOPE, 65±
WEST OF A DIRT ROAD.
A 10" CEDAR S10°E 34.5' S.B.T.
A 15" CEDAR S52°15'W 41.1' S.B.T.

CORNER NOTES
H.B. = HEALED BLAZE V.S. = VISIBLE SCRIBING
S.B.T. = SCRIBED AS A BEARING TREE
STD. MON = 3 1/4" USFS ALUM. CAP
ON A 5/8" ROD
STD. BLM MON = 3 1/4" STAMPED BRASS CAP
ON 2" STEEL PIPE
N.R.F. = NO RECORD FOUND

T21N R8E
1/4 SC
CORNER NO. 12
S 34
T20N
LS 3966
1990
FD. 3/4" PIPE IN SMALL STONE MOUND.
SET STD. MON IN STONE MOUND.
COR. FALLS ON GENTLE WEST SLOPE,
250± EAST OF, AND 75± ABOVE
AN OLD LOGGING ROAD.
FD. STUMP HOLE N45°E 16.5'
REC. 25" SPRUCE N45°E 16.5' (GLO)
FD. CEDAR STUMP EAST 15.5'
REC. 24" CEDAR LINE TREE EAST 16.5' (GLO)
FD. LARGE ROTTEN STUMP N45°30'W 33.0'
REC. 25" SPRUCE N45°30'W 33.0' (GLO)
A 11" FIR N22°E 18.5' S.B.T.
A 12" FIR N22°W 11.6' S.B.T.

NW 1/16
S4
LS 3966
1990
CORNER NO. 16
SET STD. MON IN STONE MOUND.
COR. FALLS ON EAST SLOPE, 150±
WEST OF 21N16 RD.
A 4" Y. PINE N74°30'W 27.8' S.B.T.
A 14" B. OAK S22°15'W 60.2' S.B.T.

T21N R8E
CC
CORNER NO. 2
S6 | S5
T20N
LS 3966
1990
FD. 3/4" PIPE IN IMBEDDED STONE MOUND.
SET STD. MON IN STONE MOUND AS CC
2.28' NORTHERLY OF FD. STONE MOUND
AND PIPE.
FD. FIR ROOT BALL S75°E, ±23'
REC. 28" FIR S74°30'E 23.1' GLO TO ORIG. CC
FD. DOWN AND ROTTED FIR, S47°W, ±32'
REC. 30" FIR S47°15'W 31.7' GLO TO ORIG. CC
A 6" S. PINE S48°E 50.2' S.B.T.
A 12" D. FIR S47°W 32.8' S.B.T.
NOTE: BOTH BT'S ARE TO NEW CORNER

T21N R8E
SC
S32 | S33
T20N
LS 3966
1990
CORNER NO. 6
FD. LARGE STUMP DEPRESSION.
REC. 24" OAK TREE COR. (GLO)
SET STD. MON IN STONE MOUND
IN DEPRESSION.
FD. DEAD & DOWN 26" OAK N42°30'E 21.1' V.S.
REC. 20" B. OAK N42°30'E 21.1' (GLO)
FD. STUMP HOLE & B. OAK ROOT BALL
N0°30'W 45.5'
REC. 7" B. OAK N0°30'W 45.5' (GLO)
A 12" CEDAR N10°W 10.5' S.B.T.
A 10" FIR N53°E 65.8' S.B.T.

T21N R8E
1/4 LS 3966
S4
T20N R8E
1990
CORNER NO. 9
SET STD. MON IN STONE MOUND.
POSITION BY SINGLE PROPORTION.
COR. FALLS ON NW SLOPE, 150±
SOUTH OF LOST CREEK.
A 4" D. FIR S59°30'W 5.5' S.B.T.
MARKED "X" HIGH & "BT" LOW
A 6" D. FIR S30°E 43.0' S.B.T.

CORNER NO. 13
FD. 4' STONE MOUND.
SET 5/8" UNMARKED REBAR IN STONE MOUND
TO PERPETUATE ORIGINAL CLOSING CORNER.
FD. 39" CEDAR S52°W 29.7' V.S.
REC. 28" CEDAR S52°W 29.7' (GLO)
A 11" W. FIR S26°W 37.0' S.B.T.
A 15" S. PINE S30°E 55.3' S.B.T.

N 1/16
C
S4
LS 3966
1990
CORNER NO. 17
SET STD. MON IN STONE MOUND.
COR. FALLS ON N/W SLOPE, 70±
WEST OF A DIRT ROAD.
A 10" W. FIR S80°15'W 32.2' S.B.T.
A 7" Y. PINE S4°W 12.8' S.B.T.

T21N R8E
LINE TREE
R.M.
CORNER NO. 3
1990
FD. 29" CEDAR W/ HACK MARKS
ON THE EAST & WEST SIDES.
REC. 15" CEDAR LINE TREE (GLO)
SET STD. MON AS R.M. TO LINE TREE.
R.M. LIES N86°25'W 17.0' FROM
LINE TREE.
TREE LOCATED ON A FLAT RIDGE, 70±
WEST OF A SHARP DROP OFF TO THE EAST,
AND 30' WEST OF AN OLD DITCH.
A 4" FIR S59°W 27.2' S.B.T.
MARKED "X" HIGH & "BT" LOW.

T21N R8E
CC
CORNER NO. 7
S5 | S4
T20N
LS 3966
1990
FD. 3/4" PIPE IN DEEPLY IMBEDDED STONE MOUND
SET STD. MON 0.37' S'LY OF FD. PIPE IN STONE MOUND.
COR. FALLS ON GENTLE S/W SLOPE.
SEE DETAIL "C" SHEET 2
A 12" W. FIR S10°15'E 16.7' S.B.T.
A 10" W. FIR S44°30'W 14.2' S.B.T.
NO ORIGINAL BT'S FOUND

T21N R8E
SC
S33 | S34
T20N
LS 3966
1990
CORNER NO. 10
FD. LARGE D. FIR ROOT HOLE AND
1 1/2" IP W/CAP.
REC. 30" D. FIR TREE COR. (GLO)
SET STD. MON IN STONE MOUND, IN ROOT HOLE
COR. FALLS ON GENTLE NORTH SLOPE,
60± NORTH OF A RIDGE TOP.
FD. 14" D. FIR N73°E 15.3' H.B.
REC. N.R.F.
A 14" D. FIR N18°W 34.9' S.B.T.

80
1/16
S5 | S4
LS 3966
1990
CORNER NO. 14
SET STD. MON IN STONE MOUND.
COR. FALLS ON NORTH EDGE OF A ROAD.
A 7" D. FIR S31°15'W 50.6' S.B.T.
A 16" W. FIR S64°30'E 25.1' S.B.T.

T20N R8E
R.M.
6.5
LS 3966
LINE TREE
1990
CORNER NO. 18
FD. 64" S. PINE STUMP WITH HACK
VISIBLE AT 34" DIAMETER POINT.
ACCEPTED AS GLO LINE TREE
SET STD. MON. FOR RM S72°34'W, 6.5'
A 4" W. FIR BEARS N31°W, 4.2' S.B.T.
"X" HIGH, "BT" LOW
A 6" Y. PINE BEARS S77°W, 16.7' S.B.T.

T21N R8E
1/4 S32
CORNER NO. 4
T20N R8E
LS 3966
1990
REC. 12" X 10" X 6" STONE (GLO)
FD. ROCK MOUND.
SET STD. MON IN STONE MOUND.
FD. 21" B. OAK N7°30'W 16.5' V.S.
REC. 8" B. OAK N7°W 16.5' (GLO)
FD. 22" B. OAK S8°E 15.0' AXE MARKS
REC. 10" B. OAK S16°30'E 13.2' (GLO)
A 10" CEDAR N36°W 6.2' S.B.T.
A 12" W. FIR N65°E 21.0' S.B.T.

T21N R8E
1/4 SC
S33
T20N
LS 3966
1990
CORNER NO. 8
FD. 12"x17"x7" STONE IN STONE MOUND.
REC. 12"x17"x7" STONE IN STONE MOUND (GLO)
SET STD. MON IN STONE MOUND.
COR. FALLS ON EAST SLOPE, 200±
WEST OF, AND 100± ABOVE A
MAIN LOGGING RD.
FD. 72" S. PINE STUMP N15°30'E 38.3'
REC. 50" S. PINE N15°30'E 38.3' (GLO)
FD. 62" FIR N85°W 27.0' BARK SCRIBED
REC. 46" SPRUCE N85°W 27.1' (GLO)
FD. OAK STUMP HOLE S21°30'W 39.6'
REC. 10" OAK S21°30'W 39.6' (GLO)
A 12" S. PINE N55°W 41.3' S.B.T.
A 12" FIR N38°E 21.1' S.B.T.

T21N R8E
S34
CORNER NO. 11 SET CC
S4 | S3
T20N R8E
CC
1990
SET STD. MON IN STONE MOUND.
COR. FALLS ON A SOUTH SLOPE.
A 9" CEDAR S45°30'W 12.5' S.B.T.
A 18" W. FIR S84°15'E 22.2' S.B.T.
CORNER NO. 11 FD. GLO CC
REC. POST
REC. 12" B. OAK S62°E, 60.0'
FD. 22" B. OAK S62°E, 64.0'
SCRIBING IS ROTTED AWAY, EDGE OF OLD FACE IS VISIBLE.
REC. 28" SPRUCE S18°30'W, 42.2'

80
W 1/16
S4
LS 3966
1990
CORNER NO. 15
SET STD. MON IN STONE MOUND.
COR. FALLS ON S/W SLOPE.
A 17" D. FIR S56°E 44.9' S.B.T.
A 14" S. PINE S19°30'W 12.7' S.B.T.

RECORD OF SURVEY
FOR
USDA FOREST SERVICE
IN SECTIONS 4, 5, 8, AND 17 THRU 19
T20N R8E MDM
IN THE
UNINCORPORATED AREAS OF BUTTE & PLUMAS
COUNTIES, STATE OF CALIFORNIA

DEL TERRA INC.
SURVEYING
P.O. BOX 4632
REDDING, CA 96099
PHONE (916) 241-8050

SCALE: 1" = 1000' DATE: MAY 1991
SHEET: 3 OF 5