

Note: All bearings & distances for bearing trees are based upon True North and ground distances.

Corner Notes

Corner Key Cap Markings

① T 23 N R 11 E
 $\frac{6\frac{1}{2}}{7\frac{1}{8}}$
 1978

Found BLM Brass Cap on I.P. in Mound of stone with bearing trees with Bearing Tree tags
 48" Fir Snag N 23°36' W, 8.8' (Tag S 24° E, 14 lks.)
 56" Pine N 58°14' E, 25.2' (Tag S 61 1/2° W, 36 lks.)
 20" Fir N 65°56' E, 14.6' (Tag S 67° W, 22 lks.)
 9" Pine S 05°16' E, 9.1' (Tag N 4° W, 15 lks.)

② T 23 N R 11 E
 1/4
 $\frac{7}{8}$
 LS 2843
 1992

Found Mound of Rock with 15"x 8"x 7" Stone, no visible markings. Set Standard USFS Aluminum Cap on 5/8" rod Stump snag N 87°05' E, 18.6' (20" Pine East, 28 lks.)
 9" Cedar with Bearing Tree tag S 79°31' W, 19.5'

③ W 1/16 $\frac{S 5}{S 8}$
 LS 2843
 1992

Set Standard USFS Aluminum Cap on 5/8" rod and marked Bearing Trees
 20" Cedar N 61°57' E, 38.6' blazed & scribed (1/16 S 8 BT)
 8" Cedar S 26°56' E, 63.6' blazed & scribed (1/16 S 8 BT)

④ NW 1/16
 S 8
 LS 2843
 1992

Set Standard USFS Aluminum Cap on 5/8" rod and marked Bearing Trees
 8" Pine N 71°57' W, 12.5' blazed & scribed (1/16 S 8 BT)
 9" Cedar S 1°19' E, 17.5' blazed & scribed (1/16 S 8 BT)

⑤ T 23 N R 11 E
 1/4 $\frac{5}{8}$

Found BLM Brass Cap in mound of stone with bearing trees with bearing tree tags
 8" Pine N 15°40' W, 28.4' (Tag S 14 1/2° E, 44 lks.)
 24" Cedar N 62°21' E 15.4' (Tag S 63° W, 23 lks.)
 15" Fir S 77°40' E, 48.8' (Tag N 76 1/2° W, 74 lks.)

⑥ N 1/16 $\frac{C}{S 8}$
 LS 2843
 1992

Set Standard USFS Aluminum Cap on 5/8" rod and marked Bearing Trees
 8" Cedar S 27°41' W, 23.2' blazed & scribed (1/16 S 8 BT)
 6" Pine S 56°09' E, 12.4' blazed & scribed (1/16 S 8 BT)

⑦ NE 1/16
 S 8
 LS 2843
 1992

Set Standard USFS Aluminum Cap on 5/8" rod and marked Bearing Trees
 8" Cedar S 57°18' W, 81.8' blazed & scribed (1/16 S 8 BT)
 11" Pine S 26°23' E, 92.2' blazed & scribed (1/16 S 8 BT)

⑧ E 1/16 $\frac{S 5}{S 8}$
 LS 2843
 1992

Set Standard USFS Aluminum Cap on 5/8" rod and marked Bearing Trees
 8" Cedar N 35°05' E, 25.6' blazed & scribed (1/16 S 8 BT)
 15" Pine S 36°57' E, 27.2' blazed & scribed (1/16 S 8 BT)

⑨ T 23 N R 11 E
 $\frac{5\frac{1}{4}}{8\frac{1}{9}}$
 LS 2843
 1992

Found mound of stone and Set Standard USFS Aluminum Cap, bearing trees with Bearing Tree tags
 22" Pine N 2°20' E, 34.6' (Tag S 3° W, 53 lks.)
 23" Cedar stump S 78°49' E, 26.5' (Tag N 77° W, 41.5 lks.)

Corner Key Cap Markings

⑩ T 23 N R 11 E
 1/4
 S 8 | S 9
 LS 2843
 1992

Corner established by Single Proportion. Set Standard USFS Aluminum Cap on 5/8" rod with bearing trees
 28" Pine S 69°30' E, 101.0', I blazed & scribed (1/4 S 9 BT)
 tree also has Bearing Tree Tag marked (RP N 42° W, 74 lks)
 39" Fir S 27°40' E 68.9' blazed with "K" tag marked approximate 1/4 corner
 14" Cedar S 4°57' W, 76.4', I blazed & scribed (1/4 S 8 BT)
 Burned stump S 67°18' E, 118.0' with Bearing Tree tag (Tag N 46° W, 100 lks.)

⑪ T 23 N R 11 E
 $\frac{9\frac{1}{10}}{16\frac{1}{15}}$
 LS 2843
 1992

Found mound of stone and Set Standard USFS Aluminum Cap, bearing trees with Bearing Tree tags
 20" Pine N 7°27' E 10.8' with "K" tag, not legable
 Stump remnant N 73°34 E 53.0' (Tag S 72° W, 81 lks.)
 Stump remnant S 49°55 E 23.7' (Tag N 53° W, 36 lks.)
 24" Pine S 17°39' W 46.5' (Tag N 17 1/4° E, 45')

⑫ T 23 N R 11 E
 $\frac{8\frac{1}{9}}{17\frac{1}{16}}$
 LS 2843
 1992

Corner established by Double Proportion. Set Standard USFS Aluminum Cap on 5/8" rod in mound of stone with bearing trees
 20" Pine N 86°36' E, 70.3', I blazed & scribed (S 9 BT)
 21" Pine SN 56°27' E, 88.0', I blazed & scribed (S 16 BT)
 13" Fir s 14°01' E, 96.1', I blazed & scribed (S 17 BT)
 9" Pine N 11°33' W, 19.2', I blazed & scribed (S 8 BT)

⑬ W C
 1/4 $\frac{8}{17}$
 LS 2843
 1992

Found 32" Fir snag blazed & scribed for 1/4 Corner.
 Stumphole S 78°30' E, 40.9' (Record, 10" Fir S 78° E, 62 lks.)
 Set Standard USFS Aluminum Cap N 88°35'52" E, 20.00' as Witness Corner, with Bearing Trees
 11" Fir S 87°01' E, 38.5', I blazed & scribed (X)(1/4 S 17 BT)
 12" Fir N 39°45' W, 26.0', I blazed & scribed (X) (1/4 S 8 BT)

⑭ T 23 N R 11 E
 1/4
 S 17 | S 16

Found BLM Brass Cap on I.P. Bearing trees have Bearing Tree tags
 13" Cedar N 30°51' E, 28.0'
 15" Pine N 28°04' W, 12.4'
 17" Pine S 25°51' E, 18.6'
 40" Pine S 62°14' W, 39.9'

RECORD OF SURVEY
 for
 Sierra Pacific Industries

A portion of Section 8
 T. 23 N., R. 11 E., M.D.M.
 PLUMAS COUNTY — CALIFORNIA
 SCALE 1" = 400' MAY, 1992

HAMBY SURVEYING INC.
 P.O. Box 1209
 PORTOLA, CA. 96122
 Phone 916-832-5571

SHEET 2 OF 2