

**CORNER NOTES**

H.B. = HEALED BLAZE  
 V.S. = VISIBLE SCRIBING  
 S.B.T. = SCRIBED AS A BEARING TREE  
 STD. DTI MON. = 2" ALUM. CAP ON  
 A 5/8" REBAR  
 ALL ACCESSORIES MARKED PER  
 1973 BLM MANUAL

**T23N R5E**  
**S4 | S3**  
**S9 | S10**  
 CORNER NO. 1  
 FD. 2 1/2" GLO BRASS CAP ON A 2" STEEL PIPE IN A MOUND OF STONE. CORNER FALLS 130± SOUTH OF A ROAD ON A SLIGHT NORTH SLOPE IN TIMBER AND ROCK.  
 1938

**W 1/4 C**  
**S3 | S2**  
 CORNER NO. 4  
 FD. A 2 1/2" GLO BRASS CAP ON A 1" IRON PIPE IN A MOUND OF STONE. CORNER FALLS ON AN EAST SLOPE, 100± NORTHWEST OF A DRAW.  
 1938

**T24N R5E**  
**S35 | S36**  
**T23N R5E**  
**S1**  
 CORNER NO. 7  
 FD. A 2 1/2" GLO BRASS CAP ON A 2" IRON PIPE IN A MOUND OF STONE. CORNER FALLS ON AN ABANDONED ROAD ON A STEEP EAST SLOPE 175± WEST OF RAILROAD TRACKS.  
 1938

FD. AN 11" BLACK OAK BEARS N2°W, 16.6' -HB  
 REC. AN 8 BLACK OAK BEARS N5 1/2°W, 15.8' (GLO 1938)  
 FD. A 15" CEDAR BEARS N47°E, 39.5' -HB  
 REC. AN 8" CEDAR BEARS N48°E, 38.3' (GLO 1938)  
 FD. A 31" CEDAR BEARS S58°E, 30.5' -VS  
 REC. A 26" CEDAR BEARS S59 1/2°E, 30.4' (GLO 1938)  
 FD. A 9" CEDAR BEARS S9°W, 39.9' -VS  
 REC. A 10" CEDAR BEARS S8 3/4°E, 40.3' (GLO 1938)

FD. A 40" SUGAR PINE BEARS N89°E, 56.6' -HB  
 REC. A 30" SUGAR PINE BEARS N84 1/2°E, 56.8' (GLO 1938)  
 FD. DEAD AND STANDING PINE BEARS N63°W, 39.3' -VS  
 REC. A 20" SUGAR PINE BEARS N58°W, 39.6' (GLO 1938)  
 A 7" YELLOW PINE SCRIBED WITH AN "X" BEARS S62°W, 38.0' -SBT  
 TRUE CORNER IS 13.20', N 00°57'26" E FROM MONUMENT

FD. A 7" WHITE OAK BEARS N42°E, 6.4' -HB  
 REC. A 4" WHITE OAK BEARS N42°E, 6.6' (GLO 1938)  
 FD. A 30" WHITE OAK BEARS N74 1/2°W, 30.7'  
 REC. A 22" WHITE OAK BEARS N74 1/2°W, 30.4' (GLO 1938)

**1/4 S3**  
**S10**  
 CORNER NO. 2  
 FD. A 2 1/2" GLO BRASS CAP ON A 1" IRON PIPE. CORNER FALLS ON AN EAST SLOPE, 100± EAST OF THE TOP OF A NORTH-SOUTH RIDGE.  
 1938

**T24N R5E**  
**S34 | S35**  
**S3 | S2**  
**T23N**  
**1938**  
 CORNER NO. 5  
 FD. A 2 1/2" GLO BRASS CAP ON A 2" IRON PIPE. CORNER FALLS ON A STEEP WEST SLOPE ON TOP OF CUT OF AN OLD ROAD, 150± EAST OF SWAMP CREEK AND 200± NORTH OF POWER LINES.

**S3**  
**S10 | S11**  
**T23N R5E**  
**CC**  
 CORNER NO. 8  
 FD. 2 1/2" GLO BRASS CAP ON A 2" IRON PIPE  
 1938  
 (NO ACCESSORIES TIED)

FD. A PINE STUMP HOLE BEARS S44°E, 54.1'  
 REC. A 26" SUGAR PINE BEARS S44°E, 54.1' (GLO 1938)  
 FD. A 33" SUGAR PINE BEARS N46°W, 27.3' -HB  
 REC. A 30" SUGAR PINE BEARS N46°W, 19.8' (GLO 1938)  
 A 12" YELLOW PINE BEARS S39°W, 22.5' -SBT

FD. DEAD AND STANDING OAK BEARS S76°E, 18.3' -VS  
 REC. A 36" BLACK OAK BEARS S79°E, 18.5' (GLO 1938)  
 FD. A 19" BLACK OAK BEARS N71 1/2°E, 27.7' -HB  
 REC. 14" BLACK OAK BEARS N71 1/2°E, 29.0' (GLO 1938)  
 FD. A 13" CEDAR BEARS N1 1/4°E, 27.9' -HB  
 REC. A 5" CEDAR BEARS N1 1/4°E, 29.0' (GLO 1938)  
 FD. A 25" CEDAR BEARS S72°E, 41.8' -HB  
 REC. A 14" CEDAR BEARS S72°E, 41.6' (GLO 1938)  
 A 6" WHITE FIR BEARS S24°W, 61.2' -SBT  
 A 6" YELLOW PINE BEARS N35°W, 21.5' -SBT

**T24N R5E**  
**S35**  
**S2 | S1**  
**T23N R5E**  
**CC**  
 CORNER NO. 9  
 FD. A 2 1/2" GLO BRASS CAP ON A 2" IRON PIPE. CORNER FALLS ON THE WEST BANK OF A SMALL NORTH-SOUTH DRAW, 7± EAST TO CENTER OF DRAW.  
 (NO ACCESSORIES TIED)

**T23N R5E**  
**S3 | S2**  
**S11**  
 CORNER NO. 3  
 FD. A 2 1/2" GLO BRASS CAP ON A 2" IRON PIPE. CORNER FALLS ON A VERY STEEP SLOPE AMONG VERY LARGE GRANITE BOULDERS AND 200± SOUTH OF A CREEK.  
 1938

**1/4 S35**  
**S2**  
 CORNER NO. 6  
 FD. A 2" BRASS CAP ON A 1" IRON PIPE IN A MOUND OF STONE. CORNER FALLS ON A STEEP SOUTHEAST SLOPE.  
 1935

FD. AN 11" CEDAR BEARS N21°E, 12.1' -HB  
 REC. A 6" CEDAR BEARS N23°E, 12.5' (GLO 1875)  
 FD. AN 8" WHITE OAK BEARS S42°E, 9.0' -HB  
 REC. A 5" WHITE OAK BEARS S44°E, 9.9' (GLO 1875)  
 FD. AN 18" CEDAR BEARS N57°W, 32.9' -HB  
 REC. A 10" CEDAR BEARS N57°W, 31.7' (GLO 1875)  
 FD. A 20' X 10' X 10' GRANITE ROCK SOUTH 2.4'  
 REC. A GRANITE OUTCROP 10' X 10' X 10' SOUTH 2.3' (GLO 1875)

FD. A 17" BLACK OAK BEARS N20°E, 38.8' -HB  
 REC. A 9" BLACK OAK BEARS N20 1/4°E, 38.3' (GLO 1875)  
 FD. DEAD AND DOWN BLACK OAK BEARS S34°E, 11.7' TO CENTER OF REMAINS  
 REC. A 9" BLACK OAK BEARS S34 1/2°E, 12.2' (GLO 1875)  
 FD. A 33" YELLOW PINE SNAG BEARS S20°W, 17.8' -HB  
 REC. A 22" YELLOW PINE BEARS S20°W, 17.8 (GLO 1938)  
 FD. A 33" YELLOW PINE SNAG BEARS N59 1/2°W, 28.7' -HB  
 REC. A 24" YELLOW PINE BEARS N59 1/2°W, 28.4' (GLO 1938)  
 A 6" BLACK OAK BEARS S45°E, 5.4' -SBT

**RECORD OF SURVEY**

FOR

**USDA FOREST SERVICE**

IN SECTIONS 1, 2, 3, 4, 9, 10, & 11 IN T23N, R5E AND IN SECTIONS 34, 35, & 36 T24N R5E MDM

IN THE

UNINCORPORATED AREA OF PLUMAS COUNTY, STATE OF CALIFORNIA

**DEL TERRA INC.**  
 SURVEYING  
 P.O. BOX 4632  
 REDDING, CA 96099  
 PHONE (916) 241-8050

SCALE: 1" = 1' DATE: JUNE, 1992

SHEET: 2 OF 2