

24	T24N R13E C1/4 S13 LS 5623 1989	1	24	RECORD: NOTHING SET FOUND: NOTHING SET: STD USFS MON 8" ABOVE GROUND 18"X18"X4" MOS FWB: 24" PINE S 00°36' W 21.0 FT SCRIBED "C 1/4 S13BT" 24" PINE N 89°34' W 78.5 FT SCRIBED "C 1/4 S13BT"	32	32	T24N R14E S17 S16 S20 S21 RCE 21673 1977	RECORD: (GLO) SET A STONE 24X15X6 IN A STONE MOUND 4 1/2 FEET IN DIAMETER AT BASE AND 2 FEET HIGH FOR CORNER TO SECTIONS 16,17,20,21 ON A BED OF ROCKS. FOUND: STD USFS MON 4" ABOVE GROUND IN A 36"X36"X6" MOS (5RS80) FWB: 11" JP S 44° E 68.5 FT (5RS80) 16" JP N 86° W 24.8 FT (5RS80) 16" JP N 06° W 52.0 FT (5RS80)	40	40	T24N R14E CE 1/16 S17 LS 5623 1989	RECORD: NOTHING SET FOUND: NOTHING SET: STD USFS DRIVE-IN MON ON A 48" ROD, 6" ABOVE GROUND IN A 24"X24"X8" MOS FWB: 18" PINE S 07°06' E 9.6 FT SCRIBED "CE 1/16 S17BT" 23" PINE S 74°21' W 20.1 FT SCRIBED "CE 1/16 S17BT"
25	SE1/16 S13 LS 5623 1989	25	RECORD: NOTHING SET FOUND: NOTHING SET: STD USFS MON ON A 24" ROD, 12" ABOVE GROUND IN A 24"X24"X8" MOS FWB: 15" PINE N 55°32' E 6.8 FT SCRIBED "SE 1/16 S13BT" 10" PINE S 25°28' E 19.0 FT SCRIBED "SE 1/16 S13BT"	33	33	T24N R14E 1/4 S17 S20	RECORD: (GLO) SET A POST 4 FEET LONG AND 4 INCHES DIAMETER, 2 FEET DEEP FOR QUARTER SECTION CORNER FROM WHICH BEARS A YELLOW PINE 20 INCHES DIAMETER N.15W.85 LINKS. A YELLOW PINE 10 INCHES DIAMETER S.30°E.100 LINKS. FOUND: NOTHING SET: NOTHING, CALCULATED CORNER POSITION BY SINGLE PROPORTION	41	41	T24N R13E 1/4 S10 S11 LS 5623 WC 1990	RECORD: (GLO) NOTHING FOUND: NOTHING SET: STD USFS DRIVE-IN MON ON 36" OF ROD IN A 18"X18"X10" MOS FWB: 14" PP N74°12'W 123.6 FT SCRIBED "X BT"	
26	N1/16 S14 S13 LS 5623 1989	26	RECORD: NOTHING SET FOUND: NOTHING SET: STD USFS ROCK CAP IN A 12"X12"X4" MOUND OF MORTAR FWB: 10" PINE S 18°20' E 60.0 FT SCRIBED "N 1/16 S13BT" 7" PINE N 62°44' W 23.9 FT SCRIBED "N 1/16 S14BT"	34	34	T24N R14E S18 S17 S19 S20 1989	RECORD: (GLO) SET A STONE 18X12X10 IN A STONE MOUND 4 1/2 FEET IN DIAMETER AT BASE AND 2 FEET HIGH FOR CORNER TO SECTIONS 17,18,19,20 ON A BED OF ROCKS. FOUND: NOTHING SET: A STD USFS MON, 6" ABOVE GROUND IN A 36"X36"X5" MOS SET BY DOUBLE PROPORTION FWB: 5" IC S 75°09' E 21.4 FT SCRIBED "BT" 15" PINE S 65°18' W 76.6 FT SCRIBED "T24N R14E S19BT"	42	42	T24N S24 S18 S19 CC R14E	RECORD: (GLO) POST 5' LONG AND 4" DIA. 2' DEEP FOR CLOSING CORNER TO FRACTIONAL SEC'S 18,19 FWB: YELLOW PINE 28" N63°E 78 LINKS DIST. FIR 16" S29°E 84 LINKS DIST. FOUND: NOTHING CALCULATED POINT ONLY SET: NOTHING	
27	T24N R14E 7 8 18 17 LS 3181 1969	27	RECORD: (GLO) SET A POST 4 FEET LONG AND 4 INCHES DIAMETER, 2 FEET DEEP IN A STONE MOUND 4 1/2 FEET IN DIAMETER AT BASE AND 2 FEET HIGH FOR CORNER TO SECTIONS 7,8,17,18 ON A BED OF LAVA. FOUND: STD DWR MON 16" ABOVE GROUND IN A 42"X30"X6" MOS, ACCEPTED SET: NOTHING (ACCEPTED EXISTING MON) FWB: 26" PINE N 83°34' E 19.2 FT SCRIBED "T24N R14E S17BT" 22" PINE S 15°46' E 33.7 FT SCRIBED "T24N R14E S17BT" 18" PINE S 68°17' W 143.4 FT SCRIBED "T24N R14E S18BT"	35	35	T24N R14E 1/4 18 17 LS 3181 1969	RECORD: (GLO) SET A STONE 30X15X15 IN A STONE MOUND 4 1/2 FEET IN DIAMETER AT BASE AND 2 FEET HIGH FOR QUARTER SECTION CORNER ON A BED OF ROCKS. FOUND: STD DWR MON 18" ABOVE GROUND IN A 36"X36"X8" MOS, ACCEPTED AS BEST AVAILABLE EVIDENCE OF ORIGINAL CORNER LOCATION SET: NOTHING (ACCEPTED EXISTING MON) FWB: 13" PINE N 48°04' W 13.1 FT SCRIBED "1/4 S18 BT" 12" PINE N 06°26' E 22.4 FT SCRIBED "1/4 S17 BT"	43	43	T24N S25 S36 LS 4495 1986	RECORD: (GLO) POST 4' LONG 4" DIA. 2' IN GROUND FOR COR TO SEC'S 25,36 FWB: FIR 8" DIA. N27°W 24 LKS DIST. YELLOW PINE 7" DIA. S27°30'W 8 LKS DIST. FOUND: STD USFS MON 8" ABOVE GROUND 36"X36"X8" MOS W/ A 1" IP 24" LONG METAL TAG LS 2322 FWB: WF 22" DIA. N25W APPROX 16.6 FT DIST. (SCRIBING VISIBLE) JP 23" DIA. S33W 6.1 FT DIST. (SCRIBING VISIBLE) SET: NOTHING	
28	T24N R14E W1/16 S17 LS 5623 1989	28	RECORD: NOTHING SET FOUND: NOTHING SET: A STD USFS MON 2" ABOVE GROUND IN A 24"X24"X1" MOS FWB: 5" JP N 04°07' W 4.5 FT SCRIBED "W 1/16 S8BT" 16" JP S 74°18' E 74.0 FT SCRibed "W 1/16 S8BT"	36	36	T24N R14E N1/16 S18 S17 LS 5623 1989	RECORD: (GLO) NOTHING SET FOUND: NOTHING SET: STD USFS DRIVE-IN MON ON A 36" ROD, 4" ABOVE GROUND IN A 24"X24"X4" MOS FWB: 7" PINE S 67°50' E 19.2 FT SCRIBED "N 1/16 S17BT" 22" PINE N 38°53' W 6.9 FT SCRIBED "N 1/16 S18BT"	44	44	T23N T24N S1 S31 CC T23N R14E	RECORD: (GLO) YELLOW PINE 30" DIA. FOR CLOSING CORNER TO T23,24N R13E FOUND: P.PINE 8" TALL DECAYED STUMP SCRIBING ON SE FACE VISIBLE BUT ILLEGIBLE (ACCEPTED AS CORNER LOCATION) SET: NOTHING	
29	T24N 8 17 R14E	29	RECORD: (GLO) SET A POST 4 FEET LONG, 4 INCHES DIAMETER 2 FEET DEEP IN A MOUND ?? IN DIAMETER AT BASE AND 2 FEET HIGH WITH PITS 24X18X12 FOR QUARTER SECTION CORNER. FOUND: STD DWR MON 4" ABOVE GROUND 42"X42"X4" MOS, ACCEPTED AS BEST AVAILABLE EVIDENCE OF ORIGINAL CORNER LOCATION SET: NOTHING	37	37	T24N R14E NW1/16 S17 LS 5623 1989	RECORD: (GLO) NOTHING SET FOUND: NOTHING SET: STD USFS DRIVE-IN MON ON A 24" ROD, 8" ABOVE GROUND IN A 30"X30"X12" MOS FWB: 12" JP S 72°19' W 95.0 FT SCRIBED "NW 1/16 S17BT" 8" JP S 14°56' E 47.9 FT SCRIBED "NW 1/16 S18BT"	45	45	T24N R14E S31 S32 S6 S5 T23N R14E	RECORD: (GLO) STONE 20"X15"X6" IN MOS 4 1/2 FT DIA. AT BASE 2 FT HIGH FOR 1/4 SEC. COR. FOUND: NOTHING CALCULATED POINT ONLY SET: NOTHING	
30	T24N 8 9 17 16 R14	30	RECORD: (GLO) SET A POST 5 FEET LONG AND 4 INCHES DIAMETER, 2 FEET DEEP IN A MOUND 4 1/2 FEET IN DIAMETER AT BASE AND 2 FEET HIGH WITH PITS 24X18X12 FOR CORNER TO SECTIONS 8,9,16,17. FOUND: STD DWR MON 12" ABOVE GROUND, NO MOS, ACCEPTED AS BEST AVAILABLE EVIDENCE OF ORIGINAL CORNER LOCATION SET: NOTHING	38	38	T24N R14E C N1/16 S17 S20 1989	RECORD: (GLO) NOTHING SET FOUND: NOTHING SET: STD USFS DRIVE-IN MON ON A 24" ROD, 6" ABOVE GROUND IN A 24"X24"X6" MOS FWB: 13" JP N 64°09' E 24.1 FT SCRIBED "CN 1/16 S17BT" 20" JP S 01°33' W 7.5 FT SCRIBED "CN 1/16 S17BT"	46	46	T24N R14E S32 S33 S5 S4 LS 5856 1988	RECORD: (GLO) POST 4' LONG 4" DIA. 2' DEEP FOR COR TO SEC'S 4,5,32,33 FWB: PINE 15" DIA. N29°W 32 LKS DIST. PINE 20" DIA. S40°W 47 LKS DIST. PINE 12" DIA. N36°E 77 LKS DIST. PINE 08" DIA. S51°E 95 LKS DIST. FOUND: 2 1/2" USDA ALUM. PIPE W/ CAP (LS 5856) 12" ABOVE GROUND, 3'X3'X1" MOS FWB: PINE STUMP 20" DIA. S39°13'W 31.57 FT DIST (GLO) PINE 14" DIA. N64°41'E 15.10 FT DIST (NEW BT) PINE 9" DIA. N70°09'W 23.80 FT DIST (NEW BT) PINE 9" DIA. S66°02'E 14.70 FT DIST (NEW BT) SET: NOTHING	
31	T24N R14E 1/4 17 16 LS 3181 1969	31	RECORD: (GLO) SET A POST 4 FEET LONG AND 4 INCHES DIAMETER, 2 FEET DEEP IN A MOUND 4 1/2 FEET IN DIAMETER AT BASE AND 2 FEET HIGH WITH PITS 24X18X12 FOR QUARTER SECTION CORNER. FOUND: STD DWR MON, 9" ABOVE GROUND IN A 42"X30"X8" MOS ACCEPTED AS BEST AVAILABLE EVIDENCE OF ORIGINAL CORNER LOCATION FWB: 26" JP S 30 1/2 E 60.7 FT W/ CLOSED FACE AND BT TAG (NO RECORD) 32" JP N 59° W 77.9 FT W/ CLOSED FACE AND BT TAG (NO RECORD) SET: NOTHING	39	39	T24N R14E NE 1/16 S17 LS 5623 1989	RECORD: (GLO) NOTHING SET FOUND: NOTHING SET: STD USFS DRIVE-IN MON, 6" ABOVE GROUND IN A 24"X24"X6" MOS					

RECORD OF SURVEY

LOCATED IN SECTIONS 11 & 13 T24N R13E AND SECTION 17 T24N R14E MDM, COUNTY OF PLUMAS, STATE OF CALIFORNIA, FOR THE PLUMAS NATIONAL FOREST, P.O. BOX 11500 QUINCY, CA. 95971.

SURVEY CREW L.GROSS
R.KNOTTGEN
D.HOBBS
B.WILLARD
H.STOKES

DRAWN BY S.SASSER SHEET: 5 OF 5