

CORNER MONUMENTATION

1 NE CORNER SECTION 6	2 NE CORNER SECTION 5	3 NE CORNER SECTION 4	4 SW CORNER SECTION 6	5 1/4 CORNER SECTION 6 & 7	6 N E CORNER SECTION 7	7 NW CORNER SECTION 9
FOUND 2" IP WITH 2 1/2" 1938 GLO BRASS CAP IN A MOS ACCESSORIES NOT TIED. SEE (R2)	FOUND 2" IP WITH 2 1/2" 1938 GLO BRASS CAP IN MOS ACCESSORIES NOT TIED. SEE (R2)	CORNER POSITION CALCULATED USING (R3) NOT FIELD TIED TO THIS SURVEY	FOUND 2" IP WITH 2 1/2" 1938 GLO BRASS CAP IN MOS ACCESSORIES NOT TIED. SEE (R2)	SET U.S.F.S. 3 1/2" ALUM. CAP ON 5/8" REBAR IN 2' X 2' X 1' MOS FROM WHICH BEARS: SET 8" LIVE OAK N65°W 12.1' SET 7" P PINE S32°E 25.1'	SET U.S.F.S. 3 1/2" ALUM. CAP ON 5/8" REBAR FROM WHICH BEARS: SET 16" RED FIR S35°58'W 123.9' SET 4" RED FIR N55°E 35.5' SET 18" CEDAR N36°58'W 112.6'	SET U.S.F.S. 3 1/2" ALUM. CAP ON 5/8" REBAR IN 2' X 2' X 1' MOS FROM WHICH BEARS: SET 5" LIVE OAK N83°56'W 15.5' SET 12" LIVE OAK N83°56'W 16.6' SET 27" P PINE N82°31'W 42.2' SET 22" S PINE S80°8'W 38.2'
8 1/4 CORNER SECTION 4 & 9	9 NE CORNER SECTION 10	10 WITNESS CORNER TO 1/4 CORNER SECTIONS 7 & 8	11 WITNESS CORNER TO 1/4 CORNER SECTIONS 8 & 9	12 WITNESS CORNER TO W 1/4 SECTION 7	13 1/4 CORNER SECTION 8 & 9	14 CE 1/16 CORNER SECTION 9
SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR IN 4' X 4' X 1' MOS FROM WHICH BEARS: SET 16" CEDAR S19°E 12.7' SET 19" P PINE N15°W 14.9'	FOUND ORIG. RED FIR WITH VISIBLE SCRIBES (ORIG. BT) SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR AT RECORD BEARING AND DISTANCE FROM ORIG. BT FROM WHICH BEARS: FOUND 38" RED FIR S60°E 85.8' (R1) SET 7" RED FIR N70°13'E 57.7' SET 28" RED FIR S31°26'E 25.1' SET 28" RED FIR S41°21'W 37.1'	SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR FROM WHICH BEARS: SET 5" P PINE S26°E 8.3' SET 10" CEDAR N45°W 7.0'	SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR IN 2' X 2' X 1' MOS FROM WHICH BEARS: SET 13" LIVE OAK S55°W 32.4' SET 4" LIVE OAK N30°E 22.3'	FOUND 1" IP WITH 2 1/2" 1938 GLO BRASS CAP FROM WHICH BEARS: SET 13" LIVE OAK S55°W 32.4' SET 4" LIVE OAK N30°E 22.3'	SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR FROM WHICH BEARS: SET 20" D FIR N87°W 22.8' SET 12" D FIR S50°E 8.1'	SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR FROM WHICH BEARS: SET 13" CEDAR S65°W 16.6' SET 12" W FIR N8°E 28.7'
15 SW CORNER SECTION 7	16 1/4 CORNER SECTION 7 & 18	17 SE CORNER SECTION 7	18 E 1/16 CORNER SECTION 9 & 16	19 SE CORNER SECTION 10	20 WITNESS CORNER TO N1/16 CORNER SECTIONS 13 & 18	21 WITNESS CORNER ON N1/16 CORNER SECTIONS 13 & 18
FOUND 2" IP WITH 2 1/2" 1938 BRASS CAP IN 2' X 3' X 1' MOS ACCESSORIES NOT TIED. SEE (R2)	SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR FROM WHICH BEARS: SET 5" D FIR N13°W 17.5' SET 4" D FIR S80°W 23.5'	SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR IN 2' X 2' X 1' MOS FROM WHICH BEARS: SET 12" D FIR S76°W 18.4' SET 11" D FIR N54°W 23.2' SET 9" CEDAR N52°E 7.3'	SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR FROM WHICH BEARS: SET 20" RED FIR S52°33'E 96.3' SET 6" CEDAR S37°25'W 70.9'	FOUND U.S.F.S. 3 1/2" ALUM CAP ON ALUM ROD IN 2' X 2' X 1' MOS LS 5623 1991 FROM WHICH BEARS: FOUND DECAYED STUMP WITH VISIBLE SCRIBING S85°W 59.4'(R1) FOUND 36" S PINE S85°W 59.4'	SEE DETAIL 2 OF SHEET 1 OF 2 SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR FROM WHICH BEARS: SET 18" P PINE S8°E 32.5' SET 20" P PINE N20°W 9.5'	SEE DETAIL 2 OF SHEET 1 OF 2 SET U.S.F.S. 3 1/2" ALUM CAP ON 5/8" REBAR FROM WHICH BEARS: SET 10" LIVE OAK S12°E 8.8' SET 15" D FIR N20°W 12.7'
22 WITNESS CORNER TO W 1/4 CORNER SECTION 18 SEE DETAIL 2 OF SHEET 1 OF 2 FOUND 2" IP W/ 2 1/2" 1938 GLO BRASS CAP ACCESSORIES NOT TIED. SEE (R2)	23 SE CORNER SECTION 31	24 SW CORNER SECTION 16	25 1/4 CORNER SECTION 16 & 15	26 NE CORNER SECTION 11		
FOUND STANDARD BLM MONUMENT IN 3' X 3' X 1' MOS ACCESSORIES NOT TIED. SEE (R4)	FOUND STANDARD BLM MONUMENT IN 3' X 3' X 1' MOS ACCESSORIES NOT TIED. SEE (R4)	CORNER POSITION CALCULATED USING (R3) NOT FIELD TIED TO THIS SURVEY	CORNER POSITION CALCULATED USING (R3) NOT FIELD TIED TO THIS SURVEY	FOUND AND ACCEPTED ORIGINAL MOS PER (R1) FROM WHICH BEARS: ORIGINAL ACCESSORIES WITH VISIBLE SCRIBING: (48" S PINE STUMP S57°47'W 10.5') (54" S PINE STUMP N34°31'W 12.5') (60" S PINE STUMP N59°48'E 8.6') SET 9" RED FIR S22°11'E 22.6' SET 9" RED FIR S26°08'W 48.0' SET 10" RED FIR N21°39'E 10.7' SET 10" RED FIR N12°52'W 46.3'		

PROJECT HISTORY

T.F. BATTLEFIELD JULY 19, 1869 - PARTIAL SURVEY OF TOWNSHIP LINE
 E.A. VON SCHMIDT JUNE 18, 1875 - COMPLETION OF TOWNSHIP AND RANGE LINES
 R1 E.A. VON SCHMIDT JUNE 15, 1875 - SUBDIVISION OF TOWNSHIP
 Wm MINTO JUNE 12, 1880 - COMPLETION SURVEY
 M.F. REILLY MARCH 6, 1884 - SOUTH LINE OF TOWNSHIP RETRACEMENT
 R2 ROGER F. WILSON GLO APRIL 15, 1938 - GROUP NO. 158 RETRACEMENT OF TOWNSHIP EXTERIOR.
 R3 10 R/S 40 BY DEL TERRA INC. OCT 1994
 R4 BLM DEPENANT RESURVEY JUNE 1978, GROUP NO. 720


RECORD OF SURVEY
FOR
SIERRA PACIFIC IND.

BEING SECTIONS 7, 8 AND 9, TOWNSHIP 23 NORTH, RANGE 6 EAST, MDM PLUMAS COUNTY CALIFORNIA

96-01-002

JANUARY, 1997

SHEET 2 OF 2



L & L SURVEYING

1007 BILLE ROAD PO BOX 671 PARADISE, CA 95967 (916)877-4300