

Record Bearing Trees per 6 RS 106
 30" Pine Blazed & Scribed S 6 1/2' W, 20.8'
 7" Cedar Blazed & Scribed S 55' 1/2' W, 20.5'
 10" Cedar Blazed & Scribed N 69 1/2' W, 12.2'

Basis of Bearings

The Basis of Bearings of this map is the North-South centerline of Section 4, from the Center 1/4 corner to the North 1/4 corner shown as N00°00'05"W, in Book 6 of Record of Surveys at page 106, Plumas County records.


Record Bearing Trees per 7 RS 109

12" Pine N 52' W, 51.3'
 12" Pine N 20' W, 49.9'
 9" Oak N 64' W, 14.0'
 10" Cedar N 3' E, 59.8'
 15" Fir S 12' E, 69.2'
 4" Fir S 44' W, 10.2'

Northeast Corner of Section 4
 Found Std. U.S.F.S. Aluminum Cap per 7 RS 109 stamped as shown

SURVEYOR'S STATEMENT

This map correctly represents a survey made by me or under my direction in conformance with the requirements of the Land Surveyors' Act at the request of Don Beskeen in June, 1995.



John W. Hamby
 John W. Hamby LS 2843

COUNTY SURVEYOR'S STATEMENT

This map has been examined in accordance with Section 8766 of the Land Surveyors' Act this 6TH day of July, 1995.


R Tom Hunter
 R. Tom Hunter RCE 30515
 PLUMAS COUNTY SURVEYOR
 License Expiration Date 3/31/96

RECORDER'S STATEMENT

Filed this 6TH day of July, 1995 at 1:45 P.m. in Book 10 of Record of Surveys, at page 73, at the request of the County Surveyor.

Fee \$ 800
 File No. 3845

Judith Wells
 County Recorder
 by *Lori Lini*
 Deputy



North 1/4 Corner found B.L.M. Brass Cap per 6 RS 106 stamped as shown

T24N R10E
 1/4 S33
 S4
 T23N
 1971

(West 40.00 chs. per G.L.O.)

Basis of Bearings
 (S 00°00'05" E 2006.68' R1)

2006.37'

893.27'

Lot 2

26.89 acres

1324.54'

S 89°44'39" E

2649.08'

1324.54'

Lot 1

N 00°07'15" W

876.78'

2645.77'

1322.88'

1322.89'

N 89°01'46" W

33

34

4

3

T24N R10E
 S33 | S34
 S4 | S3
 RCE 22836
 1984

860.29'

1941.05'

(35.92 chs. per G.L.O.)

N 00°14'45" W

1080.76'

Record Bearing Trees per 6 RS 106

30" Fir snag 12' high w/scribing, S 30 1/2' E, 11.9'
 31" Fir w/scribing N 63' W, 26.1'
 8.5" Fir W/scribing S 45 1/2' E, 26.7'

Record Bearing Trees per 6 RS 106
 Scribed 9" Cedar S 13' W, 28.4'
 Scribed 15" Fir N 41' W, 4.7'

Center 1/4 Corner Section 4
 Found Std. U.S.F.S. Aluminum Cap per 6 RS 106 stamped as shown

East 1/4 Corner of Section 4
 Found Std. U.S.F.S. Aluminum Cap per 6 RS 106 stamped as shown

T24N R10E
 C 1/4
 S 4
 1983
 LS 4976

T24N R10E
 1/4
 S4 | S3
 1983
 LS 4976

N 89°33'25" E

2653.74'

(N 89°32'56" E 2654.06' R1)

LEGEND

- FOUND point as described
- SET 5/8" rebar with Aluminum Cap LS 2843
- (R1) RECORD per 6 RS 106

**RECORD OF SURVEY
 for
 Donald Beskeen**

Lot 2 of the NE 1/4 of Section 4
 T. 23 N., R. 10 E., M.D.M.

Plumas County ~ California
 Scale 1" = 200' June, 1995

Hamby Surveying Inc.
 P.O. Box 1209
 Portola, CA 96122
 (916) 832-5571