

**MONUMENT SCHEDULE
(CONT.)**

<p>21 T26NR10E S28 1/4 S33 LS 3966 1990</p>	<p>FD. AL. CAP ON 5/8" ROD IN 20"x 6" S.M. 7" S.P. SNAG, V.S. N60°12'W, 19.2' (N57°W, 19.4')(1) 6" W.F., H.B., S13°38'W, 18.5' (S12°30'W, 18.7')(1) 8" D.F., N.T., N66°23'W, 33.2'</p>	<p>34 FD. 3/4" I.P., L.S. 3621, IN 30"x 6" S.M. 15" W.F., H.B., N69°18'W, 12.7' (N75°W, 12.6')(2) 19" W.F., V.S., S52°34'E, 8.1' (S49°E, 7.9')(2)</p>	<p>48 S32 S33 T.S.F. MS6317 RCE29700 1998</p>	<p>SET C.R. IN 20"x 6" S.M. 11" D.F., N.T., N31°54'E, 23.7' 6" D.F., N.T., N18°17'W, 29.6'</p>
<p>22 S28 E1/16 S33 RCE29700 1998</p>	<p>SET C.R. IN 36"x 8" S.M. 12" W.F., N.T., N16°41'W, 22.3' 7" D.F., N.T., S79°14'W, 17.4'</p>	<p>35 FD. 3/4" I.P. LS 3621 IN 20"x 6" S.M. 11" D.F., V.S., S1°23'E, 32.2' (NO RECORD) 19" W.F., H.B., S65°41'E, 21.3' (S66°E, 21.2')(2)</p>	<p>49 S.F.2 MS6317</p>	<p>FD. ORIGINAL 1-1/2" I.P. IN 30"x 6" S.M. 42"D.F. STUMP, N.V., N4°53'E, 9.8' (N3°30'E, 9.8')(8)</p>
<p>23 T26NR10E S28 S27 S33 S34 LS 3966 1990</p>	<p>FD. AL. CAP ON 5/8" ROD IN 36"x 8" S.M. 13" D.F., H.B., S52°20'W, 18.0' (S51°45'W, 18.0')(1) 11" D.F., H.B., S15°39'E, 4.1' (S19°30'E, 4.1')(1) 7" D.F., H.B., N40°21'E, 17.5', (N45°E, 17.6')(1) 9" CED. V.S., N1°07'E, 9.1' (N1°30'W, 9.1')(1)</p>	<p>36 S29 S-PLU MS1211A RCE29700 1998</p>	<p>50 MS6317 T.S.F. S32 S33 RCE29700 1998</p>	<p>SET C.R. IN 24"x 6" S.M. 7" D.F., N.T., S13°22'W, 8.3' 9" D.F., N.T., S46°27'E, 10.5'</p>
<p>24 T26NR10E N1/16 S31 S32 RCE29700 1998</p>	<p>THE CORNER PER RS BK-4 PG-60 THRU 63 WAS LOST. POSITION DETERMINED FROM EXIST. BEARING TREE WITH MEASUREMENT CHECKS TO ADJACENT CORNERS. SET C.R. IN WEST SHOULDER OF SKID ROAD, CAP IS 6" BELOW GRADE. 18" S.P., V.S., S88°38'E, 25.7' (S88°E, 24.5')(3) 10" D.F., N.T., S5°44'W, 12.4'</p>	<p>37 M.S. 1211A 1 PLUMAS S29 Q.M. RCE29700 1998</p>	<p>51 MS6317 T.S.F. N S32 RCE29700 1998</p>	<p>SET C.R. IN 32"x 8" S.M. 8" P.P., N.T., N78°55'E, 16.8' 9" W.F., N.T., N21°41'E, 28.3'</p>
<p>25 T26NR10E C N1/16 S32 RCE29700 1998</p>	<p>SET C.R. IN 40"x 10" SM 10" W.F., N.T., N25°29'W, 22.2' 7" B.O., N.T., N32°12'E, 14.6'</p>	<p>38 MS1211A C PLU S29 RCE29700 1998</p>	<p>52 S.F.3 MS6317</p>	<p>FD. ORIGINAL 1-1/2" I.P. IN SCATTERED S.M. 28" CED. STUMP; V.S., S18°53'W, 21.1' (S20°55'W, 21.0')(8)</p>
<p>26 FD. 3/4" I.P., L.S. 2322, IN 16"x 4" S.M. ON NORTH SHOULDER OF SKID ROAD. 17" D.F., H.B., N65°55'W, 34.0' (N63°W, 34.9')(3) 11" D.F., N.T., N43°13'W, 54.1'</p>	<p>39 FD. ORIGINAL 1-1/2" I.P. IN 30"x 8" S.M. FOR CORNER NO. 3 OF THE PLUMAS QUARTZ MINE; PER: M.S. 6335 A & B.</p>	<p>40 C S29 PLU MS1211A RCE29700 1998</p>	<p>53 W.C. P2-2 MS6317</p>	<p>FD. ORIGINAL 1-1/2" I.P. WITNESS CORNER IN 38"x 20" S.M. ON SW'LY EDGE OF DIRT ROAD. 24" P.P., H.B., S29°02'E, 12.0' (S26°30'E, 11.5')(8)</p>
<p>27 NW1/16 S33 LS 3966 1990</p>	<p>FD. AL. CAPPED 5/8" ROD IN 24"x 6" S.M. A 3/4" I.P. TAGGED LS 3621, IS N33°14'47"W, 3.34' SET PER: (2), AND WAS REJECTED. 13" W.F., H.B., S83°08'E, 4.2' (NO RECORD) 17" W.F., V.S., N67°47'W, 12.7' (NO RECORD) 8" W.F., H.B., N75°20'E, 4.1' (N75°15'E, 4.2')(1) 8" W.F., H.B., S13°35'W, 6.2' (S16°30'W, 6.2')(1)</p>	<p>41 S29 PLU MS1211A RCE29700 1998</p>	<p>54 MS6317 PREMIUM N S32 RCE29700 1998</p>	<p>SET C.R. IN 30"x 6" S.M. COR. #2 OF WEST PLUMAS MILL SITE A 24"x 8" S.M., S70°57'E, 49.5', WITH RECORD 32"D.F. B.T.; (PER: MS 6335A & B) 14" D.F., N.T., N52°05'E, 32.1' 7" D.F., N.T., S87°16'E, 46.1'</p>
<p>28 C N1/16 S33 LS 3966 1990</p>	<p>FD. AL. CAPPED 5/8" ROD IN 24"x 6" S.M. 7" D.F., H.B., S81°16'W, 12.7' (S82°45'W, 12.7')(1) 6" D.F., H.B., S15°44'E, 7.3' (S15°E, 7.3')(1)</p>	<p>42 C4 MS6317</p>	<p>55 MS6317 PREMIUM S32 RCE29700 1998</p>	<p>FD. ORIGINAL 1-1/2" I.P. IN S.M. SET C.R. IN SAME LOCATION REBUILT 30"x 12" S.M. LEFT I.P. ON TOP OF S.M. N1/4 COR. SECTION 32, N37°33'22"W, 1250.27'; (N37°07'50"W, 1243.06')(8) 42" D.F. STUMP, H.B., S34°02'W, 25.3'; (S51°15'W, 32.8')(8) 9" W.F., N.T., S32°27'W, 17.8' 8" D.F., N.T., S50°E, 4.5'</p>
<p>29 T26NR10E S32 C1/4 LS 3966 1989</p>	<p>FD. AL. CAPPED 5/8" ROD IN 24"x 6" S.M. 28" W.F., H.B., S39°51'W, 15.2' (S51°15'E, 15.3')(1) 17" D.F., H.B., N64°04'E, 21.2' (N72°30'E, 21.6')(1)</p>	<p>43 S32 T.L.A. MS 6317 RCE29700 1998</p>	<p>56 MS6317 T.L.A. S32 T.S.F. RCE29700 1998</p>	<p>FD. ORIGINAL 1-1/2" I.P. BURIED IN FILL ON NORTH SIDE OF SKID ROAD. S 1/4 COR. OF SECTION 29, S15°49'42"W, 408.46' SET C.R. IN OLD SKID ROAD IN 6"x 4" S.M. BY SINGLE PROPORTION BETWEEN COR'S. #3 & #4 OF THE CRYSOLOTE LODE, PER: MS 631. S 1/4 COR. SECTION 29, N89°33'05"W, 561.77'; (N88°59'W, 557.37')(8) 7" D.F., N.T., S54°27'W, 14.6' 10" D.F., N.T., S19°29'E, 19.6'</p>
<p>30 1/4 T26NR10E S32 S33 1970</p>	<p>FD. BLM B.C. IN 36"x 12" S.M. 14"D.F., H.B., S23°31'E, 13.1' (S24°E, 13.2')(1) 16" D.F., H.B., N40°55'W, 37.7' (N40°W, 40.0')(1)</p>	<p>44 S29 S32 TLA MS6317 RCE29700 1998</p>	<td> </td>	
<p>31 W1/16 C S33 RCE29700 1998</p>	<p>SET C.R. IN 24"x 6" S.M. 6" B.O., N.T., N65°08'E, 16.3' 9" B.O., N.T., N15°08'E, 22.5'</p>	<p>45 LA4 MS6317</p>	<td> </td>	
<p>32 RM T26N R10E S33 10 1/4 COR 1970</p>	<p>FD. ORIGINAL TREE CORNER (28" D.F.) AND BLM B.C. REFERENCE MONUMENT IN 30"x 6" S.M. R.M. S42°57'07"W, 18.0' (S45°W, 18.0')(6) 26" D.F., H.B., S51°18'E, 25.1' (S51°E, 24.4')(1) 30" S.P., H.B., S83°38'W, 19.8' (S85°W, 20.5')(1)</p>	<p>46 S29 S32 MS6317 RCE29700 1998</p>	<td> </td>	
<p>33 W1/16 C S34 LS 3966 1990</p>	<p>FD. AL. CAPPED 5/8" ROD IN 32"x 8" S.M. 12" D.F., H.B., S40°42'E, 5.5' (S43°15'E, 5.5')(1) 7" S.P., V.S., N16°43'E, 7.1' (N27°30'E, 7.1')(1)</p>	<p>47 MS 6317 S32 TLA 1 TSF RCE29700 1998</p>	<td> </td>	

MONUMENT SCHEDULE LEGEND:

AL. = ALUMINUM	I.P. = IRON PIPE
B.C. = BRASS CAP	N.T. = NEW BEARING TREE, APPROPRIATELY SCRIBED
B.O. = BLACK OAK	N.V. = NOTHING VISIBLE
B.T. = BEARING TREE	P.P. = PONDEROSA PINE
CED. = CEDAR	S.M. = STONE MOUND
C.R. = 5/8" REBAR, WITH ALUMINUM CAP	S.P. = SUGAR PINE
D.F. = DOUGLAS FIR	V.S. = VISIBLE SCRIBING
FD. = FOUND	W.F. = WHITE FIR
H.B. = HEALED BLAZE	

RECORD LEGEND:

- (1) RECORD DATA PER: RECORD OF SURVEY BK-9, PG-5 TO 14.
- (2) RECORD DATA PER: RECORD OF SURVEY BK-4, PG-97
- (3) RECORD DATA PER: RECORD OF SURVEY BK-4, PG-60 TO 63.
- (4) RECORD DATA PER: RECORD OF SURVEY BK-3, PG-106.
- (5) RECORD DATA PER: PARCEL MAPS; BK-9, PG-46.
- (7) RECORD DATA PER: MINERAL SURVEY NO 6335 A&B.
- (8) RECORD DATA PER: MINERAL SURVEY NO. 6317.
- (9) RECORD DATA PER: ORIG. G.L.O. SURVEY BY D. BROWN, IN 1869.
- (99) CORNER NUMBER AS SHOWN ON SHEETS 2, 3, & 4.

MONUMENT SCHEDULE NOTES:

1. REFERENCE TREES HAVE 16d NAILS IN CENTER FRONT AT BOTTOM OF FACE. ANGLES ARE TO THE FACE NAILS. DISTANCES ARE MEASURED TO A 16d NAIL IN SIDE NOTCH @ CENTER BASE OF TREE.

RECORD OF SURVEY

FOR
THE CHY COMPANY
BEING PORTIONS OF
SECTIONS 28, 29, 32, 33, & 34, T.26 N., R.10 E., M.D.M.

IN THE UNINCORPORATED TERRITORY OF
THE COUNTY OF PLUMAS
STATE OF CALIFORNIA

S. & E. ENGINEERING CO.
NEVADA CITY CALIFORNIA
SCALE AS SHOWN OCTOBER, 1998