




Corner Notes:

1 Found corner as noted in 10 R.S. page 110. A Standard U.S.D.A. monument 5" above ground in a 1 1/2' stone mound.


From which bears:
 A 18 1/2" Pine N86°15'E, 110.09', scribed: T28NR7E18BT.
 A 5 1/2" Pine S21°52'E, 36.62', scribed: XBT.
 A 12" Pine S58°22'W, 19.91', scribed: T28NR6ES24BT.
 A 24" Pine N15°59'W, 67.37', scribed: T28NR6ES13BT.

6 Found a 2" dia. Iron Pipe LS 2322 in a 1 1/2' dia. by 6" high stone mound.



From which bears:
 A 22 1/2" Pine N25°00'E, 14.17', with healed blaze.
 <A 16" Pine N25°00'E, 14.30'.>
 A 27" Pine S63°37'W, 10.23', with healed blaze.
 <A 22" Pine S62°00'W, 10.20'.>

11 Set a Standard U.S.D.A. Monument 24" in ground 4" above in a 2' dia. stone mound.



From which bears:
 A 16 1/2" Pine N70°00'W, 23.20', scribed: CW1/16S19BT.
 A 16 1/2" Pine S16°06'W, 34.83', scribed: CW1/16S19BT.

16 Set a Standard U.S.D.A. Monument 22" in ground 6" above in a 1 1/2' dia. stone mound. Placed a magnet under the monument.



From which bears:
 A 20" White Fir Snag, N24°25'W, 9.45', with visible scribing.
 A 16 1/2" White Fir, S59°40'E, 50.60', with visible scribing.
 A 22 1/2" White Fir, S24°50'W, 34.00', with healed blaze.

2 Found corner as noted in 10 R.S. page 110. A Standard U.S.D.A. Monument 4" above ground in a 1 1/2' dia. stone mound.



From which bears:
 A 16 1/2" Pine S66°17'E, 17.31', (Record a 14" Pine S67°E, 17.4').
 A 18" Pine N44°40'W, 17.18', (Record a 14" Pine N45°W, 17.3').

7 Found a 2" dia. Iron Pipe LS 2322, 9" above ground in a 1 1/2' dia. by 6" high stone mound.


From which bears:
 A 19" Pine N57°45'W, 32.46', with healed blaze.
 <A 14" Pine N58°30'W, 32.50'.>
 A 17" Pine S7°30'W, 10.51', open face with visible scribing.
 <A 15" Pine S6°30'W, 10.80'.>


12 Set a Standard U.S.D.A. Monument 24" in ground 4" above in a 2' dia. stone mound. Placed a magnet under the monument.


From which bears:
 A 19" Pine N57°45'W, 32.46', with healed blaze.
 <A 14" Pine N58°30'W, 32.50'.>
 A 17" Pine S7°30'W, 10.51', open face with visible scribing.
 <A 15" Pine S6°30'W, 10.80'.>


17 Found a 33" Fir Snag Tree Corner.


From which bears:
 A B.L.M. Brass Cap 4" above ground in a 1' dia. stone mound for Reference Monument. N41°54'E, 27.57'.
 A 20" White Fir Snag, N24°25'W, 9.45', with visible scribing.
 A 16 1/2" White Fir, S59°40'E, 50.60', with visible scribing.
 A 22 1/2" White Fir, S24°50'W, 34.00', with healed blaze.


1974 B.L.M. Remonumentation:
 A 33" Fir Tree Corner.
 A B.L.M. Reference Monument, N45°00'E, 27.00'.
 A 20" Fir, N24°00'W, 13 Links.
 A 10" White Fir, S55°00'E, 76 Links.
 A 18" White Fir, S29°00'W, 51 Links.

3 Found corner as noted in 10 R.S. page 110. A Standard U.S.D.A. monument 4" above ground in a 1 1/2' dia. stone mound.


From which bears:
 A 19" Pine N76°15'E, 17.62', (Record 14" Pine N74°E, 17.6').
 A 16" Pine S57°13'W, 17.36', (Record a 10" Pine S60°E, 17.4').
 A 1 1/4" Iron Pipe LS 2322 bears S89°35'E, 44.09', (Record N89°21'18"E, 43.68').
 A 28" dia. by 6" high Pine with open face and illegible scribing, bears N8°10'W, 32.58'.


8 Set a Standard U.S.D.A. Monument 22" in ground 6" above in a 1 1/2' dia. stone mound.


From which bears:
 A 17" Pine N48°28'W, 63.86', scribed: NE1/16S19BT.
 A 13" Pine S6°48'W, 35.80', scribed: NE1/16S19BT.


13 No original evidence found. At prorate position set a Standard U.S.D.A. Monument 24" in ground 4" above in a 1 1/2' dia. stone mound. Placed a magnet under the monument.


No Bearing Trees within reason.


From which bears:
 A 2' dia. by 2' high Stump, S32°00'W, 63.60', Placed a nail on the West side. Bearing by compass, distance by tape.
 A 2' dia. by 1' high Stump, S32°00'E, 17.80', Placed a nail on the North side. Bearing by compass, distance by tape.

18 Corner destroyed by State Highway 89. At calculated position Set a Brass Tablet with a magnet in concrete, 10" below shoulder on North of State Highway No. 89.



From which bears:
 A 11" Pine N40°56'E, 105.89', scribed: 1/4S19BT.
 A 15" Pine S86°33'E, 86.93', scribed: 1/4S30BT.
 A Caltrans T-bar S89°56'56"E, 206.12'. {N89°38'46"E, 206.10'}.
 A Caltrans T-bar S89°09'51"W, 144.00'. {S89°46'01"W, 143.97'}.
 A Caltrans Monument in Cement N3°01'06"E, 57.98'. {N2°35'17"E, 57.94'}

4 Found corner as noted in 10 R.S. page 110. A Standard U.S.D.A. Monument in a 1 1/2' dia. stone mound.



From which bears:
 A 14" Pine N59°49'W, 155.93'.
 A 16 1/2" Pine S64°52'W, 136.51'.

9 Set a Standard U.S.D.A. Monument 26" in ground 2" above in a 1 1/2' dia. stone mound. No Bearing Trees within reason.



From which bears:
 A 12" Pine N43°15'W, 37.67', scribed: SW1/16S19BT.
 A 12 1/2" Pine S64°00'W, 16.43', scribed: SW1/16S19BT.
 A 1' dia. stone mound with an iron pipe laying on top, bears S89°23'E, 75.73'.
 A C.A.F. tag 10-29-84 states assumed 1/16 corner position.


14 Set a Standard U.S.D.A. Monument 22" in ground 6" above in a 2 1/2' dia. stone mound.


From which bears:
 A 12" Pine N43°15'W, 37.67', scribed: SW1/16S19BT.
 A 12 1/2" Pine S64°00'W, 16.43', scribed: SW1/16S19BT.
 A 1' dia. stone mound with an iron pipe laying on top, bears S89°23'E, 75.73'.
 A C.A.F. tag 10-29-84 states assumed 1/16 corner position.


15 Set a Standard U.S.D.A. Monument 24" in ground 4" above in a 2' dia. stone mound.


From which bears:
 A 14" Pine S64°15'W, 14.41', scribed: CS1/16S19BT.
 A 10" Pine N50°30'W, 21.19', scribed: CS1/16S19BT.

19 Corner position lies in Lake Almanor. Nothing found or set. Calculated position only, 4 R.S. Pg. 38.


5 Found corner as noted in 10 R.S. page 110. A Standard U.S.D.A. monument in a 1' dia. stone mound.


From which bears:
 A Stump bears S33°07'W, 30.42', (Record A 16" Lodgepole S31°W, 30.3').
 A 16" Pine N60°28'W, 320.90'.
 A Forked Poplar, East Fork 7 1/2", West Fork 7", S52°32'W, 378.09'.

10 Found a 1 1/2" dia. Iron Pipe LS 2322, 11" above ground in a 2' dia. by 10" high stone mound.


From which bears:
 A 36" by 6" high Pine N56°15'W, 95.20', with open face with open face with hack marks.
 <A 40" Pine N53°30'W, 94.30'.>
 A 15" Pine S42°00'E, 25.24', scribed: 1/4S19BT.
 A 13 1/2" Pine N37°15'W, 30.12', scribed: 1/4S24BT.

15 General Notes

- The Standard U.S.D.A. Monuments that were set in this survey are 2 1/2" dia. aluminum pipe with a 3 1/2" aluminum cap, 28" in length. The corner identification was stamped on the cap as per the 1973 BLM Manual of Instructions".
- Trees marked as accessories to corner monuments were scribed in accordance to the 1973 "BLM Manual of Instructions".

12 RS 138

March 2003

RECORD OF SURVEY FOR LASSEN NATIONAL FOREST In Section 19

T.28 N. R.7 E., M.D.M. in the unincorporated territory of Plumas County, CA.

Scale 1" = 800'
Sheet 2 of 2