

T27N R13E CORNER No. 1 1/4 S21 FD. A 15 X 14 X 7 INCH MARKED STONE IN A MOUND OF STONE. SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND FRESHENED MOUND. CORNER FALLS ON THE WEST EDGE OF A RIDGE RUNNING SOUTHEAST-NORTHWEST. 1/4 S28 FD. A 30" JEFFREY PINE, S31E, 2.6' -HB REC. A 14" PINE, S31E, 2.6' (2) SCRIBED A 23" PONDEROSA PINE, S30E, 2.9' "1/4 S 28 BT" SCRIBED A 12" DOUGLAS FIR, N7W, 37.7' "1/4 S21 BT"	S 1/4 S26 CORNER No. 7 S28 S27 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A SMALL MOUND OF STONE. CORNER FALLS ON A MODERATE SOUTHWEST SLOPE, 120'± NORTH OF A SHALLOW SWALE. SCRIBED AN 11" DOUGLAS FIR, S44 3/4E, 32.2' "S 1/16 S27 BT" SCRIBED A 13" WHITE FIR, S28W, 38.5' "S 1/16 S28 BT"	CORNER NOTES HB = HEALED BLAZE VS = VISIBLE SCRIBING (1) = GLO 1874 (2) = GLO 1879	T27N R13E CORNER No. 19 1/4 FD. A 16 X 14 X 7 INCH MARKED STONE IN A MOUND OF STONE. SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND FRESHENED MOUND. CORNER FALLS ON UNEVEN GROUND IN MIXED TIMBER. S32 S33 FD. A 36' YELLOW PINE, N56E, 70.0' -HB REC. A 24" PINE, N55E, 68.0' (2) SCRIBED A 12" SUGAR PINE, S11E, 19.3' "1/4 S33 BT" SCRIBED A 10" SUGAR PINE, S88W, 4.8' "1/4 S32 BT"	T27N R13E CORNER No. 26 1/4 S34 S3 CORNER No. 26 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A STEEP, ROCKY WESTERLY SLOPE IN PINE AND MAHOGANY. T26N 2001 FD. A 24" YELLOW PINE, N84W, 13.2' -HB REC. A 12" BLACK PINE, N84W, 13.2' (1) SCRIBED A 10" SUGAR PINE, S29E, 23.3' "1/4 S3 BT" SCRIBED A 25" SUGAR PINE, N42E, 31.2' "1/4 S34 BT"
T27N R13E CORNER No. 2 1/4 S22 FD. A 16 X 10 X 5 INCH MARKED STONE IN A MOUND OF STONE. SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND FRESHENED MOUND. CORNER FALLS ON A FLAT, 50'± WEST OF A CREEK. MEDIUM TO LARGE TIMBER BORDERS MEADOW. MINIMAL BRUSH. 1/4 S27 FD. A 36" JEFFREY PINE, S46 3/4W, 130.7' -HB REC. A 14" PINE, S46 3/4W, 130.7' (2) SCRIBED A 10" YELLOW PINE, N18E, 72.2' "1/4 S22 BT" SCRIBED A 17" YELLOW PINE, S73W, 27.4' "1/4 S27 BT"	SW 1/16 S27 CORNER No. 8 LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A STEEP SOUTH SLOPE AMONG LARGE BOULDERS. SCRIBED AN 8" PONDEROSA PINE, S47W, 5.7' "SW 1/16 S27 BT" SCRIBED AN 8" BLACK OAK, N77 1/4E, 27.3' "SW 1/16 S27 BT"	LS 3966 2001 CORNER No. 13 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD. CORNER FALLS AT THE NORTH EDGE OF THE FINGER OF A MEADOW. SCRIBED A 10" JEFFREY PINE, S80W, 93.6' "W 1/16 S34 BT" SCRIBED A 12" JEFFREY PINE, N26 1/2W, 14.4' "W 1/16 S27 BT"	T27N R13E CORNER No. 20 1/4 S33 S34 CORNER No. 20 FD. A 18 X 14 X 12 INCH MARKED STONE IN A MOUND OF STONE. SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND FRESHENED MOUND. CORNER FALLS ON A MODERATE SOUTH SLOPE IN MIXED PINE AND FIR. LS 3966 2001 FD. A 34" JEFFREY PINE S41 1/2E, 59.1' DEAD AND DOWN -VS REC. A 26" PINE, S50E, 58.1' (2) FD. A 3" PINE STUMP, N23W, 46.0' -VS REC. A 24" PINE, N35W, 44.9' (2) SCRIBED A 15" YELLOW PINE, N73W, 30.8' "1/4 S34 BT" SCRIBED A 10" YELLOW PINE, N40E, 5.3' "1/4 S33 BT"	
T27N R13E CORNER No. 3 1/4 S29 S28 FD. A 18 X 14 X 6 INCH STONE IN A MOUND OF STONE. SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND FRESHENED MOUND. CORNER FALLS ON A WEST SLOPE IN LIGHT MIXED TIMBER. LS 3966 2001 FD. A 25" YELLOW PINE, N60E, 70.6' -HB REC. A 20" PINE, N60E, 70.6' (2) SCRIBED A 7" INCENSE CEDAR, S18E, 11.9' "1/4 S28 BT" SCRIBED A 5" INCENSE CEDAR, S53W, 8.0' "X BT"	S 1/16 S27 CORNER No. 9 C LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD. CORNER FALLS IN A MEADOW, 50'± EAST OF A CREEK. SCRIBED A 21" PONDEROSA PINE, N79E, 121.2' "CS 1/16 S27 BT" SCRIBED A 30" PONDEROSA PINE, N15E, 135.5' "CS 1/16 S27 BT"	LS 3966 2001 CORNER No. 14 1/4 S34 CORNER No. 14 FD. A MOUND OF STONE. SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND FRESHENED MOUND. CORNER FALLS 100'± SOUTHEAST OF THE EDGE OF A MEADOW AND 60'± NORTHWEST OF A ROAD. FD. PINE REMAINS AND STUMP HOLE, N59E, 54.1' REC. A 16" PINE, N59E, 54.1' (2) SCRIBED A 15" JEFFREY PINE, N30W, 15.4' "1/4 S27 BT" SCRIBED A 19" JEFFREY PINE, S66W, 47.2' "1/4 S34 BT"	W 1/16 S33 CORNER No. 21 C—C S27 LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS 40'± SOUTHEAST OF A ROAD RUNNING NORTHEAST TO SOUTHWEST, 12' ABOVE THE ROAD SURFACE IN PINE TIMBER. SCRIBED AN 11" YELLOW PINE, S43E, 15.2' "CW 1/16 S34 BT" SCRIBED A 10" YELLOW PINE, N48E, 14.1' "CW 1/16 S34 BT"	
CORNER No. 4 FD. A 17" YELLOW PINE TREE CORNER WITH A HEALED BLAZE. (8" PINE)1. CORNER FALLS IN A DRAW (DRAINS N40W) AMONG VERY LARGE GRANITE BOULDERS. FD. A 29" YELLOW PINE, N61E, 20.7' -HB REC. A 12" PINE, N70E, 20.5' FD. A 17" FIR SNAG, S73 1/2W, 22.2' -HB REC. A 4" FIR, WEST 23.1' (2) SCRIBED AN 11" YELLOW PINE, S65W, 38.1' "1/4 S28 BT"	T27N R13E CORNER No. 10 1/4 S28 S33 LS 3966 2001 FD. A STONE MARKED "1/4" IN A MOUND OF STONE. SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND FRESHENED MOUND. CORNER FALLS IN A FINGER OF A MEADOW AT A NORTH-SOUTH FENCE. FD. A 55" PONDEROSA PINE, N3E, 91.1' REC. A 30" PINE, N3E, 91.1' (2) SCRIBED A 20" PONDEROSA PINE, S48W, 138.4' "1/4 S33 BT"	LS 3966 2001 CORNER No. 15 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON THE SOUTHWEST EDGE OF AN OLD ROAD. SCRIBED A 7" YELLOW PINE, S82W, 8.5' "X BT" SCRIBED A 13" YELLOW PINE, S31 1/4E, 9.2' "NE 1/16 S33 BT"	T27N R13E CORNER No. 22 1/4 S34 S35 LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A MODERATE WEST SLOPE, 120'± EAST OF A MEADOW. FD. A 6" YELLOW PINE, N33W, 56.5' "N 1/16 S33 BT" SCRIBED A 15" YELLOW PINE, N76E, 31.7' "N 1/16 S34 BT"	
T27N R13E CORNER No. 5 1/4 S27 S26 FD. A MOUND OF STONE. SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND FRESHENED MOUND. CORNER FALLS ON A STEEP NORTHWEST SLOPE, 75'± NORTHEAST OF A SKID ROAD. LS 3966 2001 FD. A ROTTED PINE STUMP WITH A SCRIBED FACE, N53W, 42.2' REC. A 28" PINE, N53W, 42.2' (2) FD. THE ROTTED REMAINS OF A FIR, N2E, 36.3' REC. A 34" FIR, N2E, 36.3' (2) SCRIBED A 6" DOUGLAS FIR, N86W, 8.8' "1/4 S27 BT" SCRIBED A 16" JEFFREY PINE, N52E, 23.3' "1/4 S26 BT"	E 1/16 S33 CORNER No. 11 LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A SMALL MOUND OF STONE. CORNER FALLS IN A MEADOW. SCRIBED A 20" JEFFREY PINE, N56W, 95.3' "E 1/16 S28 BT" SCRIBED A 19" JEFFREY PINE, S38W, 69.3' "E 1/16 S33 BT"	N 1/16 S34 CORNER No. 16 S33 S34 LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A MODERATE WEST SLOPE, 120'± EAST OF A MEADOW. SCRIBED A 6" YELLOW PINE, N33W, 56.5' "N 1/16 S33 BT" SCRIBED A 15" YELLOW PINE, N76E, 31.7' "N 1/16 S34 BT"	T27N R13E CORNER No. 24 1/4 S33 S4 LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A GENTLE SOUTH SLOPE, 30'± EAST OF A SMALL SWALE. FD. A 37" YELLOW PINE, N60W, 10.6' -HB REC. A 19" BLACK PINE, N60W, 10.6' (1) SCRIBED A 37" PONDEROSA PINE, N55W, 10.6' "1/4 S33 BT" SCRIBED AN 8" YELLOW PINE, S20W, 23.3' "1/4 S4 BT"	
SE 1/16 S28 CORNER No. 6 LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD. CORNER FALLS IN THE FILL BANK OF A ROAD, 10' EAST OF A NORTH-SOUTH FENCE. SCRIBED A 17" JEFFREY PINE, S35 1/2W, 9.5' "SE 1/16 S28 BT" SCRIBED A 20" JEFFREY PINE, N52 3/4W, 21.0' "SE 1/16 S28 BT"	T27N R13E CORNER No. 12 S28 S27 S33 S34 LS 3966 2001 FD. A MOUND OF STONE. MARKED STONE PER (2) NOT IN MOUND. SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND FRESHENED MOUND. CORNER FALLS ON A GENTLE WEST SLOPE IN A SHALLOW SWALE, 100'± SOUTH OF A ROAD. FD. A 43" JEFFREY PINE, N49W, 44.0' -HB REC. 28" PINE, N50W, 44.9' (2) FD. A 27" JEFFREY PINE, N49E, 84.6' -HB REC. A 20" PINE, N49E, 84.5' (2) FD. A STUMP, S51W, 78.5' VS REC. A 30" PINE, S51E, 78.5' (2) SCRIBED AN 11" JEFFREY PINE, S49W, 15.3' "T27N R13E S33 BT" SCRIBED A 14" JEFFREY PINE, S35E, 18.7' "T27N R13E S34 BT"	NW 1/16 S34 CORNER No. 17 LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A GENTLE WEST SLOPE IN OPEN, GRASSY MEADOW AMONG MID SIZE PINES. SCRIBED A 22" YELLOW PINE, S24W, 18.0' "NW 1/16 S34 BT" SCRIBED AN 8" YELLOW PINE, S79E, 9.6' "NW 1/16 S34 BT"	T27N R13E CORNER No. 25 S28 S27 LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A MODERATE SOUTH SLOPE IN PINES AND SAGE AND MANZANITA BRUSH. FD. A 17" X 20 X 6 INCH (20 X 20 X 8 INCH)1 MARKED STONE IN A MOUND OF STONE. SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND FRESHENED MOUND. CORNER FALLS ON A MODERATE SOUTH SLOPE IN PINES AND SAGE AND MANZANITA BRUSH. FD. A 30" YELLOW PINE, S33W, 9.9' -HB REC. A 26" PITCH PINE, S33W, 9.9' (1) SCRIBED A 26" PONDEROSA PINE, S35W, 9.9' "T26N R13E S4 BT" SCRIBED A 28" PONDEROSA PINE, N78E, 25.2' "T27N R13E S34 BT" SCRIBED A 9" DOUGLAS FIR, N67E, 16.6' "T27N R13E S34 BT" SCRIBED A 23" PONDEROSA PINE, N12E, 29.0' "T27N R13E S34 BT" SCRIBED A 13" PONDEROSA PINE, N38W, 51.8' "T27N R13E S33 BT"	
SE 1/16 S28 CORNER No. 6 LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD. CORNER FALLS IN THE FILL BANK OF A ROAD, 10' EAST OF A NORTH-SOUTH FENCE. SCRIBED A 17" JEFFREY PINE, S35 1/2W, 9.5' "SE 1/16 S28 BT" SCRIBED A 20" JEFFREY PINE, N52 3/4W, 21.0' "SE 1/16 S28 BT"	C C LS 3966 2001 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A MODERATE WEST SLOPE IN MIXED FIR AND PINE. SCRIBED A 10" YELLOW PINE, S51E, 24.8' "CN 1/16 S34 BT" SCRIBED A 9" DOUGLAS FIR, N67E, 16.6' "CN 1/16 S34 BT"		RECORD OF SURVEY FOR USDA FOREST SERVICE PLUMAS NATIONAL FOREST "STONY RIDGE" IN SECTIONS 27, 28, 33 AND 34, IN T 27 N, R 13 E, M.D.M. IN THE UNINCORPORATED AREA OF PLUMAS COUNTY, STATE OF CALIFORNIA	
			DEL TERRA INC. SURVEYING 1168 INDUSTRIAL ST. REDDING, CA 96002 PHONE (530) 241-8050	
			DATE: OCTOBER, 2001 SHEET 2 OF 2	