

T22N R8E 1/4 S27 S26 LS 3621 1980	CORNER No. 1 FD. A STD USFS MONUMENT IN A MOUND OF STONE. CORNER FALLS ON A MODERATE SOUTHWEST SLOPE IN TIMBER AND BRUSH, 50'± NORTHEAST OF A ROAD. FD. A 19" SUGAR PINE, N53°W, 8.1' -HB REC. A 10" PINE, N53°W, 8.1' (1) FD. A 24" SUGAR PINE, N28°E, 9.5' -HB REC. A 14" PINE, N28°E, 9.5' (1)	E 1/16 C-C S35 LS 4753 2003	CORNER No. 8 FD. A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE PER (1). CORNER FALLS ON A MODERATE WEST SLOPE IN TIMBER AND BRUSH. FD. A 16" WHITE FIR, N22°E, 11.0' -VS REC. A 16" WHITE FIR, N22°E, 11.0' (1) FD. A 10" WHITE FIR, S42°E, 19.8' -VS REC. A 10" WHITE FIR, S42°E, 19.8' (1)
T22N R8E 1/4 S27 S26 S34 S35 LS 3621 1980	CORNER No. 2 FD. A STD. USFS ALUM. CAP IN A MOUND OF STONE. CORNER FALLS ON AN EAST SLOPE, 25'± EAST OF A ROAD IN THICK WHITE FIR AND SCATTERED PINE. FD. A 23" WHITE FIR, N7°W, 7.1' -HB REC. AN 18" FIR, N2°W, 7.1' (1) FD. A 52" SUGAR PINE, S47°E, 23.8' -VS IN OPEN BLAZE REC. A 62" PINE, S50°E, 23.8' (1) FD. A 13" WHITE FIR, S85°W, 50.0' -HB REC. A 10" FIR, S85°W, 50.0' (1) FD. A 19" WHITE FIR, N65°E, 74.1' -HB REC. A 16" FIR, N65°E, 74.1' (1)	T22N R8E 1/4 S35 S36 LS 3621 1980	CORNER No. 9 FD. A STD. USFS ALUM. CAP IN A MOUND OF STONE. CORNER FALLS IN A FLAT AREA NORTHWEST OF AN OPEN LAVA REEF. FD. A 19" FIR SNAG, N55°E, 29.4' -VS REC. A 15" FIR, S55°E, 29.4' (1) FD. A 12" RED FIR, N32°W, 19.5' -HB REC. A 7" FIR, N32°W, 19.5' (1)
T22N R8E 1/4 S27 S26 S34 S35 LS 3621 1980	CORNER No. 3 FD. A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE PER (1). CORNER FALLS ON A GENTLE WEST SLOPE. FD. A 15" WHITE FIR, N81°E, 4.8' -VS REC. A 15" WHITE FIR, N81°E, 4.8' (1) FD. A 10" RED FIR, S9°E, 28.8' -VS REC. A 10" RED FIR, S9°E, 28.8' (1)	S 1/16 S34 S35 LS 4753 2003	CORNER No. 10 (AMENDED) RESET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A SMALL MOUND OF STONE. CORNER FALLS IN THE CENTER OF AN OLD SKID ROAD AMID THICK MANZANITA. A 9" PONDEROSA PINE, N7°W, 61.0' NEW TIE TO BEARING TREE FROM (1) AN 8" WHITE FIR, S50°E, 84.9' NEW TIE TO BEARING TREE FROM (1)
T22N R8E 1/4 S27 S26 S34 S35 LS 3621 1980	CORNER No. 4 FD. A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE PER (1). CORNER FALLS ON A GENTLE WEST SLOPE. FD. A 15" WHITE FIR, N81°E, 4.8' -VS REC. A 15" WHITE FIR, N81°E, 4.8' (1) FD. A 10" RED FIR, S9°E, 28.8' -VS REC. A 10" RED FIR, S9°E, 28.8' (1)	SW 1/16 S35 LS 4753 2003	CORNER No. 11 (AMENDED) RESET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A MODERATE SOUTHWEST SLOPE IN AN OLD SKID TRAIL AT THE EDGE OF A CLEAR CUT. A 7" WHITE FIR, N89°E, 20.0' NEW TIE TO BEARING TREE FROM (1) A 7" INCENSE CEDAR, N19°W, 36.0' NEW TIE TO BEARING TREE FROM (1)
T22N R8E 1/4 S27 S26 S34 S35 LS 3621 1980	CORNER No. 5 FD. A STD. USFS ALUM. CAP IN A MOUND OF STONE. CORNER FALLS ON A GENTLE WEST SLOPE IN HEAVY REGROWTH. FD. A DEAD AND DOWN RED FIR, N17°E, 27.2' -VS REC. A 12" PINE, N17°E, 27.2' (1) FD. AN 8" RED FIR SNAG, N48°W, 30.7' -HB REC. A 7" PINE, N48°W, 30.7' (1)	T22N R8E 1/4 S35 T21N 2003	CORNER No. 17 FD. A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A STEEP WEST SLOPE IN BRUSH. FD. A 27" SUGAR PINE, S3°E, 70.6' -VS IN A CHOPPED OUT FACE REC. A 7" SUGAR PINE, S3°E, 107 LKS (GLO) FD. AN 11" INCENSE CEDAR, N72°E, 25.2' -VS REC. AN 11" INCENSE CEDAR, N72°E, 25.2' (1)
T22N R8E 1/4 S27 S26 S34 S35 LS 3621 1980	CORNER No. 6 FD. A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A SMALL MOUND OF STONE PER (1). CORNER FALLS ON A MODERATE SOUTHWEST SLOPE IN TIMBER AND BRUSH. FD. A 10" WHITE FIR, S36 1/4°W, 46.1' -VS REC. A 10" WHITE FIR, S36 1/4°W, 46.1' (1) FD. AN 8" WHITE FIR, N51°W, 7.8' -VS REC. AN 8" WHITE FIR, N51°W, 7.8' (1)	N 1/16 S3 S2 LS 4753 2003	CORNER No. 12 FD. A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A SMALL MOUND OF STONE PER (1). CORNER FALLS ON A GENTLE SOUTHWEST SLOPE IN TIMBER AT THE EDGE OF A LOGGED AREA. FD. A 7" WHITE FIR, S46°E, 12.5' -VS REC. A 7" WHITE FIR, S46°E, 12.5' (1) FD. A 9" WHITE FIR, N83°W, 32.7' -VS REC. A 9" WHITE FIR, N83°W, 32.7' (1)
T22N R8E 1/4 S27 S26 S34 S35 LS 3621 2004	CORNER No. 7 FD. A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A SMALL MOUND OF STONE PER (1). CORNER FALLS ON A MODERATE SOUTHEAST SLOPE IN SCATTERED TIMBER AND HEAVY BRUSH. FD. A 12" WHITE FIR, N81 1/2°E, 28.1' -VS REC. A 12" WHITE FIR, N81 1/2°E, 28.1' (1) FD. AN 11" WHITE FIR, N30°E, 38.5' -VS REC. AN 11" WHITE FIR, N30°E, 38.5' (1)	SE 1/16 S35 LS 4753 2004	CORNER No. 13 SET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A NORTH SLOPE BETWEEN A MAIN ROAD AND A SKID ROAD IN PINE AND LIVE OAK. SCRIBED A 29" PONDEROSA, S85°W, 13.7' "SE 1/16 S36 BT"
T22N R8E 1/4 S27 S26 S34 S35 LS 3621 1980	CORNER No. 8 FD. A STD. USFS ALUM. CAP IN A MOUND OF STONE. CORNER FALLS ON A MODERATE WEST SLOPE IN HEAVY TIMBER AND BRUSH. FD. A 20" WHITE FIR, S66°W, 19.2' -HB REC. A 9" FIR, S67°W, 19.0' (1) FD. A 19" WHITE FIR, S33°E, 7.7' -HB REC. AN 8" FIR, S30°E, 7.5' (1)	T22N R8E 1/4 S34 T21N 1980	CORNER No. 15 FD. A STD. USFS ALUM. CAP IN A MOUND OF STONE. CORNER FALLS ON A MODERATE WEST SLOPE IN HEAVY TIMBER AND BRUSH. FD. A 20" WHITE FIR, S66°W, 19.2' -HB REC. A 9" FIR, S67°W, 19.0' (1) FD. A 19" WHITE FIR, S33°E, 7.7' -HB REC. AN 8" FIR, S30°E, 7.5' (1)
CORNER NOTES			
<p>HB = HEALED BLAZE VS = VISIBLE SCRIBING STD USFS MONUMENT = A 3-1/4" ALUM. CAP ON A 2-1/4" ALUM. PIPE (1) = REC. PER 13 R/S 6 (2) = REC. PER MS 5037 (3) = REC PER 5 R/S 143 (4) = RECORD PER UNRECORDED SURVEY BY CLIFF McDIVITT SURVEYING IN JUNE, 2000</p>			
T22N R8E 1/4 S3 S2 LS 4753 2003	CORNER No. 24 (AMENDED) RESET A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A MODERATELY STEEP EAST SLOPE IN THICK TIMBER. A 9" WHITE FIR, N60°W, 18.2' NEW TIE TO BEARING TREE FROM (1) SCRIBED A 10" WHITE FIR, N66°E, 6.5' "1/4 S3 BT" TREE TO SOUTHEAST FROM (1) IS DEAD	T22N R8E 1/4 S36 S3 T21N 2004	CORNER No. 31 NO ORIGINAL EVIDENCE FOUND. SET 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A STEEP NORTHEAST SLOPE IN ROCKY GROUND IN BRUSH AND SCATTERED TIMBER. SCRIBED A 7" DOUGLAS FIR, S36°E, 75.3' "T21N R8E S1 BT" SCRIBED A 14" INCENSE CEDAR, N74°W, 22.7' "T21N R8E S35 BT"
T22N R8E 1/4 S36 S3 T21N 2004	CORNER No. 33 NO ORIGINAL EVIDENCE FOUND. SET 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A STEEP WEST SLOPE IN ROCKY GROUND AMONG BURNT TREES AND CHARCOAL SNAGS. SCRIBED AN 11" WHITE FIR, S36°W, 35.6' "1/4 S1 BT" SCRIBED A 12" WHITE FIR, N72°E, 17.6' "1/4 S36 BT"	T22N R8E 1/4 S36 S3 T21N 2004	CORNER No. 34 NO ORIGINAL EVIDENCE FOUND. SET 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A MODERATE WEST SLOPE IN BURN AREA AMONG WHITETHORN AND MANZANITA. NO TREES AVAILABLE SET A STEEL POST N32°W, 3.8'
PROPERTY CORNER LS5309			
<p>CORNER No. 35 FD. A PLASTIC CAP ON A 5/8" REBAR IN A MOUND OF STONE PER (4). CORNER FALLS ON A WEST SLOPE IN SCATTERED FIR AND CEDAR.</p> <p>FD. A 36" FIR SNAG, S6 1/2°E, 22.3' REC. A 30" FIR SNAG, S15 1/4°E, 22.3' (McD 2000) FD. A 36" DOUGLAS FIR, N85°W, 23.8' REC. A 32" FIR, N84 1/2°W, 23.8' (McD 2000)</p>			
RECORD OF SURVEY			
<p>FOR USDA FOREST SERVICE PLUMAS NATIONAL FOREST "WATDOG"</p> <p>AMENDING CORNERS 10, 11, 21, 23, 24, 25 AND 26 AS SHOWN ON 13 R/S 6 & 7 RESULTING FROM A MEASUREMENT ERROR IN THE TIE TO CORNER 16</p> <p>IN SECTIONS 15, 26, 35 AND 36, OF T 22 N, R 8 E, IN SECTION 31 OF T 22 N, R 9 E, IN SECTIONS 1, 2 AND 3, OF T 21 N, R 8 E, AND IN SECTION 6, OF T 21 N, R 9 E, MDM IN THE UNINCORPORATED AREA OF PLUMAS COUNTY, STATE OF CALIFORNIA</p>			
<p>DEL TERRA INC. SURVEYING 1168 INDUSTRIAL ST. REDDING, CA 96002 PHONE (530) 241-8050</p>			
<p>DATE: SEPTEMBER, 2004 SHEET 3 OF 4</p>			