

<p>T2IN R8E R9E S1 S6 S12 S7 LS 5632 2002</p> <p>CORNER No. 36 FD. A 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE PER 12 R/S 89. CORNER FALLS ON A STEEP WEST SLOPE IN TIMBER.</p>	<p>A3 AE3 MS 5037 LS 4753 2004</p> <p>CORNER No. 45 FD. A MOUND OF STONE. SET 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND REBUILT MOUND. CORNER FALLS ON A WEST SLOPE, 300'± NORTHEAST OF A ROAD IN WHITE FIRS.</p> <p>FD. A 21" SUGAR PINE, S42°E, 56.4' -HB REC. A 4" PITCH PINE, S41°30'E, 56.45' ()2 FD. A 20" SUGAR PINE, S39°E, 56.4' -HB REC. A 4" PITCH PINE, S39°10'E 56.40' ()2 SCRIBED A 14" SUGAR PINE, S39°W, 8.6' "AE3 MS5037 BT"</p>	<p>CORNER NOTES</p> <p>HB = HEALED BLAZE VS = VISIBLE SCRIBING STD USFS MONUMENT = A 3-1/4" ALUM. CAP ON A 2-1/4" ALUM. PIPE (1) = REC. PER 13 R/S 6 (2) = REC. PER MS 5037 (3) = REC PER 5 R/S 143 (4) = RECORD PER UNRECORDED SURVEY BY CLIFF McDIVITT SURVEYING IN JUNE, 2000</p>		
<p>T2IN R8E 1/4 R9E S1 S6 LS 5632 2002</p> <p>CORNER No. 37 SET 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A MODERATE SOUTHWEST SLOPE, 125'± WEST OF A CREEK.</p> <p>SCRIBED A 7" WHITE FIR, S61°W, 28.3' "T2IN R8E S1 BT" SCRIBED A 9" WHITE FIR, S58°E, 11.7' "T2IN R9E S6 BT"</p>				
<p>RM 9.0' TO COR LS 4753 2004</p> <p>CORNER No. 41 FD. A 51" DOUGLAS FIR (38" FIR PER GLO) WITH A HEALED BLAZE ON THE NORTHEAST SIDE, A VISIBLE BARK BLAZE ON THE SOUTHWEST AND SOUTHEAST SIDES BUT NO VISIBLE SCRIBING, TAGGED BY EDGERTON IN 1976 WHEN IT WAS A 50" TREE.</p> <p>SET 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD IN A MOUND OF STONE FOR REFERENCE MONUMENT, FROM WHICH THE TREE CORNER BEARS SOUTH 49° WEST, 9.0'.</p> <p>SCRIBED A 9" DOUGLAS FIR, S39°W, 26.7' "T22N R8E S16 BT"</p>				
<p>A1 MS 5037 4753 2004 LS</p> <p>CORNER No. 42 FD. A MOUND OF STONE. SET 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND REBUILT MOUND. CORNER FALLS ON A SOUTHWEST SLOPE IN SCATTERED BRUSH AND SMALL TIMBER WITH SCATTERED OLD WHITE FIR.</p> <p>FD. A 42" SUGAR PINE, N62°W, 23.1' -HB REC. A 10" SUGAR PINE, N61°34'W, 23.13' ()2 FD. A 44" SUGAR PINE, N78°E, 30.8' -HB REC. A 30" SUGAR PINE, N78°10'E, 30.82' ()2</p>				
<p>A2 MS 5037 2004 LS 4753</p> <p>CORNER No. 43 FD. A MOUND OF STONE. SET 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND REBUILT MOUND. CORNER FALLS ON A ROUNDED RIDGE IN WHITE FIR AND SUGAR PINE.</p> <p>FD. A 17" SNAG, SOUTH, 13.7' -HB REC. A 14" WHITE FIR, S0°09'E, 13.68' ()2 FD. AN 18" WHITE FIR, S36°W, 15.2' -HB REC. A 10" WHITE FIR, S36°01'W, 15.25' ()2 SCRIBED A 13" SUGAR PINE, N74°W, 24.8' "A1 MS5037 BT"</p>				
<p>T22N R8E 1/4 S16 S15 LS 4753 2004</p> <p>CORNER No. 44 FD. A MOUND OF STONE. SET 3 1/4" USFS ALUM. CAP ON A 5/8" ALUM. ROD AND REBUILT MOUND. CORNER FALLS ON A NORTH SLOPE, 50'± SOUTH OF A ROAD.</p> <p>FD. A 42" WHITE FIR, N78°E, 9.9' -HB REC. A 22" FIR, N78°E, 15 LKS (GLO) SCRIBED A 6" WHITE FIR, N16°W, 28.8' "1/4 S16 BT"</p>				<p>RECORD OF SURVEY</p> <p>FOR USDA FOREST SERVICE PLUMAS NATIONAL FOREST "WATDOG"</p> <p>AMENDING CORNERS 10, 11, 21, 23, 24, 25 AND 26 AS SHOWN ON 13 R/S 6 & 7 RESULTING FROM A MEASUREMENT ERROR IN THE TIE TO CORNER 16</p> <p>IN SECTIONS 15, 26, 35 AND 36, OF T 22 N, R 8 E, IN SECTION 31 OF T 22 N, R 9 E, IN SECTIONS 1, 2 AND 3, OF T 21 N, R 8 E, AND IN SECTION 6, OF T 21 N, R 9 E, MDM IN THE UNINCORPORATED AREA OF PLUMAS COUNTY, STATE OF CALIFORNIA</p> <p>DEL TERRA INC. SURVEYING 1168 INDUSTRIAL ST. REDDING, CA 96002 PHONE (530) 241-8050</p> <p>DATE: SEPTEMBER, 2004 SHEET 4 OF 4</p>

