



BASIS OF BEARINGS
 *MEASURED BEARINGS AND DISTANCES ARE GRID BASED ON THE CALIFORNIA COORDINATE SYSTEM OF 1983 (CCS83), ZONE 1.

$\theta = 0^{\circ}35'35''$ AT HPGN D CA 02 ES, MULTIPLY GRID DISTANCES BY 1.000276 TO GET GROUND DISTANCES.

CONTROL WAS ESTABLISHED WITH G.P.S., TOPCON HIPER, DUAL FREQUENCY. CONTROL WAS ESTABLISHED USING THE FOLLOWING STATIONS:

HPGN D CA 02 ES (DF4390) EPOCH: MARCH, 2003
 LATITUDE: $40^{\circ}10'42.49563''$ N 1949611.19 N
 LONGITUDE: $121^{\circ}05'35.39575''$ W 6815050.79 E

HPGN CA 02 27 (KS2012) EPOCH: AUGUST 1996
 LATITUDE: $39^{\circ}51'14.41395''$ N 1832871.05 N
 LONGITUDE: $120^{\circ}41'06.40820''$ W 6930833.50 E

LATITUDES AND LONGITUDES AS PUBLISHED BY NATIONAL GEODETIC SURVEYS (NGS) IN JUNE 2001.

GENERAL NOTES

A STANDARD UNITED STATES FOREST SERVICE (USFS) DRIVE-IN MONUMENT IS A 5/8" DIAMETER ALUMINUM ROD WITH A 3-1/4" ALUMINUM CAP EDGE-MARKED WITH THE USFS LOGO.

A STANDARD BUREAU OF LAND MANAGEMENT (BLM) MONUMENT IS A 2-1/2" DIAMETER STEEL PIPE, 28" LONG WITH A 3-1/2" BRASS CAP EDGE-MARKED WITH THE BLM LOGO.

SURVEY HISTORY

(R1) GENERAL LAND OFFICE NOTES (WM. MINTO 1880)

STATE PLANE COORDINATES CALIFORNIA - ZONE 1 1983		
$\theta = 0^{\circ}51'35''$ AT HPGN D CA 02 ES, MULTIPLY GRID DISTANCE BY 1.00011651 TO GET GROUND DISTANCES.		
CORNER #	NORTHING	EASTING
13	1847774.291	6936384.824
14	1847859.924	6939095.902
15	1847945.560	6941806.978
16	1850481.702	6937638.024
17	1853267.009	6941705.295

MULTIPLY MEASURED DISTANCES BY 1.0001651 TO GET GROUND DISTANCES

- LEGEND**
- PRORATED CORNER POINT (NOTHING SET) SEARCHED FOR ORIG. CORNER NOT FOUND
 - FOUND BLM CORNER
 - CORNER NOTE
 - SET STANDARD U.S. FOREST SERVICE DRIVE-IN MONUMENT (BEARING TREES AS NOTED)
 - PROPERTY BOUNDARY MARKED AND POSTED

RECORD OF SURVEY
 SECTION 32, T24N R12E, MDM,
 PLUMAS COUNTY, CALIFORNIA
 FOR
 U.S.D.A. PLUMAS NATIONAL FOREST
 P.O. BOX 11500, QUINCY, CA.
 DRAWN BY: B. SNOW DATE: OCTOBER, 2006