

<p>LS 2670 CORNER No. 29 C N 1/16 S29 FD. A 1/2" IRON PIPE WITH A 1 1/2" ALUM CAP IN A MOUND OF STONE PER 2 RS 83 WHICH BEARS S 36° 39' 11" E, 1.16' FROM TRUE POSITION FOR N 1/16 CORNER. CORNER FALLS ON A MODERATE SOUTHEAST SLOPE IN TIMBER. FD. A 29" SUGAR PINE, N64°W, 25.4' -HB REC. A 18" SUGAR PINE, N65°W, 25.1' (2 RS 83) FD. A 25" SUGAR PINE, S30°W, 17.6' -HB REC. A 12" SUGAR PINE, S31°W, 17.5' (2 RS 83)</p>	<p>LS 2670 CORNER No. 37 C 1/16 S30 FD. A 1/2" IRON PIPE WITH A 1 1/2" ALUM CAP IN A MOUND OF STONE PER 2 RS 83 WHICH BEARS N 73° 50' 56" W, 0.86' FROM TRUE POSITION FOR CS 1/16 CORNER SECTION 30. CORNER FALLS ON A STEEP WEST SLOPE. FD. A 25" INCENSE CEDAR, N42°W, 10.8' -HB REC. A 16" INCENSE CEDAR, N44°W, 9.6' (2 RS 83) FD. A 22" DOUGLAS FIR, S7°W, 10.3' -HB REC. A 12" DOUGLAS FIR, S4°W, 10.4' (2 RS 83)</p>	<p>CORNER NOTES HB = HEALED BLAZE VS = VISIBLE SCRIBING NVM = NO VISIBLE MARKS TRUE POSITION = POSITION AS DETERMINED PER 1973 BLM MANUAL BCIP = BRASS CAPPED IRON PIPE DRIVE IN MONUMENT = 3 1/4" ALUM CAP ON AN ALUM ROD</p>	<p>W 1/16 C S31 CORNER No. 49 LS 4753 2006 SET A 3 1/4" ALUM. CAP ON A 3/4" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS AT THE SOUTH EDGE OF SLATE CREEK, 30'± SOUTH OF THREAD. SCRIBED A 9" DOUGLAS FIR, S36°E, 66.5' "CW 1/16 S31 BT" SCRIBED A 9" SUGAR PINE, N14°W, 69.2' "CW 1/16 S31 BT"</p>	<p>SC T21N R8E CORNER No. 57 1/4 S36 FD. A USFS DRIVE IN MONUMENT - NO MOUND OF STONE PER 9 RS 84. CORNER FALLS ON A MODERATE SOUTHEAST SLOPE IN TIMBER AND BRUSH. LS 3966 1992 FD. A PINE SNAG, N25°E, 9.9' -NVM REC. A 55" SUGAR PINE, N25°E, 9.9' (GLO) FD. A 9" INCENSE CEDAR, N4°W, 24.5' -VS REC. A 9" CEDAR, N4°W, 24.5' (9 RS 84) FD. AN 11" INCENSE CEDAR, N59°E, 24.8' -VS REC. A 13" CEDAR, N69°E, 24.8' (9 RS 84)</p>
<p>CORNER No. 30 RECORD POSITION PER 12 RS 37 - NOT TIED THIS SURVEY.</p>	<p>LS 2780 CORNER No. 39 SW 1/16 S29 FD. A 1/2" IRON PIPE WITH A 1 1/2" ALUM CAP IN A MOUND OF STONE PER 2 RS 83 WHICH BEARS S 25° 08' 04" W, 0.66' FROM TRUE POSITION FOR SW 1/16 CORNER SECTION 29. CORNER FALLS ON A STEEP, ROCKY SOUTHWEST SLOPE. FD. A 46" INCENSE CEDAR, N4°E, 33.5' -HB REC. A 36" INCENSE CEDAR, N4°E, 33.5' (2 RS 83) FD. A 21" WHITE FIR, N70 1/2°W, 36.3' -HB REC. A 14" WHITE FIR, N70 1/2°W, 36.3' (2 RS 83)</p>	<p>CORNER No. 45 RECORD POSITION PER 12 RS 37 - NOT TIED THIS SURVEY.</p>	<p>T21N R9E CORNER No. 50 1/4 S31 S32 FD. A 12 X 10 X 8 INCH STONE MARKED "1/4" IN A SCATTERED MOUND OF STONE. SET A 3 1/4" ALUM. CAP ON A 3/4" ALUM. ROD AND REBUILT MOUND WITH STONE ALONGSIDE. CORNER FALLS ON A MODERATE NORTHWEST SLOPE IN TIMBER, 100'± EAST OF A CLEAR CUT.</p>	<p>NW 1/16 S1 CORNER No. 58 LS 3966 1992 FD. A USFS DRIVE IN MONUMENT IN A MOUND OF STONE PER 9 RS 84 WHICH BEARS S 82° 42' 39" W, 0.68' FROM TRUE CORNER. CORNER FALLS EAST OF RIDGE TOP IN TIMBER, 150'± NORTH OF A ROAD. FD. AN 11" INCENSE CEDAR, N81°W, 31.1' -VS REC. A 10" CEDAR, N81°W, 31.1' (9 RS 84) FD. A 14" INCENSE CEDAR, S44°E, 18.6' -VS REC. A 13" CEDAR, S44°E, 18.6' (9 RS 84)</p>
<p>LS 2780 CORNER No. 31 C 1/4 S30 1959 FD. A 1/2" IRON PIPE WITH A 1 1/2" BRASS CAP IN A MOUND OF STONE PER 2 RS 83 WHICH BEARS N 49° 48' 02" E, 1.91' FROM TRUE POSITION FOR CENTER 1/4 CORNER. CORNER FALLS ON A STEEP SOUTHWEST SLOPE IN TIMBER. FD. A 26" WHITE FIR, S36 3/4°W, 16.0' -HB REC. A 20" DOUGLAS FIR, S31°W, 16.4' (2 RS 83) FD. A 16" INCENSE CEDAR, S44 3/4°E, 16.4' -HB REC. A 14" INCENSE CEDAR, S45°E, 18.2' (2 RS 83)</p>	<p>LS 2780 CORNER No. 39 SW 1/16 S29 FD. A 1/2" IRON PIPE WITH A 1 1/2" ALUM CAP IN A MOUND OF STONE PER 2 RS 83 WHICH BEARS S 25° 08' 04" W, 0.66' FROM TRUE POSITION FOR SW 1/16 CORNER SECTION 29. CORNER FALLS ON A STEEP, ROCKY SOUTHWEST SLOPE. FD. A 46" INCENSE CEDAR, N4°E, 33.5' -HB REC. A 36" INCENSE CEDAR, N4°E, 33.5' (2 RS 83) FD. A 21" WHITE FIR, N70 1/2°W, 36.3' -HB REC. A 14" WHITE FIR, N70 1/2°W, 36.3' (2 RS 83)</p>	<p>CORNER No. 45 RECORD POSITION PER 12 RS 37 - NOT TIED THIS SURVEY.</p>	<p>T21N R8E CORNER No. 51 1/4 S1 T20N R8E FD. A 13" WHITE FIR, N65 1/4°W, 30.8' "W 1/16 S29 BT" REC. A 13" DOUGLAS FIR, S69°E, 32.5' "W 1/16 S32 BT" REC. BT'S NOT FD</p>	<p>C 1/4 S1 CORNER No. 59 LS 4753 2007 SET A 3 1/4" ALUM. CAP ON A 3/4" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A STEEP SOUTHWEST SLOPE IN TIMBER, 100'± NORTH OF ONION CREEK. FD. A 10" DOUGLAS FIR, S18°W, 7.1' -HB REC. A 6" WHITE FIR, S18°W, 7.1' (9 R/S 84) FD. A 10" DOUGLAS FIR, S63°E, 30.7' -HB REC. AN 8" WHITE FIR, S63°E, 30.7' (9 R/S 84)</p>
<p>CORNER No. 33 RECORD POSITION PER 12 RS 37 - NOT TIED THIS SURVEY.</p>	<p>LS 2780 CORNER No. 40 S 1/16 S29 C FD. AN UNMARKED 1" IRON PIPE (PROBABLY SET BY LARSON PER 2 RS 83) WHICH BEARS N 51° 42' W, 2.53' FROM TRUE POSITION FOR CS 1/16 CORNER SECTION 29. SET A 3 1/4" ALUM. CAP ON A 3/4" ALUM. ROD IN A MOUND OF STONE. CORNER FALLS ON A GENTLE NORTHEAST SLOPE AT THE SOUTH EDGE OF A CLEAR CUT.</p>	<p>LS 2670 CORNER No. 46 1/4 S29 S32 1959 FD. A 13" INCENSE CEDAR, N4 3/4°E, 14.2' -HB REC. AN 8" INCENSE CEDAR, N10°E, 14.8' (2 RS 83) FD. A WHITE FIR SNAG, S54°W, 24.2' -NVM REC. A 12" WHITE FIR, S54 1/2°W, 24.1' (2 RS 83)</p>	<p>T21N R8E CORNER No. 52 S36 S2 S1 FD. A 1/2" IRON PIPE WITH A 1 1/2" ALUM CAP IN A MOUND OF STONE PER 2 RS 83 WHICH BEARS N 10° 41' 51" E, 20.83' FROM TRUE POSITION FOR S 1/4 CORNER SECTION 29. MONUMENT AND ACCESSORIES NOT ACCEPTED THIS SURVEY. - NOTHING SET THIS SURVEY -</p>	<p>NE 1/16 S1 CORNER No. 60 LS 4753 2007 SET A 3 1/4" ALUM. CAP ON A 3/4" ALUM. ROD (NO MOUND). CORNER FALLS ON A GENTLE SOUTHWEST SLOPE IN TIMBER AND BLACK OAK. FD. A 12" INCENSE CEDAR, S27°W, 29.0' -HB REC. A 12" CEDAR, S27°W, 29.0' (9 R/S 84) FD. AN 8" INCENSE CEDAR, S73°E, 67.2' -HB REC. AN 5" CEDAR, S73°E, 67.2' (9 R/S 84)</p>
<p>LS 2670 CORNER No. 34 E 1/16 S29 1959 FD. A 1/2" IRON PIPE WITH A 2" BRASS CAP IN A MOUND OF STONE PER 2 RS 83. CORNER FALLS ON A MODERATE NORTH SLOPE IN TIMBER. FD. A 36" INCENSE CEDAR, N12°W, 10.6' -HB REC. A 24" INCENSE CEDAR, N12°W, 10.5' (2 RS 83) SCRIBED A 16" SUGAR PINE, S86°E, 20.3' "CE 1/16 S29 BT"</p>	<p>LS 2780 CORNER No. 41 SE 1/16 S29 1959 FD. A 1/2" IRON PIPE WITH A 1 1/2" ALUM CAP IN A MOUND OF STONE PER 2 RS 83. CORNER FALLS ON A MODERATE SOUTHEAST SLOPE IN TIMBER, 60'± NORTHWEST OF A ROAD.</p>	<p>LS 2670 CORNER No. 47 T21N R9E S29 S28 S32 S33 1959 FD. A 1/2" IRON PIPE WITH A 1 1/2" ALUM CAP IN A MOUND OF STONE PER 2 RS 83. CORNER FALLS ON A STEEP NORTHEAST SLOPE, 200'± SOUTH OF SLATE CREEK.</p>	<p>FD. A 21" WHITE FIR, N25 1/2°E, 13.0' -HB REC. AN 18" WHITE FIR, N25 1/2°E, 13.0' (2 RS 83) FD. A 22" WHITE FIR, S55°E, 27.5' -HB REC. A 16" WHITE FIR, S55°E, 27.5' (2 RS 83)</p>	<p>E 1/16 S1 CORNER No. 53 LS 4753 2007 SET A 3 1/4" ALUM. CAP ON A 3/4" ALUM. ROD IN A SMALL MOUND OF STONE. CORNER FALLS ON A STEEP NORTHEAST SLOPE IN TIMBER AND BRUSH. SCRIBED A 12" DOUGLAS FIR, S72°W, 27.6' "E 1/16 S1 BT" SCRIBED A 13" DOUGLAS FIR, S4°E, 14.6' "E 1/16 S1 BT"</p>
<p>LS 2670 CORNER No. 35 S 1/4 S29 1959 FD. A 1/2" IRON PIPE WITH A 2" BRASS CAP IN A MOUND OF STONE PER 2 RS 83. CORNER FALLS ON A STEEP NORTHWEST SLOPE IN TIMBER. FD. A 20" DOUGLAS FIR, S29°E, 11.2' -HB REC. A 10" WHITE FIR, S29°E, 11.1' (2 RS 83) FD. A 15" DOUGLAS FIR, S60°W, 11.6' -HB REC. AN 8" DOUGLAS FIR, S60°W, 11.3' (2 RS 83)</p>	<p>LS 2670 CORNER No. 42 T21N R9E S25 S30 S36 S31 1959 FD. A 1 1/2" BRASS CAP ON A 1/2" METAL CONDUIT PER 12 RS 37. ACCESSORIES NOT TIED</p>	<p>LS 2670 CORNER No. 43 S 1/16 S30 S31 1959 FD. A 1/2" IRON PIPE WITH A 1 1/2" ALUM CAP (NO REC.) WHICH BEARS N 88° 18' 05" W, 0.60' FROM TRUE POSITION FOR W 1/16 CORNER 30/31. CORNER FALLS ON A GENTLE WEST SLOPE. FD. A 9" WHITE FIR, S13°E, 7.8' -HB NO REC. FD. 24" PONDEROSA PINE, N50°W, 14.1' -HB NO REC.</p>	<p>T21N R8E CORNER No. 48 1/4 S36 S31 LS 4753 2006 FD. A 3/4" IRON PIPE (NO REC.) IN A MOUND OF STONE. ACCEPTED FOR 1/4 CORNER 36/31. SET A 3 1/4" ALUM. CAP ON A 3/4" ALUM. ROD ALONGSIDE AND REBUILT MOUND. CORNER FALLS ON A STEEP EAST SLOPE IN TIMBER, 100'± WEST OF A ROAD. FD. A PINE STUMP, N79°W, 10.6' MARKED "POSSIBLE BT" BY JOE EGDERTON OF THE USFS REC. 7" SUGAR PINE, N79°W, 16 LKS (GLO 1870) SCRIBED. A 13" WHITE FIR, S52 1/2°E, 8.0' "1/4 S36 BT" SCRIBED A 24" DOUGLAS FIR, S61 1/4°W, 14.0' "1/4 S31 BT"</p>	<p>SC 1/4 S31 CORNER No. 55 1939 FD. A GLO BCIP IN A MOUND OF STONE. CORNER FALLS ON A STEEP WEST SLOPE IN TIMBER. FD. A 16" DOUGLAS FIR, N48°W, 11.1' -HB REC. A 10" FIR, N51°W, 11.2 (GLO) FD. A 29" PONDEROSA PINE, N4°E, 16.3' -HB REC. A 28" YELLOW PINE, N4 1/2°E, 15.8' (GLO)</p>
<p>LS 2670 CORNER No. 36 S 1/16 S30 1959 FD. A 1/2" IRON PIPE WITH A 1 1/2" ALUM CAP IN A MOUND OF STONE PER 2 RS 83 WHICH BEARS S 5° 47' 08" E, 1.38' FROM TRUE POSITION FOR S 1/16 CORNER 25/30. CORNER FALLS ON A MODERATE SOUTH SLOPE IN TIMBER. FD. A 21" WHITE FIR, N22°W, 20.0' -HB REC. AN 8" WHITE FIR, N56°E, 13.6' (2 RS 83) FD. A 28" SUGAR PINE, S13 1/2°E, 21.8' -HB REC. AN 8" SUGAR PINE, N72°W, 4.3' (2 RS 83)</p>	<p>CORNER No. 44 RECORD POSITION PER 12 RS 37 - NOT TIED THIS SURVEY.</p>			<p>RECORD OF SURVEY FOR USDA FOREST SERVICE PLUMAS NATIONAL FOREST "STRAWBERRY" IN SECTIONS 8, 17, 20, 29 AND 30, T 21 N, R 9 E, AND IN SECTION 1, T 20 N, R 8 E, MDM, IN THE UNINCORPORATED AREA OF PLUMAS COUNTY, STATE OF CALIFORNIA</p> <p>DEL TERRA INC. SURVEYING 1168 INDUSTRIAL ST. REDDING, CA 96002 PHONE (530) 241-8050</p> <p>DATE: MARCH, 2007 SHEET 6 OF 7</p>