

### 1 Cor. of secs. 14, 15, 22 & 23, T21N, R9E

#### HISTORY OF ORIGINAL CORNER ESTABLISHED:

Original corner set by D.C. Hall, under GLO Contract dated July 5, 1881, approved March 13, 1883, record states  
Set a slate stone 12 x 12 x 6 ins., 6 ins. deep, mkd. with 3 notches on the south and two on the east and raised a stone mound alongside.  
from which:  
A fir, 20 ins. diam., bears N. 80° E., 55 lks. dist., mkd. T21N R9E S14 BT  
A fir, 20 ins. diam., bears S. 25° E., 38 lks. dist., mkd. T21N R9E S23 BT  
A fir, 24 ins. diam., bears N. 30° W., 36 lks. dist., mkd. T21N R9E S15 BT

#### Subsequent monumentation:

Corner was remonumented by Albert H. Devoe, LS 3079, during survey recorded in 1962 as 2-RS-16 in Sierra County and 2-RS-75 in Plumas County, from the remains of the original southeast bearing tree, record states:

Original BT is a stump S. 25° E., 25 ft., scribing visible.  
the sec. cor. is a 2 in. steel cap on pipe in rock mound

from which:  
A Douglas fir, 8 ins. diam. bears N. 32°30' E., 17.4 ft., scribed S14 BT  
A sugar pine, 11 ins. diam. bears S. 75°15' E., 34.0 ft., scribed S23 BT  
A Douglas fir, 11 ins. diam. bears S. 45°15' W., 43 ft., scribed S22 BT  
A white fir, 13 ins. diam. bears N. 51°15' W., 24.6 ft., scribed S15 BT

#### DESCRIPTION OF CORNER EVIDENCE FOUND:

Found a 2 ins. diam. iron pipe, firmly set, with steel cap mkd. as shown, projecting 5 ins. above the ground, from which the remains of original bearing tree  
A fir stump, 31 ins. diam., bears S. 19°2' E., 24.5 ft. dist., with blaze and scribe marks S/3 BT clearly visible (record: S. 25° E., 25.1 ft.)  
and the accessories mkd. by Devoe  
A fir, 17 ins. diam., alive and healthy, bears N. 32°15' E., 17.4 ft. dist., with fully healed blaze.  
A pine, 23 ins. diam., alive and healthy, bears S. 75°4' E., 34.0 ft. dist., with no discernable blaze but aged red paint.  
A fir, 26 ins. diam., alive and healthy, bears S. 45°4' W., 43 ft. dist., with fully healed blaze.  
A fir, 23 ins. diam., alive and healthy, bears N. 51°4' W., 24.6 ft. dist., with fully healed blaze.

#### DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE LOCATION OF THIS CORNER:

None

State Plane Coordinates of corner position, CA Zone 1, NAD83 (CORS96):  
N = 1765986.71 sft. E = 6857136.08 sft.



### continued from previous column

#### record states

Original BT's are  
A 58 in. diam. white fir, which bears N. 45° E., 89.1 ft., face is closed.  
A 60 in. diam. white fir, scribing visible, which bears S. 10° E., 78.5 ft.  
Set a brass cap in rock mound at corner position  
from which  
A sugar pine, 24 ins. diam. bears N. 44°15' W., 35 ft., scribed S10 BT  
A white fir, 13.5 ins. diam. bears N. 71°30' E., 9.6 ft., scribed S11 BT  
A white fir, 17.5 ins. diam. bears S. 32°45' E., 25 ft., scribed S14 BT  
A white fir, 20 ins. diam. bears S. 45°15' W., 26 ft., scribed S15 BT

#### DESCRIPTION OF CORNER EVIDENCE FOUND:

Found a 1 in. diam. iron pipe, loose, with 2 ins. diam. brass cap, mkd. as shown, projecting 4 ins. above the ground, in mound 3 ft. base, 1 ft. high from which the original bearing trees

A fir, 83 ins. diam., alive and healthy, bears S. 10° E., 78.5 ft. dist., with opened blaze and scribe marks visible.  
A fir, 59 ins. diam., alive and healthy, bears N. 45° E., 94.9 ft. dist., with a fully healed blaze, (record: 89.1 ft.)  
and the accessories mkd. by Devoe  
A fir, 27 ins. diam., alive and healthy, bears N. 72° E., 9.2 ft. dist., with fully healed blaze (record: N. 74° E.)  
A fir, 27 ins. diam., alive and healthy, bears S. 33° E., 24.4 ft. dist., with fully healed blaze.  
A fir, 30 ins. diam., alive and healthy, bears S. 44° W., 23.8 ft. dist., with fully healed blaze.  
A fir, 24 ins. diam., alive and healthy, bears N. 46° W., 33.9 ft. dist., with fully healed blaze, (record: 33.0 ft.)

#### DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE LOCATION OF THIS CORNER:

I remove the recovered iron pipe, and replace it with a standard USDA Forest Service 3 1/4 ins. diam. alum. cap on 3/4 in. diam. by 30 ins. long alum. drive rod, buried 28 ins. in the gnd., with magnet in 9 ins. long break-away base, in rock collar, mkd. as shown.

State Plane Coordinates of corner position, CA Zone 1, NAD83 (CORS96):  
N = 1771305.31 sft. E = 6856983.17 sft.




### continued from previous column

#### DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE LOCATION OF THIS CORNER:

At the proportionate distance, shown herein, set a standard USDA Forest Service 3 1/4 ins. diam. alum. cap on 3/4 in. diam. by 30 ins. long alum. drive rod, buried 20 ins. in the gnd., with magnet in 9 ins. long break-away base, in rock mound, 3 ft. base, to top, mkd. as shown

From which:  
A Douglas fir, 7 ins. diam., bears N. 69° E., 5.4 ft. dist., mkd. X BT.  
A Douglas fir, 13 ins. diam., bears N. 49°2' W., 10.1 ft. dist., mkd. C-E-NV1/64 S14 BT.

State Plane Coordinates of corner position, CA Zone 1, NAD83 (CORS96):  
N = 1769986.24 sft. E = 6858948.55 sft.



### 7 E-W 1/64 cor. of secs. 11 and 14, T21N, R9E

#### HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner was established by Albert H. Devoe, LS 3079, during survey recorded in 1962 as 2-RS-16 in Sierra County and 2-RS-75 in Plumas County.

record states

Set brass cap in rock mound

from which  
A 16 in. diam. sugar pine, bears S. 11°45' W., 17.4 ft., scribed EW 1/64 BT

#### DESCRIPTION OF CORNER EVIDENCE FOUND:

Found a 3/4 in. diam. iron pipe, loose, with 1 in. diam. brass cap, mkd. as shown, projecting 4 ins. above rock mound, 2 ft. base, 1/2 ft. high from which the remains of original bearing tree


A dead and standing pine, bears S. 11°45' W., 17.4 ft. dist., with a fully healed blaze

#### DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE LOCATION OF THIS CORNER:

I remove the recovered iron pipe, and replace it with a standard USDA Forest Service 3 1/4 ins. diam. alum. cap on 3/4 in. diam. by 30 ins. long alum. drive rod, buried 27 ins. in the gnd., with magnet in 9 ins. long break-away base, in rock collar, mkd. as shown.

New bearing tree  
A white fir, 30 ins. diam., bears N. 35°4' E., 71.8 ft. dist., mkd. EW1/64 S11 BT.  
A white fir, 6 ins. diam., bears N. 45° W., 9.1 ft. dist., mkd. EW1/64 S11 BT.

State Plane Coordinates of corner position, CA Zone 1, NAD83 (CORS96):  
N = 1771347.21 sft. E = 6859562.22 sft.



### 8 C-W 1/16 cor. of sec. 14, T21N, R9E


#### HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner was established by Albert H. Devoe, LS 3079, during survey recorded in 1962 as 2-RS-16 in Sierra County and 2-RS-75 in Plumas County.

record states

Set brass cap in rock mound on steep rocky slope, 15 ft. east of old H2O ditch.

from which  
A Douglas fir, 16 ins. diam. bears S. 17°30' W., 28.3 ft. dist., scribed CW 1/16 BT



#### DESCRIPTION OF CORNER EVIDENCE FOUND:

Found a 3/4 in. diam. iron pipe, loose, with 1 in. diam. brass cap, mkd. as shown, projecting 12 ins. above rock mound, 1 ft. base, 1 ft. high.

from which the remains of original bearing tree

A Douglas fir, 20 ins. diam., alive and healthy, bears S. 21°2' W., 28.3 ft. dist., with a fully healed blaze (record: S. 17°2' W.)

#### DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE LOCATION OF THIS CORNER:

I remove the recovered iron pipe, and replace it with a standard USDA Forest Service 3 1/4 ins. diam. alum. cap on 3/4 in. diam. by 30 ins. long alum. drive rod, buried 27 ins. in the gnd., with magnet in 9 ins. long break-away base, in rock collar, mkd. as shown.

New bearing tree  
A white fir, 6 ins. diam., bears S. 5° W., 53 lks. dist., mkd. 1/4 S BT

State Plane Coordinates of corner position, CA Zone 1, NAD83 (CORS96):  
N = 1768621.99 sft. E = 6858362.09 sft.



### 9 1/4 cor. of secs. 14 and 23, T21N, R9E

#### HISTORY OF ORIGINAL CORNER ESTABLISHED:

Original corner set by D.C. Hall, under GLO Contract dated July 5, 1881, approved March 13, 1883, record states

Set a slate stone 18 x 12 x 10 - 9" deep, marked 1/4 S, and raised a stone mound alongside for 1/4 section corner

from which:  
A fir, 6 ins. diam., bears S. 5° W., 53 lks. dist., mkd. 1/4 S BT

#### DESCRIPTION OF CORNER EVIDENCE FOUND:


Thorough search of area finds no evidence of original corner position. Search area has been extensively logged and mined. Corner is determined lost and reestablished by single proportionate measurement.

#### DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE LOCATION OF THIS CORNER:

At the proportionate distance, shown herein, set a standard USDA Forest Service 3 1/4 ins. diam. alum. cap on 3/4 in. diam. by 30 ins. long alum. drive rod, buried 26 ins. in the gnd., with magnet in 9 ins. long break-away base, in rock collar, mkd. as shown.

From which:  
A cedar, 10 ins. diam., bears N. 10° E., 74.0 ft. dist., mkd. 1/4 S14 BT.  
A pine, 11 ins. diam., bears S. 41°4' W., 27.5 ft. dist., mkd. 1/4 S23 BT.

State Plane Coordinates of corner position, CA Zone 1, NAD83 (CORS96):  
N = 1766013.24 sft. E = 6859642.12 sft.



### 10 C-S 1/16 cor. of sec. 14, T21N, R9E

#### HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner was established by Albert H. Devoe, LS 3079, during survey recorded in 1962 as 2-RS-16 in Sierra County and 2-RS-75 in Plumas County.

record states

Set brass cap in small rock mound

from which  
A white fir, 9 ins. diam. bears East, 11.9 ft. scribed CS 1/16 BT

A white fir, 10 ins. diam. bears S. 20°30' E., 19.1 ft. scribed CS 1/16 BT

#### DESCRIPTION OF CORNER EVIDENCE FOUND:

Found 1 in. diam. iron pipe, loose, with 1 1/2 ins. diam. brass cap, mkd. as shown, projecting 4 ins. above rock collar, from which the original bearing tree

A fir, 23 ins. diam., alive and healthy, bears East, 11.9 ft., with a fully healed blaze.


A down and dead fir, slightly down hill from a stump hole with a fully healed blaze, bears S. 20°2' E., 19.1 ft. dist.

#### DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE LOCATION OF THIS CORNER:

I remove the recovered iron pipe, and replace it with a standard USDA Forest Service 3 1/4 ins. diam. alum. cap on 3/4 in. diam. by 30 ins. long alum. drive rod, buried 26 ins. in the gnd., with magnet in 9 ins. long break-away base, in rock collar, mkd. as shown.

New bearing tree  
A cedar, 16 ins. diam., bears N. 18°4' W., 35.6 ft. dist., mkd. CS 1/16 S14 BT.

State Plane Coordinates of corner position, CA Zone 1, NAD83 (CORS96):  
N = 1767320.68 sft. E = 6859634.75 sft.



### 11 Cor. of secs. 10, 11, 14 & 15, T21N, R9E

#### HISTORY OF ORIGINAL CORNER ESTABLISHED:

Original corner set by D.C. Hall, under GLO Contract dated July 5, 1881, approved March 13, 1883, record states


Set a granite stone 11 x 10 x 8 ins., 5 ins. deep marked with 2 notches on east and 4 on south and raised a stone mound alongside.

from which:  
A fir, 24 ins. diam., bears N. 45° E., 135 lks. dist., mkd. T21N R9E S11 BT

A spruce, 48 ins. diam., bears S. 10° E., 119 lks. dist., mkd. T21N R9E S14 BT

#### Subsequent monumentation:

Corner was remonumented by Albert H. Devoe, LS 3079, during survey recorded in 1962 as 2-RS-16 in Sierra County and 2-RS-75 in Plumas County, from the original NE and SE bearing trees.



continues in next column