

SECTION 6

- ⑩ NW SECTION 6
RECORD: BLM BC (Daniel Dierenfield 1978)
FD: BLM BC
SET: NOTHING
- ⑪ N 1/16 SECTIONS 1/6
RECORD: NONE
FD: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 11" DOUGLAS FIR SCRIBED CN 1/16 S6 BT N65°21'E 15.8'
FWB: 10" PONDEROSA PINE SCRIBED CN 1/16 S1 BT S42°43'W 7.8'
- ⑫ NW 1/16 S6
RECORD: NONE
FD: NOTHING
SET: RM STANDARD USFS MONUMENT IN MOS 4' WEST OF TRUE COR
FWB: 12" DOUGLAS FIR SCRIBED NW 1/16 S6 BT S88°11'W 33.2'
FWB: 10" CEDAR SCRIBED NW 1/16 S6 BT S10°53'W, 47.2'
- ⑬ CW 1/16 S6
RECORD: NONE
FD: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 17" CEDAR SCRIBED CW 1/16 S6 BT N39°44'W 4.6'
FWB: 7" CEDAR SCRIBED CW 1/16 S6 BT S60°45'W 21.9'
- ⑭ W 1/16 S6/S7
RECORD: NONE
FD: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 13" DOUGLAS FIR SCRIBED W 1/16 S6 BT N73°54'W 18.0'
FWB: 12" DOUGLAS FIR SCRIBED W 1/16 S6 BT N43°13'E 23.4'
- ⑮ SW SECTION CORNER SECTION 6
RECORD: 3X3 POST IN MOS (GLO HALL 1882)
FWB: 20" FIR N84°W 42 LKS.
FD: REMAINS OF ROTTEN FIR WITH 1940'S LOCATION POSTER
SET: STANDARD USFS MONUMENT IN MOS
FWB: 16" DOUGLAS FIR SCRIBED T23N R12E S7 BT S57°26'E 4.6'
FWB: 12" DOUGLAS FIR SCRIBED T23N R11E S12 BT S65°18'W 38.7'
FWB: 9" DOUGLAS FIR SCRIBED T23N R11E S1 BT N83°07'W 47.9'
FWB: 6" DOUGLAS FIR SCRIBED X BT N01°17'E 15.5'
- ⑯ 1/4 S6/S7
RECORD: 16X14X10 VOLCANIC STONE IN MOS (GLO HALL, 1882)
FWB: 22" FIR N70°W 35 LKS.
FWB: 21" PITCH PINE S61°E 81 LKS.
FD: MOS
FWB: 34" DOUGLAS FIR WITH SCAR AND TAGS N76° 51'W 29.9'
FWB: 36" PONDEROSA PINE S41°03'E 51.7'
SET: STANDARD USFS MONUMENT IN MOS
- ⑰ NE SECTION CORNER SEC 6
RECORD: FS LS5623 (14RS83)
FD: FS LS5623 (14RS83)
SET: NOTHING - ACCEPTED EXISTING CORNER
- ⑱ SE SECTION 6
RECORD: BLM BC (Daniel Dierenfield 1978 Remon.)
FD: BLM BC
SET: NOTHING - ACCEPTED EXISTING BLM CORNER

SECTION 7

- ⑲ C 1/4 S 7
RECORD: NONE
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 15" DOUGLAS FIR SCRIBED C 1/4 S7 BT N59°48'W 26.6'
FWB: 9" BLACK OAK SCRIBED C 1/4 S7 BT N54°24'E 9.8'
- ⑳ W 1/4 SECTION 7
RECORD: USFS STANDARD MONUMENT (13RS29) (HAMBY)
FOUND: USFS STANDARD MONUMENT (RCE 15265) (13RS29)
NOTHING - ACCEPTED EXISTING USFS CORNER
- ㉑ E 1/4 SECTION 7
RECORD: GRANITE STONE 18X16X4 (D.C.HALL 1882)
FWB: 16" FIR N84°E 92 LKS.
FWB: 30" PITCH PINE N30°W 159 LKS.
FD: NOTHING
SET: STANDARD USFS MONUMENT IN MOS (PRORATE POSITION)
FWB: 13" DOUGLAS FIR SCRIBED 1/4 S7 BT N01°02'W 61.4'
FWB: 16" PONDEROSA PINE SCRIBED 1/4 S8 BT S42°24'E 79.5'
- ㉒ SW CORNER SECTION 7
RECORD: BLM BC (10RS74 HAMBY)
FD: BLM BC (10RS74 HAMBY)
SET: ACCEPTED EXISTING BLM BC
- ㉓ SE SECTION CORNER SECTION 7
RECORD: 20" PINE STUMP (10RS74 HAMBY)
FD: 20" PINE STUMP
FWB: BLM BC RM S29°31'E 9.2' (10RS74)
SET: NOTHING - ACCEPTED EXIST CORNER
- ㉔ S 1/4 SECTON 7
RECORD: 5/8 REBAR W/ALM CAP LS 2843 (10RS74 HAMBY)
FD: ALM CAP LS 2843 (10RS74)
SET: NOTHING - ACCEPTED EXISTING CORNER

SECTION 12

- ㉕ N 1/4 SECTION 12
RECORD: BLM BC (Daniel Dierenfield 1978)
FD: BLM BC (Daniel Dierenfield 1978)
SET: NOTHING - ACCEPTED BLM CORNER
- ㉖ NW 1/16 SECTION 12
RECORD: 5/8 REBAR W ALM CAP LS2843 (13RS29 HAMBY)
FD: 5/8 REBAR W ALM CAP LS2843 (13RS29 HAMBY)
SET: STANDARD USFS MONUMENT IN MOS
FWB: 15" CEDAR SCRIBED NW 1/6 S12 BT N33°37'W 22.8'
FWB: 9" CEDAR SCRIBED NW 1/6 S12 BT N86°57'E 12.7'
- ㉗ CW 1/16 SECTION 12
RECORD: 5/8 REBAR W ALM CAP LS2843 (13RS29 HAMBY)
FD: 5/8 REBAR W ALM CAP LS2843 (13RS29 HAMBY)
SET: STANDARD USFS MONUMENT IN MOS
FWB: 37" CEDAR SCRIBED CW 1/6 S12 BT S72°55'W 23.2'
FWB: 10" FIR SCRIBED CW 1/6 S12 BT S08°52'E, 43.9'

- ㉘ SW 1/16 SECTION 12
RECORD: RECORD CORNER (13RS29 HAMBY LS 2843)
FD: CORNER POINT (CALC. PER 13RS29)
SET: STANDARD USFS MONUMENT IN MOS
FWB: 12" FIR SCRIBED SW 1/6 S12 BT N40°50'W 16.2'
FWB: 15" FIR SCRIBED SW 1/6 S12 BT N62°00'E 20.4'
FWB: WOOD POST TAGGED RCE 7294 S78°47'E 18.4'
FWB: 3/8" RB TAGGED RCE 15265 S89°05'08"E 7.65'
- ㉙ CS 1/16 SECTION 12
RECORD: RECORD CORNER (13 RS 29 HAMBY)(CALC POSTION)
FD: NOTHING
SET: RM (PT 1) STANDARD USFS MONUMENT IN MOS
FWB: 16" PONDEROSA PINE SCRIBED CS 1/6 S12 BT N19°42'E 44.0'
FWB: 8" FIR SCRIBED CS 1/6 S12 BT N69°16'E, 29.3'

- ㉚ S 1/4 SECTION 12
RECORD: 3/4" IP TAGGED LS 3297 (13 RS 29 HAMBY)
FD: 3/4" IP TAGGED LS 3297
SET: NOTHING

SECTION 2

- ㉛ NW SECTION CORNER SECTION 2
RECORD: BLM BC (Hiester 1942)(SEE SHT 11)
FD: BLM BC (Hiester 1942)
SET: NOTHING - ACCEPTED BLM CORNER
- ㉜ N 1/4 S2
RECORD: 26X16X6 STONE IN MOS (4RS18)
FWB: 24" CEDAR DOWN & DEAD S26°E 46.2'(4RS18)
FWB: 13.5" DOUGLAS FIR NBT S42°W 33.6' NBT(4RS18)
FWB: 19.2" CEDAR WITH SCAR N13°W 65.3' (4RS18)
FD: 26X16X6 STONE IN MOS (4RS18)
FWB: 20" DOUGLAS FIR WITH SCAR S42°W 33.5'(4RS18)
SET: STANDARD USFS MONUMENT IN MOS (REPLACED STONE)
- ㉝ NE SECTION CORNER SECTION 2
RECORD: 3/4" IRON PIPE (4RS12 HENDERSON)
FD: 1" IRON PIPE IN MOS
SET: STANDARD USFS MONUMENT IN MOS
FWB: 15" SUGAR PINE WITH SCAR N2°E 58.2'
FWB: 17" PONDEROSA PINE WITH SCAR S48°W 53.7'
- ㉞ W 1/4 SECTION 2
RECORD: 1.5" BRASS CAP (4RS82 NICKLOS)
FOUND: 1.5" BRASS CAP LS 3848
SET: NOTHING
- ㉟ C 1/4 SECTION 2
RECORD: NONE
FD: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 18" DOUGLAS FIR SCRIBED C 1/4 S2 BT N43°W 15.8' NBT
FWB: 11" RED FIR SCRIBED C 1/4 S2 BT S33°W 17.0' NBT

- ㊱ SW SECTION CORNER SECTION 2
RECORD: USFS STANDARD MONUMENT LS4570 (8RS61)
FOUND: USFS STANDARD MONUMENT LS4570 (8RS61)
SET: NOTHING - ACCEPTED USFS CORNER

SECTION 2

- ㊲ S 1/4 SECTION 2
RECORD: STANDARD USFS MON. LS4570 (8RS61)
FOUND: STANDARD USFS MON. LS4570 (8RS61)
SET: NOTHING - ACCEPTED USFS MONUMENT
- ㊳ E 1/4 SECTION 2
RECORD: 1" IP W/WASHER LS 3297 (4RS12)
FOUND: 1" IP W/WASHER LS 3297 (4RS12)
SET: NOTHING - ACCEPTED LS3297 CORNER

SHEET INDEX

SECTION 11 T23NR11E MDM	1 OF 11
SECTION 6 & 7 T23NR12E MDM	2 OF 11
SECTION 2 T22NR11E MDM	3 OF 11
SECTION 12 T23NR11E MDM	4 OF 11
SECTION 27 & 26 T23NR11E MDM	5 OF 11
SECTION 10 T23NR11E MDM	6 OF 11
CORNER NOTES S11	7 OF 11
CORNER NOTES S6 S7 S12 S2	8 OF 11
CORNER NOTES S27 S26	9 OF 11
CORNER NOTES S10	10 OF 11
BLM FIELD NOTES S27 S26	11 OF 11

GENERAL NOTES

A STANDARD UNITED STATES FOREST SERVICE (USFS) DRIVE-IN MONUMENT IS A 5/8" DIAMETER ALUMINUM ROD WITH A 3-1/4" ALUMINUM CAP EDGE-MARKED WITH THE USFS LOGO.

A STANDARD BUREAU OF LAND MANAGEMENT (BLM) MONUMENT IS A 2-1/2" DIAMETER STEEL PIPE, 28" LONG WITH A 3-1/2" BRASS CAP EDGE-MARKED WITH THE BLM LOGO.

NOTE

ALL BLM CORNERS USED ON THIS SURVEY WERE VERIFIED AND ACCEPTED BY ME, HOWEVER, THE BLM BEARING TREES WERE NOT TIED BUT WERE CHECKED IN THE FIELD AND COMPARED WITH THE BLM FIELD NOTES.

RECORD OF SURVEY

SECTIONS 6 & 7 T23N R12E, MDM
SECTIONS 2, T22N R11E, MDM
SECTION 12, T23N R11E, MDM
PLUMAS COUNTY, CALIFORNIA
FOR
U.S.D.A. PLUMAS NATIONAL FOREST
159 LAWRENCE ST
QUINCY, CA. 95971

DRAWN BY: B. SNOW DATE: DECEMBER, 2011 SHEET 8 OF 11