

SECTION 29

(20) N 1/4 SECTION 29

RECORD: 3 1/4" ALM CAP RCE 19119 (R2)
FOUND: 3 1/4" ALM CAP RCE 19119 (R2)
SET: NOTHING - ACCEPTED EXISTING CORNER

(21) NE CORNER SECTION 29

RECORD: 3 1/4" ALM CAP RCE 19119 (R2)
FOUND: 3 1/4" ALM CAP RCE 19119 (R2)
SET: NOTHING

(22) CN 1/16 SECTION 29

RECORD: NONE
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 9" CEDAR SCRIBED "CN 1/16 S29 BT" N88°59'W, 26.7'
FWB: 24" WHITE FIR SCRIBED "CN 1/16 S29 BT" S4°09'W 51.4'

(23) N 1/16 SECTION 29/28

RECORD: NONE
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 11" WHITE FIR SCRIBED "N 1/16 S28 BT" N06°31'E 87.2'
FWB: 16" WHITE FIR SCRIBED "N 1/16 S28 BT" S47°36'E 65.6'

(24) S 1/4 SECTION 29

RECORD: ASPEN FOR 1/4 CORNER (R1)
FWB: 5" CEDAR, S36°E, 9 LKS. (R1)
FWB: 10" ASPEN, N40°W, 18 LKS. (R1)
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 28" RED FIR SCRIBED "1/4 S32 BT" S35°43'W 27.0'
FWB: 16" RED FIR SCRIBED "1/4 S32 BT" S13°32'E 39.0'

(25) W 1/4 CORNER SECTION 29

RECORD: POST (R1)
FWB: 3" BLACK OAK N85°W, 17 LKS. (R1)
FWB: 5" BLACK OAK S22°E 14 LKS. (R1)
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 12" WHITE FIR SCRIBED "1/4 S30 BT" N32°18'W 37.4'
FWB: 13" WHITE FIR SCRIBED "1/4 S30 BT" S71°26'W 31.6'

(26) SW CORNER SECTION 29

RECORD: 5" BLACK OAK FOR SECTION CORNER (R1)
FWB: 30" FIR N62°E, 20 LKS. (R1)
FWB: 36" FIR S45°E, 110 LKS. (R1)
FWB: 40" FIR S26°W, 105 LKS. (R1)
FWB: 8" BLACK OAK, N75°W, 112 LKS. (R1)
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS (SET BY DOUBLE PRORATE)
FWB: 10" BLACK OAK SCRIBED "T23N R6E S30 BT" N42°38'W, 30.2'
FWB: 21" PONDEROSA PINE SCRIBED "T23N R6E S29 BT" N14°53'W 30.3'
FWB: 14" PONDEROSA PINE SCRIBED "T23N R6E S32 BT" S71°17'E 34.6'
FWB: 16" PONDEROSA PINE SCRIBED "T23N R6E S31 BT" S69°50'W 19.2'

(27) NW SECTION CORNER 29

RECORD: 10" FIR FOR SECTION CORNER (R1)
FWB: 22" FIR N25°W 33 LKS. (R1)
FWB: 30" FIR S82°W 48 LKS. (R1)
FWB: 36" FIR N80°E 125 LKS. (R1)
FWB: 28" SUGAR PINE S45°E 52 LKS. (R1)
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS (SET BY DOUBLE PRORATE)
FWB: 30" SUGAR PINE SCRIBED "T23N R6E S19 BT" N17°55'W 48.1'
FWB: 16" RED FIR SCRIBED "T23N R6E S20 BT" N16°47'E 7.2'
FWB: 10" WHITE FIR SCRIBED "T23N R6E S29 BT" S39°46'E 6.9'
FWB: 11" WHITE FIR SCRIBED "T23N R6E S30 BT" S82°13'W 35.4'

SECTION 19

(28) NW CORNER SECTION 19

RECORD: NOTHING SET AT CORNER POINT (R3)
FWB: GLO BRASS CAP WC N2°34'W 26 LKS (R3)
FOUND: NOTHING AT CORNER POINT
FWB: BRASS CAP FOR WC N2°08'W 26 LKS (R3)
SET: NOTHING

(29) W 1/4 SECTION 19

RECORD: GLO BRASS CAP (R3)
FWB: A 40" SUGAR PINE N3 1/2°E 205 LKS (R3)
A 40" RED FIR S35°W 27 LKS (R3)
FOUND: GLO BRASS CAP (R3)
FWB: A 49" SUGAR PINE N3 1/2°E 205 LKS (R3)
A 50" RED FIR S35°W 27 LKS (R3)
SET: NOTHING - ACCEPTED EXISTING GLO CORNER

(30) SW CORNER SECTION 19

RECORD: GLO BRASS CAP (R3)
FWB: A 48" SUGAR PINE STUMP N51 1/2°E 117 LKS NO VISABLE SCRIBE (R3)
FWB: A 28" FIR SNAG S72°E 61 LKS, FOUND SCRIBING. (R3)
FWB: A 12" FIR STUMP S16°W 109 LKS BURNED. (R3)
FWB: A 36" SUGAR PINE N15°W 155 LKS WITH SCRIBING VISIBLE (R3)
FOUND: GLO BRASS CAP (R3)
FWB: 24" WHITE FIR EAST 39 LKS CF (R3)
FWB: 12" STUMP ROTTEN S76 1/2°W 58 LKS (R3)
FWB: 22" SUGAR PINE N52°W 136 LKS CF (R3)
FWB: 40" ROTTEN STUMP N15°W 155 LKS CF (R3)
SET: NOTHING - ACCEPTED GLO CORNER

(31) N 1/16 SECTIONS 24/19

RECORD: NONE
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 9" WHITE FIR SCRIBED "N 1/16 S24 BT" N27°47'W 37.2'
FWB: 13" WHITE FIR SCRIBED "N 1/16 S19 BT" S47°11'E 52.6'

(32) NW 1/16 SECTION 19

RECORD: NONE
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 6" DOUGLAS FIR SCRIBED "NW 1/16 S19 BT" N05°07'W 10.0'
FWB: 8" WHITE FIR SCRIBED "NW 1/16 S19 BT" S50°24'W 42.9'

(33) CW 1/16 SECTION 19

RECORD: NONE
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 15" DOUGLAS FIR SCRIBED "CW 1/16 S19 BT" N28°04'W 15.0'
FWB: 30" SUGAR PINE SCRIBED "CW 1/16 S19 BT" S69°18'E 6.0'

(34) C 1/4 SECTION 19

RECORD: NONE
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 19" WHITE FIR SCRIBED "C 1/4 S19 BT" N87°13'E 12.8'
FWB: 20" WHITE FIR SCRIBED "C 1/4 S19 BT" S11°47'E 20.4'

(35) CE 1/16 SECTION 19

RECORD: NONE
FOUND: NOTHING
SET: NOTHING AT CORNER POINT
FWB: SET WITNESS COR. STANDARD USFS MON. IN MOS S87°13'19"E 34.0'
FWB: 18" DOUGLAS FIR SCRIBED "CE 1/16 S19 BT" S26°38'E 92.5'
FWB: 33" CEDAR SCRIBED "CE 1/16 S19 BT" S42°13'W 10.0'

(36) SE 1/16 SECTION 19

RECORD: NONE
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 18" WHITE FIR SCRIBED "SE 1/16 S19 BT" S77°12'E 22.2'
FWB: 12" DOUGLAS FIR SCRIBED "SE 1/16 S19 BT" N13°54'W 12.2'

(37) S 1/16 SECTION 19/20

RECORD: NONE
FOUND: NOTHING
SET: NOTHING AT CORNER POINT (CORNER IS NOT ACCESSIBLE)
FWB: SET WITNESS COR. STANDARD USFS MONUMENT IN MOS N0°29'16"E 5.0'
FWB: 8" BLACK OAK SCRIBED "X BT" N23°53'E, 42.2'
FWB: 34" CEDAR SCRIBED "X BT" S87°12'E 31.8'

(38) N 1/4 SECTION 19

RECORD: NOTHING
FOUND: NOTHING AT CORNER POINT
FWB: FD WITNESS CORNER USFS MON. LS5623 S14°26'18"W 2.10'(SEE NOTE)
SET: NOTHING AT CORNER POINT

(39) S 1/4 SECTION 19

RECORD: 12"x8"x8" STONE IN STONE MOUND (R1)
FOUND: 12"x8"x8" STONE IN STONE MOUND (R1)
FWB 19" CEDAR S69°40'W 24.4' CF (R1)
FWB 20" CEDAR N32°33'W 19.4' CF (R1)
FWB 72" SUGAR PINE STUMP CF S20°W 58 LKS (R1)
FWB 60" FIR STUMP SCRIBING VISIBLE N66°E 41 LKS (R1)
SET: REPLACED STONE WITH STANDARD USFS MONUMENT IN MOS

(40) E 1/4 SECTION 19

RECORD: POST (R1)
FWB 8" BLACK OAK N84°E 49 LKS (R1)
FWB 4" BLACK OAK N41°W 26 LKS. (R1)
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 8" BLACK OAK SCRIBED "1/4 S20 BT" N21°28'E 11.3'
FWB: 8" DOUGLAS FIR SCRIBED "1/4 S20 BT" S41°18'E 21.1'

(41) NE CORNER SECTION 19 (WITNESS POINT)

RECORD: 4X4 OAK POST (R1)
FWB: 18" FIR N42°E 49 LKS. (R1)
FWB: 20" FIR N40°W 70 LKS. (R1)
FWB: 4" BLACK OAK S9°W 18 LKS (R1)
FWB: 4" BLACK OAK S3°E 7 LKS (R1)
FOUND: NOTHING
SET: NOTHING (CORNER IS NOT ACCESSIBLE)
FWB: SET A WITNESS PT. STANDARD USFS MON. IN MOS S0°29'16"W 1251.87'
FWB: 16" DOUGLAS FIR, SCRIBED "X BT" N7°E 46.3'
FWB: 25" DOUGLAS FIR SCRIBED "X BT" S71°E 59.3'

(42) NE CORNER SECTION 6

RECORD: GLO BRASS CAP (R3)
FWB: A 8" SUGAR PINE S24 1/4° E 72 LKS (R3)
FWB A 6" BLACK OAK S53°W 64 LKS (R3)
FWB: A 10" BLACK OAK N39 1/4° W 47 LKS (R3)
FOUND: FD GLO BRASS CAP (R3)
FWB: 18" SUGAR PINE S24°E 47.5' CF (R3)
SET: NOTHING

(43) NE CORNER SECTION 20

RECORD: SET 14"x8"x8" GRANITE STONE IN MOS 48" BASE X 24" HIGH (R1)
FWB: A 18" CEDAR S76°W 85 LKS (R1)
FOUND: USFS ALM CAP LS 5623 (SEE NOTE)
FWB: A 22" CEDAR SNAG W/SCRIBING VISBLE N35°00'W 31.1' (R1)
SET: NOTHING- ACCEPTED EXISTING USFS MONUMENT

(44) N 1/4 SECTION 20

RECORD: POST (R1)
FWB 4" BLACK OAK S47°W 20 LKS (R1)
FWB 4" BLACK OAK N9°W 22 LKS (R1)
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 13" CEDAR SCRIBED "1/4 S17 BT" N35°00'W 31.1'
FWB: 14" BLACK OAK SCRIBED "1/4 S20 BT" S19°36'W 29.5'

(45) W1/4 S32

RECORD: POST (R1)
FWB 12" FIR S81°W 32 LKS (R1)
FWB 10" FIR S49°E 84 LKS (R1)
FOUND: NOTHING
SET: STANDARD USFS MONUMENT IN MOS
FWB: 9" SUGAR PINE SCRIBED "1/4 S31 BT" N2°47'W 22.0'
FWB: 8" BLACK OAK SCRIBED "1/4 S31 BT" S69°49'W 21.5'

(46) SW CORNER SECTION S32

RECORD: STANDARD BLM MONUMENT (1981 HAMILTON)
FWB: 6" CEDAR N29 3/4°E 86.5 LKS (1981 HAMILTON)
FWB: 8" CEDAR S30°E 14.5 LKS (1981 HAMILTON)
FWB: 14" BLACK OAK S39 3/4°W 51 LKS (1981 HAMILTON)
FWB: 10" CEDAR N55°W 5 LKS (1981 HAMILTON)
FOUND: STANDARD BLM MONUMENT (1981 HAMILTON)
SET: NOTHING - ACCEPTED BLM CORNER

GENERAL NOTES

(R1) GLO 1875 VON SCHMIDT
(R2) 6RS78
(R3) GLO 1938 WILSON

ABBREVIATIONS ON SHT 2 OF 4

A STANDARD UNITED STATES FOREST SERVICE (USFS) DRIVE-IN MONUMENT IS A 5/8" DIAMETER ALUMINUM ROD WITH A 3-1/4" ALUMINUM CAP EDGE-MARKED WITH THE USFS LOGO.

ALL USFS CORNERS SET ON THIS SURVEY WERE STAMPED AS PER THE BLM MANUAL OF INSTRUCTIONS.

A STANDARD BUREAU OF LAND MANAGEMENT (BLM) MONUMENT IS A 2-1/2" DIAMETER STEEL PIPE, 28" LONG WITH A 3-1/2" BRASS CAP EDGE-MARKED WITH THE BLM LOGO.

ALL BLM CORNERS USED ON THIS SURVEY WERE VERIFIED AND ACCEPTED BY ME, HOWEVER, THE BLM BEARING TREES WERE NOT TIED BUT WERE CHECKED IN THE FIELD.

ALL FOUND CORNERS WITH USFS MONUMENTS SET BY ME LS5623 WERE SET IN A 1997 SURVEY REQUESTED BY THE US FOREST SERVICE FOR THE ROCK ISLAND TIMBER SALE. AT THE END OF 1997 I RETIRED WITH THE PROMISE THAT THE RECORD MAP WOULD BE DRAFTED AND RECORDED. THE MAP WAS NEVER FINISHED AND WAS NOT RECORDED THEREFORE I HAVE INCLUDED THESE CORNERS ON THIS SURVEY. William Snow LS 5623

RECORD OF SURVEY

SECTIONS 27,28,19,29 T23N,R6E,MDM
PLUMAS COUNTY, CALIFORNIA

FOR

U.S.D.A. PLUMAS NATIONAL FOREST
159 LAWRENCE ST
QUINCY, CA. 95971

DRAWN BY: B. SNOW DATE: DECEMBER 2011 SHEET 4 OF 4